# [MC-DPLNAT-Diff]:

# **DirectPlay 8 Protocol: NAT Locator**

#### **Intellectual Property Rights Notice for Open Specifications Documentation**

- Technical Documentation. Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- Copyrights. This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the Open Specifications documentation.
- No Trade Secrets. Microsoft does not claim any trade secret rights in this documentation.
- Patents. Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft <u>Open</u> <u>Specifications Promise</u> or the <u>Microsoft Community Promise</u>. If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- License Programs. To see all of the protocols in scope under a specific license program and the associated patents, visit the <u>Patent Map</u>.
- Trademarks. The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- Fictitious Names. The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights**. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools**. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact <u>dochelp@microsoft.com</u>.

# **Revision Summary**

Date	Revision History	Revision Class	Comments
8/10/2007	0.1	Major	Initial Availability
9/28/2007	0.2	Minor	Clarified the meaning of the technical content.
10/23/2007	0.2.1	Editorial	Changed language and formatting in the technical content.
11/30/2007	1.0	Major	Updated and revised the technical content.
1/25/2008	1.0.1	Editorial	Changed language and formatting in the technical content.
3/14/2008	2.0	Major	Updated and revised the technical content.
5/16/2008	2.0.1	Editorial	Changed language and formatting in the technical content.
6/20/2008	2.1	Minor	Clarified the meaning of the technical content.
7/25/2008	2.2	Minor	Clarified the meaning of the technical content.
8/29/2008	2.2.1	Editorial	Changed language and formatting in the technical content.
10/24/2008	2.3	Minor	Clarified the meaning of the technical content.
12/5/2008	3.0	Major	Updated and revised the technical content.
1/16/2009	3.0.1	Editorial	Changed language and formatting in the technical content.
2/27/2009	4.0	Major	Updated and revised the technical content.
4/10/2009	4.1	Minor	Clarified the meaning of the technical content.
5/22/2009	4.2	Minor	Clarified the meaning of the technical content.
7/2/2009	4.2.1	Editorial	Changed language and formatting in the technical content.
8/14/2009	4.2.2	Editorial	Changed language and formatting in the technical content.
9/25/2009	4.3	Minor	Clarified the meaning of the technical content.
11/6/2009	4.3.1	Editorial	Changed language and formatting in the technical content.
12/18/2009	4.3.2	Editorial	Changed language and formatting in the technical content.
1/29/2010	5.0	Major	Updated and revised the technical content.
3/12/2010	5.0.1	Editorial	Changed language and formatting in the technical content.
4/23/2010	6.0	Major	Updated and revised the technical content.
6/4/2010	7.0	Major	Updated and revised the technical content.
7/16/2010	8.0	Major	Updated and revised the technical content.
8/27/2010	8.1	Minor	Clarified the meaning of the technical content.
10/8/2010	8.1	None	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	8.1	None	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
1/7/2011	8.1	None	No changes to the meaning, language, or formatting of the technical content.
2/11/2011	8.1	None	No changes to the meaning, language, or formatting of the technical content.
3/25/2011	8.1	None	No changes to the meaning, language, or formatting of the technical content.
5/6/2011	8.1	None	No changes to the meaning, language, or formatting of the technical content.
6/17/2011	8.2	Minor	Clarified the meaning of the technical content.
9/23/2011	8.2	None	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	9.0	Major	Updated and revised the technical content.
3/30/2012	9.0	None	No changes to the meaning, language, or formatting of the technical content.
7/12/2012	9.0	None	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	9.0	None	No changes to the meaning, language, or formatting of the technical content.
1/31/2013	9.0	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	10.0	Major	Updated and revised the technical content.
11/14/2013	10.0	None	No changes to the meaning, language, or formatting of the technical content.
2/13/2014	10.0	None	No changes to the meaning, language, or formatting of the technical content.
5/15/2014	10.0	None	No changes to the meaning, language, or formatting of the technical content.
6/30/2015	11.0	Major	Significantly changed the technical content.
10/16/2015	11.0	None	No changes to the meaning, language, or formatting of the technical content.
7/14/2016	11.0	None	No changes to the meaning, language, or formatting of the technical content.
6/1/2017	11.0	None	No changes to the meaning, language, or formatting of the technical content.
9/15/2017	12.0	Major	Significantly changed the technical content.
9/12/2018	13.0	Major	Significantly changed the technical content.
4/7/2021	<u>14.0</u>	Major	Significantly changed the technical content.

# **Table of Contents**

1 Intro	oduction	6
1.1	Glossary	6
1.2	References	7
1.2.1		
1.2.2	2 Informative References	7
1.3	Overview	8
1.4	Relationship to Other Protocols	8
1.5	Prerequisites/Preconditions	
1.6	Applicability Statement	8
1.7	Versioning and Capability Negotiation	9
1.8	Vendor-Extensible Fields	
1.9	Standards Assignments	
<b>D</b>	-	
	sages1	
2.1	Transport1	
2.2	Message Syntax	
2.2.1		
2.2.2		
2.2.3		
2.2.4	NAT_RESOLVER_RESPONSE 1	2
3 Prot	ocol Details1	3
3.1	Path Test Details	
3.1.1		
3.1.2		
3.1.3		
3.1.4		
3.1.5	5 / 55	
3.1.6		
3.1.7		
3.2	NAT Resolver Response Server Details	6
3.2.1		
3.2.2		
3.2.3		
3.2.4		
3.2.5		
3.2.6		
3.2.7		
3.3	NAT Resolver Query Client Details	
3.3.1		
3.3.2		
3.3.3		
3.3.4		-
3.3.5		
3.3.6	5 1 5	
3.3.7		
	ocol Examples1	
4.1	Example NAT Resolver Query and Response 1	
4.2	(Updated Section) Example PATH_TEST Message 1	8
5 Secu	ırity2	1
5.1	Security Considerations for Implementers	
5.2	Index of Security Parameters	
6 (Upo	lated Section) Appendix A: Product Behavior2	2

7	Change Tracking2	23
8	Index2	24

# **1** Introduction

This specification pertains to the DirectPlay 8 Protocol and describes technology available for the support of network environments that involve Network Address Translation (NAT). The NAT location functionality consists of extensions to the DirectPlay 8 Core and Service Providers Protocol [MC-DPL8CS] to improve NAT [RFC3022] support.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

#### 1.1 Glossary

This document uses the following terms:

- **DirectPlay**: A network communication library included with the Microsoft DirectX application programming interfaces. DirectPlay is a high-level software interface between applications and communication services that makes it easy to connect games over the Internet, a modem link, or a network.
- **DPNID**: A 32-bit identification value assigned to a DirectPlay player as part of its participation in a DirectPlay game session.
- **game session**: The metadata associated with the collection of computers participating in a single instance of a computer game.
- **globally unique identifier (GUID)**: A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [RFC4122] or [C706] must be used for generating the GUID. See also universally unique identifier (UUID).
- **host**: In DirectPlay, the computer responsible for responding to DirectPlay game session enumeration requests and maintaining the master copy of all the player and group lists for the game. One computer is designated as the host of the DirectPlay game session. All other participants in the DirectPlay game session are called peers. However, in peer-to-peer mode the name table entry representing the host of the session is also marked as a peer.
- **Internet Protocol security (IPsec)**: A framework of open standards for ensuring private, secure communications over Internet Protocol (IP) networks through the use of cryptographic security services. IPsec supports network-level peer authentication, data origin authentication, data integrity, data confidentiality (encryption), and replay protection.
- **Internet Protocol version 4 (IPv4)**: An Internet protocol that has 32-bit source and destination addresses. IPv4 is the predecessor of IPv6.
- **little-endian**: Multiple-byte values that are byte-ordered with the least significant byte stored in the memory location with the lowest address.
- **network address translation (NAT)**: The process of converting between IP addresses used within an intranet, or other private network, and Internet IP addresses.
- **network byte order**: The order in which the bytes of a multiple-byte number are transmitted on a network, most significant byte first (in big-endian storage). This may or may not match the order in which numbers are normally stored in memory for a particular processor.
- **payload**: The data that is transported to and from the application that is using either the DirectPlay 4 protocol or DirectPlay 8 protocol.

- **peer**: In DirectPlay, a player within a DirectPlay game session that has an established connection with every other peer in the game session, and which is not performing game session management duties. The participant that is managing the game session is called the host.
- **player**: A person who is playing a computer game. There can be multiple players on a computer participating in any given game session. See also name table.
- **private address**: An Internet Protocol version 4 (IPv4) address that is not globally routable, but is part of the private address space specified in [RFC1918] section 3.
- **public address**: An external global address used by a network address translation (NAT).
- **User Datagram Protocol (UDP)**: The connectionless protocol within TCP/IP that corresponds to the transport layer in the ISO/OSI reference model.
- **MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

#### 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

#### **1.2.1** Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[FIPS180] FIPS PUBS, "Secure Hash Standard", FIPS PUB 180-1, April 1995, http://niatec.info/GetFile.aspx?pid=63

[MC-DPL8CS] Microsoft Corporation, "DirectPlay 8 Protocol: Core and Service Providers".

[MC-DPL8R] Microsoft Corporation, "DirectPlay 8 Protocol: Reliable".

[MS-DTYP] Microsoft Corporation, "Windows Data Types".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, http://www.rfc-editor.org/rfc/rfc2119.txt

#### **1.2.2 Informative References**

[RFC3022] Srisuresh, P., and Egevang, K., "Traditional IP Network Address Translator (Traditional NAT)", RFC 3022, January 2001, http://www.ietf.org/rfc/rfc3022.txt

[RFC4380] Huitema, C., "Teredo: Tunneling IPv6 over UDP through Network Address Translations (NATs)", RFC 4380, February 2006, http://www.ietf.org/rfc/rfc4380.txt

[RFC768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, August 1980, http://www.rfc-editor.org/rfc/rfc768.txt

[UPNPWANIP] UPnP Forum, "WANIPConnection:1", November 2001, http://www.upnp.org/standardizeddcps/documents/UPnP\_IGD\_WANIPConnection%201.0.pdf

### 1.3 Overview

The DirectPlay 8 Protocol: NAT Locator consists of three separate packet types: path tests, Network Address Translation (NAT) resolver queries, and NAT resolver responses. These optional messages are used to modify behavior of the DirectPlay 8 Core and Service Providers Protocol [MC-DPL8CS] connection process so as to increase support for network environments that involve NAT. They are not required for operation of the DirectPlay 8 Core and Service Providers Protocol.

Path tests are packets used to augment the DirectPlay 8 Protocol: Core and Service Providers connection process. While an existing participant is initiating a connection to a new player in response to a DN\_MSG\_INTERNAL\_INSTRUCT\_CONNECT message from the host, it can configure itself to accept PATH\_TEST messages from the new player. Similarly, the new player can begin to periodically send PATH\_TEST messages to the existing players from which it expects to receive connection attempts. These PATH\_TEST messages are used to create port mappings in NAT or firewall devices that would otherwise prevent the DirectPlay 8 Protocol: Core and Service Providers connection from succeeding.

NAT resolver queries and responses are part of an out-of-band mechanism to enable DirectPlay 8 Protocol: Core and Service Providers hosts to acquire additional addressing information that they can provide to potential clients to improve connectivity in specific, limited NAT scenarios. They enable hosts to create port mappings in NAT or firewall devices and identify the resulting public address and port. This public address and port can then be advertised instead of the local, private address and port that hosts normally would advertise.

#### **1.4** Relationship to Other Protocols

The DirectPlay 8 Protocol: NAT Locator depends on the User Datagram Protocol (UDP) [RFC768] and Internet Protocol version 4 (IPv4). The extensions provided in the DirectPlay 8 Protocol: NAT Locator are implemented in conjunction with the DirectPlay 8 Protocol: Core and Service Providers, and nominally the DirectPlay 8 Protocol: Reliable and the DirectPlay 8 Protocol: Host and Port Enumeration.

No other protocols depend on the presence of the DirectPlay 8 Protocol: NAT Locator extensions.

It is not recommended that NAT resolver queries be performed when a Universal Plug-and-Play (UPnP) Internet Gateway Device (IGD) is configured with a port mapping; instead, the UPnP port mapping takes precedence [UPNPWANIP].

#### 1.5 Prerequisites/Preconditions

The DirectPlay 8 Protocol: NAT Locator extensions assume that a DirectPlay 8 Protocol: Core and Service Providers game session has been established, and that a peer is attempting to join a game session with the host and at least one other existing peer.

The NAT resolver query/response client/server transaction requires that the responding server be configured with a public or global Internet address. The server's direct network access is necessary to respond properly to queries from clients that are behind any devices that perform NAT. The NAT resolver query/response exchange can be performed at any time, but typically occurs when a DirectPlay 8 Protocol: Core and Service Providers host has started.

#### 1.6 Applicability Statement

DirectPlay is designed for multiplayer gaming scenarios. These extensions can be used when additional NAT traversal support is desired for a DirectPlay 8 Protocol: Core and Service Providers gaming game session.

These extensions are used when running over IPv4. They are not to be implemented using IPv6. Instead, mechanisms such as the Teredo tunneling specification [RFC4380] address NAT traversal more generically under that protocol.

# 1.7 Versioning and Capability Negotiation

None.

#### **1.8 Vendor-Extensible Fields**

None.

#### 1.9 Standards Assignments

None.

# 2 Messages

This protocol references commonly used data types as defined in [MS-DTYP].

#### 2.1 Transport

DirectPlay 8 Protocol: NAT Locator messages MUST be transported by using UDP. The source and destination port numbers are application specific and can be any value.

#### 2.2 Message Syntax

This section describes the format of messages and pseudo-structures used in the DirectPlay 8 Protocol: NAT Locator.

This protocol specification uses curly braced GUID strings as specified in [MS-DTYP] section 2.3.4.3.

### 2.2.1 PATHTESTKEYDATA

The PATHTESTKEYDATA is a pseudo-structure that is hashed to generate 64-bit key values.

0	1	2	3	4	5	6	7	8	9	1 0	1	2	3	4	5	6	7	8	9	2 0	1	2	3	4	5	6	7	8	9	3 0	1
														dpr	nidS	Sen	der														
														dp	nid⁻	Targ	get														
												gui	dAp	plic	atio	on (	[16	byt	es)												
												gı	ıidI	nsta	ance	e (1	.6 b	yte	s)												

**dpnidSender (4 bytes):** The 32-bit DPNID value identifying the sending player, in little-endian byte order.

- **dpnidTarget (4 bytes):** The 32-bit DPNID value identifying the intended recipient player, in littleendian byte order.
- **guidApplication (16 bytes):** The 128-bit GUID value identifying the DirectPlay 8 Protocol: Core and Service Providers application.
- **guidInstance (16 bytes):** The 128-bit GUID value identifying the particular DirectPlay 8 Protocol: Core and Service Providers game session instance.

### 2.2.2 PATH\_TEST

The PATH_TEST messages are sent to trigger outbound NAT and firewall mappings.
--

0	1	2	3	4	5	6	7	8	9	1 0	1	2	3	4	5	6	7	8	9	2 0	1	2	3	4	5	6	7	8	9	3 0	1
	bZero bCommand wMessageID																														
	ullKey																														

- **bZero (1 byte):** An 8-bit identifier used to distinguish this message from DirectPlay 8 Protocol: Reliable messages to the same UDP port. It MUST be set to 0.
- **bCommand (1 byte):** An 8-bit command code identifying this message as a path test message. It MUST be set to 0x05, PATH\_TEST\_DATA\_KIND (Path Test message type).
- **wMessageID (2 bytes):** A 16-bit value used to uniquely identify an individual PATH\_TEST message. This can be any value desired by the sender and MUST be ignored by the receiver. It SHOULD change each time a PATH\_TEST message is retried.
- **ullKey (8 bytes):** A 64-bit digest value used to validate the PATH\_TEST message. This MUST be generated by using the procedure outlined in section 3.1.3 and MUST be validated by the receiver prior to acting on it.

#### 2.2.3 NAT\_RESOLVER\_QUERY

The NAT\_RESOLVER\_QUERY is sent to retrieve translated address information.

0	1	2	3	4	5	6	7	8	9	1 0	1	2	3	4	5	6	7	8	9	2 0	1	2	3	4	5	6	7	8	9	3 0	1
			bΖ	ero						bC	Com	ma	nd									wM	less	sage	eID						
														dw	Soι	irce	ID														
													Use	erDa	ata	(va	riat	ole)													
						UserData (variable)																									

- **bZero (1 byte):** An 8-bit identifier used to distinguish this message from DirectPlay 8 Protocol: Reliable messages to the same UDP port. It MUST be set to 0.
- **bCommand (1 byte):** An 8-bit command code identifying this message as a NAT Resolver Query message. It MUST be set to 0x06, NAT\_RESOLVER\_QUERY\_DATA\_KIND (NAT Resolver Query message type).
- **wMessageID (2 bytes):** A 16-bit value used by the sender to uniquely identify an individual NAT Resolver Query message. This can be any value desired by the sender and MUST be echoed in the response message by the receiver. It SHOULD change each time a query message is retried.
- **dwSourceID (4 bytes):** A 32-bit value used by the sender to identify the source of a NAT Resolver Query message. This can be any value desired by the sender and MUST be echoed in the response message by the receiver.

**UserData (variable):** An optional, variable length field containing an application-specific query payload. The size of the **UserData** field is determined by the remaining size of the UDP packet. If a receiver determines that there are no more bytes after the complete NAT\_RESOLVER\_QUERY message header, then the **UserData** field was omitted by the sender.

# 2.2.4 NAT\_RESOLVER\_RESPONSE

The NAT\_RESOLVER\_RESPONSE is sent to report translated address information to the sender of a previous query.

	1																														1
					_					1										2										3	
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
			bΖ	ero						bC	Com	ma	nd								w	Mes	sag	JeIC	DEcl	ho					
													d١	«So	ourc	eID	Ecł	10													
													d	WIF	۷4 <i>،</i>	Add	res	s													
	dwI wPort																														

- **bZero (1 byte):** An 8-bit identifier used to distinguish this message from DirectPlay 8 Protocol: Reliable messages to the same UDP port. It MUST be set to 0.
- **bCommand (1 byte):** An 8-bit command code identifying this message as a NAT Resolver Response message. It MUST be set to 0x07, NAT\_RESOLVER\_RESPONSE\_DATA\_KIND (NAT Resolver Response message type).
- wMessageIDEcho (2 bytes): A 16-bit value used to uniquely identify a response to an individual NAT Resolver Query message. This MUST be set to the value of wMessageID in the query to which this message is a response.
- **dwSourceIDEcho (4 bytes):** A 32-bit value used by the sender to identify the original source to which the NAT resolver response is replying. This MUST be set to the value of **dwSourceID** in the query to which this message is a response.
- **dwIPv4Address (4 bytes):** A 32-bit value indicating the public IPv4 address of the sender of the NAT resolver query. This value MUST be set to the source IPv4 address of the query UDP packet, in Network Byte Order, modified by using the exclusive-or (XOR) bitwise operation with the value of the **dwSourceID** query field.
- wPort (2 bytes): A 16-bit value indicating the public port number of the sender of the NAT resolver query. This value MUST be set to the source port number of the query UDP packet, in Network Byte Order, modified by using the exclusive-or (XOR) bitwise operation with the value of the wMessageID query field.

# **3** Protocol Details

# 3.1 Path Test Details

# 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This specification does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this specification.

- **dpnidSender:** The 32-bit DPNID value identifying the new Path Test-sending player, in little-endian byte order.
- **dpnidTarget:** The 32-bit DPNID value identifying the existing player, in little-endian byte order.
- **guidApplication:** The 128-bit GUID value identifying the DirectPlay 8 Protocol: Core and Service Providers application.
- **guidInstance:** The 128-bit GUID value identifying the particular DirectPlay 8 Protocol: Core and Service Providers game session instance.
- **ullKey:** The 64-bit identification value used to correlate PATH\_TEST messages and DirectPlay 8 Protocol: Core and Service Providers connect attempts.

#### 3.1.2 Timers

The **Retry Timer** is used to periodically resend PATH\_TEST messages to compensate for potential packet loss. It SHOULD retry at intervals of 375 milliseconds with a maximum of 7 attempts, but can use any settings required for the particular application and network circumstances.

#### 3.1.3 Initialization

The DirectPlay 8 Protocol: NAT Locator extensions SHOULD be initialized whenever the DirectPlay 8 Protocol: Core and Service Providers begins connecting an existing peer to a new peer that is attempting to join the game session. For an existing peer, the connection starts when the existing peer receives the DN\_INSTRUCT\_CONNECT message and responds to the message by initiating the connection. For the new peer, the connection starts when the new peer receives the DN\_SEND\_CONNECT\_INFO message and responds to the message by preparing to accept the connection.

To use Path Tests, both peers MUST fill in a PATHTESTKEYDATA pseudo-structure with the following:

dpnidSender: Set to the DPNID of the new peer, in little-endian byte order.

**dpnidTarget:** Set to the DPNID of the existing peer, in little-endian byte order. For the new peer, the value of the **dpnidTarget** field is part of the DN\_SEND\_CONNECT\_INFO message described in [MC-DPL8CS] section 2.2.1.4.

guidApplication: Set to the DirectPlay 8 Protocol: Core and Service Providers application GUID.

**guidInstance:** Set to the DirectPlay 8 Protocol: Core and Service Providers game session instance GUID.

Both peers MUST then generate a SHA-1 digest, as specified in [FIPS180], of the PATHTESTKEYDATA binary data, and use the first 64 bits of the output value as the Path Test key value **ullKey**.

For the existing peer, the value of the calculated **ullKey** ADM element MUST remain associated with the connection attempt that the peer is performing until either the attempt fails, the attempt completes successfully, or the peer receives a valid PATH\_TEST message as described in section 3.1.5. Also at this time, the existing peer MUST prepare to accept PATH\_TEST messages in response to its instructed peer connection, in addition to the standard [MC-DPL8CS] and [MC-DPL8R] connection responses.

For the new peer, this value MUST be used in the periodic transmission of PATH\_TEST messages as described in section 3.1.6. Also at this time, the Path Test **Retry Timer** MUST be initialized. This process SHOULD be repeated for each existing peer as described in the DN\_SEND\_CONNECT\_INFO message ([MC-DPL8CS] section 2.2.1.4).

# 3.1.4 Higher-Layer Triggered Events


The DirectPlay 8 Protocol: Core and Service Providers SHOULD inform the DirectPlay 8 Protocol: NAT Locator when the connection attempt has completed, whether it was successful or not. The existing peer MUST stop listening for PATH\_TEST messages, and the new peer MUST stop transmitting PATH\_TEST messages at that time.

### 3.1.5 Processing Events and Sequencing Rules

When the existing peer receives a valid PATH\_TEST message, it MUST search all its outstanding [MC-DPL8CS] and corresponding [MC-DPL8R] instructed peer connections (described in [MC-DPL8CS] section 3.1.5.2) for one that has a matching **ullKey** value as described in section 3.1.3. If found, and the connect attempt has not yet received any packets from the intended target IPv4 address and port, the connection target SHOULD be modified to be the source IPv4 address and port of the PATH\_TEST message.

If no connect attempt is associated with a matching **ullKey** value, or a matching connect attempt already has received one or more packets, the existing peer MUST ignore the PATH\_TEST message.

If the message is not properly formed as described in section 2.2.2, the existing peer MUST ignore the PATH\_TEST message.



#### Figure 1: New peer's PATH\_TEST during connect attempt from existing peer

PATH\_TEST messages are used to create mappings in NAT and firewall devices so that inbound connect attempts appear to be solicited responses to a previous outbound request through the steps identified in this section. This process assumes that the host has sent the list of existing peers to the new peer, and that the host instructs the existing peer to connect to the new peer as described in [MC-DPL8CS].

- 1. The existing peer initiates a reliable protocol connection with a CONNECT message as described in [MC-DPL8R] section 2. This can be dropped by the public interface of the NAT or firewall device based on its particular filtering or port assignment policy.
- Simultaneously, the **Retry Timer** of the new peer can elapse and cause transmission of a PATH\_TEST message as described in section 3.1.6. The NAT or firewall device can implicitly create a mapping between the private address of the new peer and the public address it uses to forward the message to the existing peer.
- 3. The existing peer can receive the PATH\_TEST message and alter the destination IPv4 address and/or port for future CONNECT message retries, if the NAT device assigned a different port number from that which had originally been tried.
- 4. Because of the NAT or firewall mapping, the retried CONNECT messages can now be properly forwarded to the new peer, and the new peer can proceed with the [MC-DPL8R] CONNECTED response and the rest of the standard connection process.

If the new peer or host receives a PATH\_TEST message, it MUST be silently ignored.

#### 3.1.6 Timer Events

When the **Retry Timer** elapses, the new peer MUST send a new PATH\_TEST message to the IPv4 address and port of the existing peer for which it is expecting a connection. This message MUST be

sent from the same UDP port number on which it is expecting the connection. If fewer than the maximum number of attempts have been made, the timer MUST then be rescheduled so that it can elapse again. Otherwise, the retries have been exhausted and the Path Test operation SHOULD be canceled.

### 3.1.7 Other Local Events

None.

# 3.2 NAT Resolver Response Server Details

#### 3.2.1 Abstract Data Model

None.

#### 3.2.2 Timers

None.

#### 3.2.3 Initialization

None.

### 3.2.4 Higher-Layer Triggered Events

NAT Resolver Response Servers are not required to interact with higher-layers beyond initializing and shutting down.

#### 3.2.5 Processing Events and Sequencing Rules

When a NAT Resolver Response server receives a NAT\_RESOLVER\_QUERY message, it can validate the optional **UserData** field by using application-specific logic. If the query is properly formed as described in section 2.2.3 and application-specific logic accepts the contents of the optional **UserData** field, the NAT Resolver MUST respond with a NAT\_RESOLVER\_RESPONSE message to the sender's target IPv4 address and port. The response MUST contain the query's **WMessageID** and **dwSourceID** fields echoed in the corresponding **wMessageIDEcho** and **dwSourceIDEcho** fields. It MUST also set the source IPv4 address of the query in the dwIPv4Address field, in network byte order, and the source port number of the query in the wPort field. Both of these fields MUST also be modified by using **dwSourceID** and **wMessageID**, respectively, with the exclusive-or (XOR) bitwise operation.

If the NAT\_RESOLVER\_QUERY message is not properly formed as described in section 2.2.3, or application-specific logic rejects the contents of the optional **UserData** field, the server MUST ignore the message.

If the server receives a NAT\_RESOLVER\_RESPONSE message, it MUST be silently ignored.

#### 3.2.6 Timer Events

None.

#### 3.2.7 Other Local Events

None.

### 3.3 NAT Resolver Query Client Details

### 3.3.1 Abstract Data Model

None.

#### 3.3.2 Timers

The **Retry Timer** is used to periodically resend NAT\_RESOLVER\_QUERY messages to compensate for potential packet loss. It SHOULD retry at intervals of 1 second with a maximum of four attempts, but can use any settings required for the particular application and network circumstances.

### 3.3.3 Initialization

The NAT Resolver Query client can be initialized whenever the DirectPlay 8 Protocol: Core and Service Providers begins hosting a new game session. Initialization consists of scheduling the **Retry Timer**.

### 3.3.4 Higher-Layer Triggered Events

The DirectPlay 8 Protocol: Core and Service Providers SHOULD inform the NAT Resolver Query client when it is no longer the host of a game session. The manner in which the provider notifies the client is implementation-specific and is not influenced by the configuration of this protocol nor the DirectPlay 8 Protocol: Core and Service Providers protocol.

When a client is notified that it is no longer the host in the game session, the client MUST abort any query attempts currently in progress.

#### 3.3.5 Processing Events and Sequencing Rules

When a client receives a NAT\_RESOLVER\_RESPONSE message, it SHOULD validate that **wMessageIDEcho** and **dwSourceIDEcho** correspond to values that it sent in a previous NAT\_RESOLVER\_QUERY message's **wMessageID** and **dwSourceID** fields. If not, the packet MUST be silently ignored. Otherwise, the client SHOULD reverse the exclusive-or (XOR) bitwise operation performed on the **dwIPv4Address** and **wPort** fields, and save the resulting address and port information for use in advertising the DirectPlay 8 Protocol: Core and Service Providers game session. The **Retry Timer** SHOULD then be canceled.

If the NAT\_RESOLVER\_RESPONSE message is not properly formed as described in section 2.2.4, the client MUST ignore the message.

If a client receives a NAT\_RESOLVER\_QUERY message, it MUST be silently ignored.

#### 3.3.6 Timer Events

When the **Retry Timer** elapses, the client MUST send a new NAT\_RESOLVER\_QUERY message to the server. This message MUST be sent from the same UDP port number on which it is the host of the DirectPlay 8 Protocol: Core and Service Providers game session. If fewer than the maximum number of attempts have been made, the timer MUST then be rescheduled so that it can elapse again. Otherwise, the retries have been exhausted and the NAT Resolver Query operation SHOULD be canceled.

#### 3.3.7 Other Local Events

None.

# 4 Protocol Examples

#### 4.1 Example NAT Resolver Query and Response

The following example has two participants:

- The server IPv4 address 65.52.10.10, port 2506.
- The client IPv4 address 192.168.1.2, port 2302. Network Address Translation (NAT) will remap the client's packets as IPv4 address 65.52.252.61.

The client issues a NAT\_RESOLVER\_QUERY message to the server (that is, from 192.168.1.2:2302 to 65.52.10.10:2506) with a value of 54769 (0xD5F1) for the **wMessageID** field and a value of 3125876284 (0xBA51163C) for the **dwSourceID** field, as seen in the following frame contents (Ethernet, IPv4, and UDP headers included):

The NAT device remaps the source address and port for the message from 192.168.1.2:2302 to 65.52.252.61:2302. The NAT resolver server receives the message and sends a NAT\_RESOLVER\_RESPONSE message back to that address. The reply contains the XOR-obfuscated address, as well as the echoed values from the query. The NAT device at 65.52.252.61 maps the destination address and port of the reply to 192.168.1.2:2302 so the client can receive the message, as seen in the following frame contents (Ethernet, IPv4, and UDP headers included):

 0000
 00
 1D
 92
 37
 5E
 40
 00
 0F
 B5
 95
 C3
 C8
 00
 45
 00
 ...7^@..µ.ÃÈ..E.

 0010
 00
 2A
 42
 F2
 00
 00
 7C
 11
 E7
 02
 41
 34
 0A
 0A
 C0
 A8
 ...50...].ç..ÂA4..."

 0020
 01
 02
 09
 CA
 08
 FE
 00
 10
 45
 00
 07
 F1
 D5
 3C
 16
 ...Ê.b...E..ñÕ<.</td>

 0030
 51
 BA
 7D
 22
 AD
 87
 F9
 2B
 Q° }"¬.ù+

The client validates the reply and then de-obfuscates the public address and port included in the message. The client can display, advertise, or otherwise use its newly learned public address as appropriate.

#### 4.2 (Updated Section) Example PATH\_TEST Message

The following example has three participants:

- PlayerA The host, IPv4 address 192.168.1.3, port 2505.
- PlayerB An existing peer, IPv4 address 10.194.72.68, port 2302.
- PlayerC The joining peer, IPv4 address 192.168.1.2, port 2302. PlayerC has local firewall software installed which prevents unsolicited inbound UDP messages.

For the purposes of this example, the following assumptions are made:

- PlayerA has created a game session that uses an application GUID {02AE835D-9179-485F-8343-901D327CE794} and an instance GUID {C0A65D4F-9CE3-4F70-80DE-3AB4DF6F09B6}, as described in [MC-DPL8CS].
- PlayerB has already joined PlayerA's game session and was assigned the DPNID value 0xC0965D4C, as described in [MC-DPL8CS].

 PlayerC is in the process of joining the game session and previously exchanged the following messages with PlayerA as described in [MC-DPL8R] and [MC-DPL8CS]:

Source: 192.168.1.2:2302, Dest: 192.168.1.3:2505, Type: MC-DPL8R CONNECT Source: 192.168.1.3:2505, Dest: 192.168.1.2:2302, Type: MC-DPL8R CONNECTED Source: 192.168.1.2:2302, Dest: 192.168.1.3:2505, Type: MC-DPL8R CONNECTED Source: 192.168.1.2:2302, Dest: 192.168.1.3:2505, Type: MC-DPL8CS DN INTERNAL MESSAGE PLAYER CONNECT\_INFO Source: 192.168.1.3:2505, Dest: 192.168.1.2:2302, Type: MC-DPL8CS DN SEND\_CONNECT\_INFO, assigning DPNID 0xCOF65D4B to PlayerC Source: 192.168.1.2:2302, Dest: 192.168.1.3:2505, Type: MC-DPL8CS DN\_ACK\_CONNECT\_INFO

 PlayerA has also already sent the following messages to PlayerB regarding the joining PlayerC as described in [MC-DPL8CS].

Source: 192.168.1.3:2505, Dest: 10.194.72.68:2302, Type: MC-DPL8CS DN\_ADD\_PLAYER Source: 192.168.1.3:2505, Dest: 10.194.72.68:2302, Type: MC-DPL8CS DN INSTRUCT CONNECT

PlayerB now initiates an instructed connect to PlayerC, beginning with the CONNECT packet described in [MC-DPL8R] section 2.2.1.1, as seen in the following frame contents (Ethernet, IPv4, and UDP headers included):

 0000
 00
 1D
 92
 37
 5E
 40
 00
 0F
 B5
 95
 C3
 C8
 08
 00
 45
 00
 ...
 7^@...µ ÃÈ..E.

 0010
 00
 2C
 12
 D8
 00
 00
 7C
 11
 00
 00
 0A
 C2
 48
 44
 C0
 A8
 ...µ ÃÈ..E.
 ...µ ÃÈ..E.

 0020
 01
 02
 08
 FE
 00
 18
 21
 EF
 88
 01
 00
 06
 00
 ...p.p..!ü
 ....p.p..!ü
 ...ä. °PäÊ2.

The CONNECT packet arrives at PlayerC, but is rejected by the firewall because it does not have a mapping between local port 2302 and remote address 10.194.72.68:2302.Concurrent with the attempt by PlayerB to connect to PlayerC, PlayerC issues a PATH\_TEST message to PlayerB using a message ID 0xD0C1 and key value 0xF9AFE99C92DD82B8 (due to the DNPIDs and GUIDs described above). This results in the following frame contents (Ethernet, IPv4, and UDP headers included):

 0000
 00 0F B5 95 C3 C8 00 1D 92 37 5E 40 08 00 45 00
 ...µ•ÃÈ...'7^@..E.

 0010
 00 28 1C 45 00 00 80 11 09 D0 C0 A8 01 02 0A C2
 ...µ•ÃÈ...'7^@..E.

 0020
 48 44 08 FE 08 FE 00 14 34 4B 00 05 C1 D0 B8 82
 HD.p.p..4K..ÁĐ,,

 0030
 DD 92 9C E9 AF F9
 Ý'œÉ ù

This outbound packet implicitly establishes a firewall mapping between local port 2302 and remote address 10.194.72.68:2302. PlayerB receives this PATH\_TEST message, but PlayerB does not need to perform any of the optional state modifications described in section 3.1.5. In this example, there is no network address translation occurring, and therefore, there is no difference between the port to which the CONNECT packet was sent and the actual port that maps back to PlayerC.PlayerB now attempts to resend the CONNECT packet to PlayerC as described in [MC-DPL8R] section 2.2.1.1 (Ethernet, IPv4, and UDP headers included):

0000 00 1D 92 37 5E 40 00 0F B5 95 C3 C8 08 00 45 00 ... 7^@..μ ÃÈ..Ε.

0010	00 2	2C 12	D9	00	00	7C	11	00	00	0A	C2	48	44	C0	A8	.P.Ù ÂHDÀ"
0020	01 (	02 08	FΕ	08	FΕ	00	18	21	ΕF	88	01	01	00	06	00	þ.þ!ï
0030	01 (	00 E4	1C	вO	50	E4	CA	32	00							ä.°PäÊ2.

This time a firewall mapping exists, and the CONNECT packet is allowed to reach PlayerC. PlayerC responds with a CONNECTED packet as described in [MC-DPL8R] section 2.2.1.1, and continues with the peer connection sequence described in [MC-DPL8R] and [MC-DPL8CS]:

Source: 192.168.1.2, Destination: 10.194.72.68, Type: MC-DPL8R CONNECTED Source: 10.194.72.68, Destination: 192.168.1.2, Type: MC-DPL8R CONNECTED Source: 10.194.72.68, Destination: 192.168.1.2, Type: MC-DPL8CS DN\_SEND\_PLAYER\_DPNID

# 5 Security

#### 5.1 Security Considerations for Implementers

This protocol uses the SHA-1 hashing algorithm, which has been shown to have weaknesses [FIPS180]. However, the protocol is not intended for use in applications that demand robust security without Internet Protocol security (IPsec) or other lower-level security mechanisms already in place.

#### 5.2 Index of Security Parameters

Security parameter	Section
SHA-1 digest	3.1.3

# 6 (Updated Section) Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Windows Vista operating system
- Windows Server 2008 operating system
- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows 8 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system
- Windows Server 2016 operating system
- Windows Server 2019 operating system

#### Windows Server 2022 operating system

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

# 7 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
6 Appendix A: Product Behavior	Updated for this version of Windows Server.	Major

# 8 Index

#### A

Abstract data model client 17 client - NAT resolver query 17 path test 13 server 16 server - NAT resolver response 16 Applicability 8

# С

```
Capability negotiation 9
Change tracking 23
Client
  abstract data model 17
  higher-layer triggered events 17
  initialization 17
  other local events 17
  timer events 17
  timers 17
Client - NAT resolver query
  abstract data model 17
  higher-layer triggered events 17
  initialization 17
  local events 17
  message processing 17
  sequencing rules 17
  timer events 17
  timers 17
```

# D

Data model - abstract client 17 client - NAT resolver query 17 path test 13 server 16 server - NAT resolver response 16

# Е

```
Examples
NAT resolver
query 18
response 18
PATH_TEST message 18
```

#### F

Fields - vendor-extensible 9

#### G

Glossary 6

#### Н

Higher-layer triggered events client 17 client - NAT resolver query 17

[MC-DPLNAT-Diff] - v20210407 DirectPlay 8 Protocol: NAT Locator Copyright © 2021 Microsoft Corporation Release: April 7, 2021 path test 14 server 16 server - NAT resolver response 16

#### I

Implementer - security considerations 21 Index of security parameters 21 Informative references 7 Initialization client 17 client - NAT resolver query 17 path test 13 server 16 server - NAT resolver response 16 Introduction 6

#### L

Local events client - NAT resolver query 17 path test 16 server - NAT resolver response 16

#### Μ

Message processing client - NAT resolver query 17 path test 14 server - NAT resolver response 16 Messages NAT\_RESOLVER\_QUERY 11 NAT\_RESOLVER\_RESPONSE 12 PATH\_TEST 11 PATHTESTKEYDATA 10 syntax 10 transport 10

#### Ν

NAT\_RESOLVER\_QUERY message 11 NAT\_RESOLVER\_QUERY packet 11 NAT\_RESOLVER\_RESPONSE message 12 NAT\_RESOLVER\_RESPONSE packet 12 Normative references 7

#### 0

Other local events client 17 server 16 Overview (synopsis) 8

#### Ρ

Parameters - security index 21 Path test abstract data model 13 higher-layer triggered events 14 initialization 13 local events 16 message processing 14 sequencing rules 14 timer events 15

[MC-DPLNAT-Diff] - v20210407 DirectPlay 8 Protocol: NAT Locator Copyright © 2021 Microsoft Corporation Release: April 7, 2021 timers 13 PATH\_TEST message 11 PATH\_TEST packet 11 PATHTESTKEYDATA message 10 PATHTESTKEYDATA packet 10 Preconditions 8 Prerequisites 8 Product behavior 22

#### R

References 7 informative 7 normative 7 Relationship to other protocols 8

#### S

Security implementer considerations 21 parameter index 21 Sequencing rules client - NAT resolver query 17 path test 14 server - NAT resolver response 16 Server abstract data model 16 higher-layer triggered events 16 initialization 16 other local events 16 timer events 16 timers 16 Server - NAT resolver response abstract data model 16 higher-layer triggered events 16 initialization 16 local events 16 message processing 16 sequencing rules 16 timer events 16 timers 16 Standards assignments 9 Syntax 10

#### Т

Timer events client 17 client - NAT resolver query 17 path test 15 server 16 server - NAT resolver response 16 Timers client 17 client - NAT resolver query 17 path test 13 server 16 server - NAT resolver response 16 Tracking changes 23 Transport 10 Triggered events - higher-layer client 17 client - NAT resolver query 17 path test 14 server 16

[MC-DPLNAT-Diff] - v20210407 DirectPlay 8 Protocol: NAT Locator Copyright © 2021 Microsoft Corporation Release: April 7, 2021 server - NAT resolver response 16

#### V

Vendor-extensible fields 9 Versioning 9