

[MS-BPDP]: Background Intelligent Transfer Service (BITS) Peer- Caching: Peer Discovery Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard

specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
02/22/2007	0.1		MCPD Milestone 3 Initial Availability
06/01/2007	1.0	Major	Updated and revised the technical content.
07/03/2007	1.0.1	Editorial	Revised and edited the technical content.
07/20/2007	1.0.2	Editorial	Revised and edited the technical content.
08/10/2007	1.0.3	Editorial	Revised and edited the technical content.
09/28/2007	1.0.4	Editorial	Revised and edited the technical content.
10/23/2007	1.0.5	Editorial	Revised and edited the technical content.
11/30/2007	1.0.6	Editorial	Revised and edited the technical content.
01/25/2008	1.0.7	Editorial	Revised and edited the technical content.
03/14/2008	1.1	Minor	Updated the technical content.
05/16/2008	1.1.1	Editorial	Revised and edited the technical content.
06/20/2008	1.2	Minor	Updated the technical content.
07/25/2008	1.2.1	Editorial	Revised and edited the technical content.
08/29/2008	1.2.2	Editorial	Revised and edited the technical content.
10/24/2008	1.2.3	Editorial	Revised and edited the technical content.
12/05/2008	1.2.4	Editorial	Revised and edited the technical content.
01/16/2009	1.2.5	Editorial	Revised and edited the technical content.
02/27/2009	1.2.6	Editorial	Revised and edited the technical content.
04/10/2009	1.2.7	Editorial	Revised and edited the technical content.
05/22/2009	1.2.8	Editorial	Revised and edited the technical content.
07/02/2009	1.2.9	Editorial	Revised and edited the technical content.
08/14/2009	1.2.10	Editorial	Revised and edited the technical content.
09/25/2009	1.3	Minor	Updated the technical content.
11/06/2009	1.4	Minor	Updated the technical content.

Date	Revision History	Revision Class	Comments
12/18/2009	1.4.1	Editorial	Revised and edited the technical content.
01/29/2010	2.0	Major	Updated and revised the technical content.
03/12/2010	2.0.1	Editorial	Revised and edited the technical content.
04/23/2010	2.0.2	Editorial	Revised and edited the technical content.
06/04/2010	3.0	Major	Updated and revised the technical content.
07/16/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	3.1	Minor	Clarified the meaning of the technical content.
09/23/2011	3.2	Minor	Clarified the meaning of the technical content.
12/16/2011	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
03/30/2012	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
07/12/2012	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
01/31/2013	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
08/08/2013	3.2	No change	No changes to the meaning, language, or formatting of

Date	Revision History	Revision Class	Comments
			the technical content.
11/14/2013	3.2	No change	No changes to the meaning, language, or formatting of the technical content.
02/13/2014	3.2	No change	No changes to the meaning, language, or formatting of the technical content.

Contents

1 Introduction	7
1.1 Glossary	7
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Overview	8
1.4 Relationship to Other Protocols	9
1.5 Prerequisites/Preconditions	9
1.6 Applicability Statement	9
1.7 Versioning and Capability Negotiation	9
1.8 Vendor-Extensible Fields	10
1.9 Standards Assignments	10
2 Messages	11
2.1 Transport	11
2.2 Common Message Syntax	11
2.2.1 Namespaces	11
2.2.2 Messages	11
2.2.3 Elements	11
2.2.4 Complex Types	12
2.2.5 Simple Types	12
2.2.6 Attributes	12
2.2.7 Groups	12
2.2.8 Attribute Groups	12
3 Protocol Details	13
3.1 Server Details	13
3.1.1 Abstract Data Model	13
3.1.1.1 Protocol Metadata	13
3.1.1.2 Table of Connected Subnets	13
3.1.2 Timers	13
3.1.3 Initialization	13
3.1.4 Message Processing Events and Sequencing Rules	14
3.1.4.1 Hello	14
3.1.4.1.1 Messages	14
3.1.4.2 Bye	15
3.1.4.2.1 Messages	15
3.1.4.3 Probe	15
3.1.4.3.1 Messages	15
3.1.4.4 ProbeMatch	15
3.1.4.4.1 Messages	16
3.1.4.5 Resolve	16
3.1.4.5.1 Messages	16
3.1.4.6 ResolveMatch	16
3.1.4.6.1 Messages	17
3.1.5 Timer Events	17
3.1.6 Other Local Events	17
3.1.6.1 Shutdown	17
3.1.6.2 Add a Local IP Address	17
3.1.6.3 Remove an IP Address	18

3.2	Client Details.....	18
3.2.1	Abstract Data Model	18
3.2.1.1	Table of Subnets	18
3.2.1.2	Table of Servers	19
3.2.1.3	Tables of Server Addresses	19
3.2.1.4	Scope List.....	19
3.2.2	Timers	19
3.2.2.1	Discovery Timer	19
3.2.2.2	Discovery Suppression Timer	19
3.2.2.3	Address Scavenger Timer	20
3.2.3	Initialization	20
3.2.4	Message Processing Events and Sequencing Rules.....	20
3.2.4.1	Hello	20
3.2.4.2	Bye.....	21
3.2.4.3	Probe	21
3.2.4.4	ProbeMatch.....	21
3.2.5	Timer Events	22
3.2.5.1	Discovery Time-Out	22
3.2.5.2	Discovery Suppression Time-Out	22
3.2.5.3	Address Scavenger Time-Out	22
3.2.6	Other Local Events	22
3.2.6.1	Attach to a Subnet.....	22
3.2.6.2	Detach from a Subnet	22
3.2.6.3	Clear the Table of Servers	22
3.2.6.4	Discovery Request	23
3.2.6.5	Cancel Discovery Request	23
3.2.6.6	Enumerate Server Addresses	23
3.2.6.7	Update Server Address Time Stamp	23
3.2.6.8	Shut Down.....	23
4	Protocol Examples.....	24
4.1	Hello Message at Server Startup and Bye Message at Shutdown	24
4.2	Client Probe with Probe-Match Replies	25
5	Security.....	29
5.1	Security Considerations for Implementers.....	29
5.1.1	Potential for High Unicast Traffic	29
5.1.2	Lack of Message Authentication.....	29
5.2	Index of Security Parameters	29
6	Appendix A: Full WSDL	30
7	Appendix A: Product Behavior.....	31
8	Change Tracking.....	33
9	Index	34

1 Introduction

This document describes the Background Intelligent Transfer Service (BITS) Peer-Caching: Peer Discovery Protocol. This protocol is used to locate hosts in a **domain** that supports the URL-caching protocol implemented by BITS. The protocol is implemented by using the Web Services Dynamic Discovery (WS-Discovery) Protocol, as specified in [\[WS-Discovery\]](#).

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

domain
fully qualified domain name (FQDN)
globally unique identifier (GUID)

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

A reference marked "(Archived)" means that the reference document was either retired and is no longer being maintained or was replaced with a new document that provides current implementation details. We archive our documents online [\[Windows Protocol\]](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[RFC1035] Mockapetris, P., "Domain Names - Implementation and Specification", STD 13, RFC 1035, November 1987, <http://www.ietf.org/rfc/rfc1035.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3513] Hinden, R., and Deering, S., "Internet Protocol Version 6 (IPv6) Addressing Architecture", RFC 3513, April 2003, <http://www.ietf.org/rfc/rfc3513.txt>

[SOAP-UDP] Combs, H., Justice, J., Kakivaya, G., et al., "SOAP-over-UDP", September 2004, <http://specs.xmlsoap.org/ws/2004/09/soap-over-udp/soap-over-udp.pdf>

[SOAP1.2-2/2003] Gudgin, M., Hadley, M., Mendelsohn, N., et al., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

[WS-Discovery] Beatty, J., Kakivaya, G., Kemp D., et al., "Web Services Dynamic Discovery (WS-Discovery)", April 2005, <http://specs.xmlsoap.org/ws/2005/04/discovery/ws-discovery.pdf>

[WSAddressing] Box, D., Christensen, E., Ferguson, D., et al., "Web Services Addressing (WS-Addressing)", August 2004, <http://www.w3.org/Submission/ws-addressing/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-BPAU] Microsoft Corporation, "[Background Intelligent Transfer Service \(BITS\) Peer-Caching: Peer Authentication Protocol](#)".

[MS-BPCR] Microsoft Corporation, "[Background Intelligent Transfer Service \(BITS\) Peer-Caching: Content Retrieval Protocol](#)".

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MSDN-BITS] Microsoft Corporation, "Background Intelligent Transfer Service", [http://msdn.microsoft.com/en-us/library/bb968799\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/bb968799(VS.85).aspx)

1.3 Overview

The BITS Peer-Caching: Peer Discovery Protocol is used to locate networked hosts or devices that are implementing the server role of the [BITS Peer-Caching: Content Retrieval Protocol](#). The BITS Peer-Caching: Peer Discovery Protocol provides a way for peer servers to announce their presence to connected subnets and a way for peer clients to locate servers in connected subnets.

The BITS Peer-Caching: Peer Discovery Protocol is a specialization of Web Services Dynamic Discovery (WS-Discovery), as specified in [\[WS-Discovery\]](#), and follows its model for announcing and locating resources. The protocol defines a client role and a server role. A server announces its presence to connected IP subnets via a multicasted [Hello](#) message to UDP port 3702. A client discovers servers passively by listening for Hello messages. A client may also solicit for servers by multicasting a [Probe](#) message to the same UDP port; servers with matching characteristics reply to the client with unicast [Probe-Match](#) messages.

Windows uses the BITS Peer-Caching: Peer Discovery Protocol to implement a distributed peer-to-peer cache of URL content for use by the Background Intelligent Transfer Service (BITS) component. For more information about BITS, see [\[MSDN-BITS\]](#).

1.4 Relationship to Other Protocols

The BITS Peer-Caching: Peer Discovery Protocol does not authenticate computers to each other; Windows uses the Background Intelligent Transfer Service (BITS) Peer-Caching: Peer Authentication Protocol Specification for mutual authentication of potential peers. For more information, see [\[MS-BPAU\]](#).

WS-Discovery, and therefore the BITS Peer-Caching: Peer Discovery Protocol, uses SOAP-over-UDP as its network transport. For more information, see [\[SOAP-UDP\]](#).

A host implementing the client or server role of the BITS Peer-Caching: Peer Discovery Protocol typically also implements the same role of the [BITS Peer-Caching: Content Retrieval Protocol](#), as a higher level protocol.



Figure 1: Relationship to other protocols

1.5 Prerequisites/Preconditions

This protocol defines no prerequisites.

1.6 Applicability Statement

The primary purpose of the BITS Peer-Caching: Peer Discovery Protocol is to locate peer servers for use by the BITS Peer-Caching: Content Retrieval Protocol, as specified in [\[MS-BPCR\]](#). The BITS Peer-Caching: Peer Discovery Protocol is intended for use by hosts that are members of an Active Directory domain.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Protocol Versions:** A server advertises the versions of the protocol it supports via [Hello](#) and [Probe-Match](#) messages.

A client does not advertise the protocol versions it supports.

This specification defines version 1 of the BITS Peer-Caching: Peer Discovery Protocol. The format of each message in version 1 is defined in section [2](#) and [3](#). Because this is the initial release of the protocol, no additional versions are defined at time of publication.

- **Capability Negotiation:** The BITS Peer-Caching: Peer Discovery Protocol implicitly allows negotiation of additional capabilities by the presence or absence of additional XML elements in each message. Version 1 does not define any capabilities.

1.8 Vendor-Extensible Fields

No vendor-extensible fields are defined.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The BITS Peer-Caching: Peer Discovery Protocol is a specialization of the WS-Discovery Protocol. The Web Services Dynamic Discovery (WS-Discovery) Protocol, including dependent transports, is as specified in [\[WS-Discovery\]](#).

2.2 Common Message Syntax

This section contains common definitions used by this protocol. The syntax of the definitions uses XML Schema as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **Web Services Description Language (WSDL)** as defined in [\[WSDL\]](#).

The BITS Peer-Caching: Peer Discovery Protocol follows the message syntax of [\[WS-Discovery\]](#). Messages MUST use SOAP version 1.2, as specified in [\[SOAP1.2-2/2003\]](#). This protocol does not require the generation or processing of **SOAP faults**. No additional SOAP faults are defined.

2.2.1 Namespaces

This specification defines and references various XML namespaces using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

The following XML namespaces are used in this document:

Prefix	XML namespace	Specification
msbits	http://schemas.microsoft.com/windows/2005/05/BITS/cache	This specification ([MS-BPDP])
a	http://schemas.xmlsoap.org/ws/2004/08/addressing	[WSAddressing]
d	http://schemas.xmlsoap.org/ws/2005/04/discovery	[WS-Discovery]

2.2.2 Messages

This specification does not define any common WSDL messages.

2.2.3 Elements

The BITS Peer-Caching: Peer Discovery Protocol defines the <http://schemas.microsoft.com/windows/2005/05/BITS/cache> namespace as follows:

- The **msbits:Fqdn** element MUST contain the fully qualified DNS domain name of a host, with format as described in [\[RFC1035\]](#) section 2.3.1 and a total length of 255 characters or less.
- The **msbits:version** element MUST contain a list of versions of the BITS Peer-Caching: Peer Discovery Protocol that are supported by the sender. Versions MUST be unsigned 32-bit integers in a list delimited by white space. If version 1 is an element of the list, it MUST be the first element. This specification defines version 1, as no other versions are defined at the time of publication.
- The type **msbits:PeerServer** represents an instance of the server role.

[\[WS-Discovery\]](#) section 2.6 refers to the **a:EndpointReference** element, as specified in [\[WSAddressing\]](#) section 2. Within messages sent by the BITS Peer-Caching: Peer Discovery Protocol, the specification of the **a:EndpointReference** element is constrained in the following ways:

- The **a:Address** child element follows the recommendation of "uuid:" followed by a **GUID**. This MUST be the instance GUID of the server referred to in section [3.1.1.1](#).
- A transport address in the **d:XAddrs** element MUST have one of the following formats:

```
IPV4-str= "https://" ipv4-address  
IPV6-str= "https://[" ipv6-address "]"
```

Where:

- The **Ipv4**-address MUST be a dotted IPv4 address.
- The **Ipv6**-address MUST have one of the formats specified in [\[RFC3513\]](#) section 2.2.

2.2.4 Complex Types

This specification does not define any common XML Schema complex type definitions.

2.2.5 Simple Types

This specification does not define any common XML Schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML Schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML Schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML Schema attribute group definitions.

3 Protocol Details

3.1 Server Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The server behaves as a WS-Discovery Target Service, as specified in [\[WS-Discovery\]](#).

3.1.1.1 Protocol Metadata

The server maintains several pieces of metadata about itself:

- Its **FQDN**.
- Its active WS-Discovery scopes.
- An unsigned 32-bit integer representing the WS-Discovery metadata version.
- A GUID ([\[MS-DTYP\]](#) section 2.3.4) that is the instance GUID for WS-Discovery.

3.1.1.2 Table of Connected Subnets

The server maintains a table of all subnets for which it currently has an active IP address. Each row of the table represents a single subnet and includes the following data:

- A list of server IP addresses in the subnet.
- The subnet ID.
- The subnet mask (for IPv4) or prefix (for IPv6).

Note The abstract data model can be implemented in a variety of ways. This protocol does not prescribe or advocate any specific implementation technique.

3.1.2 Timers

No protocol-specific timers are required by the server.

3.1.3 Initialization

The first time the protocol is initialized, the server **MUST** create a unique instance GUID and **SHOULD** set its metadata version to zero. In subsequent initializations, the server **SHOULD** test whether its set of IP addresses has changed since the previous invocation by using the metadata version from the previous invocation if the set is unchanged or incrementing the metadata version if the set is different. [<1>](#) If the server does not test whether its set of IP addresses has changed, the server **MUST** create a new unique instance GUID.

The server **MUST** identify its WS-Discovery scopes by implementation-dependent means. [<2>](#)

The server MUST begin listening for messages. Transport information is specified in [\[WS-Discovery\]](#) section 2.4.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of WSDL operations defined by this specification:

Operation	Description
Hello	Used to announce a service that is joining a network.
Bye	Used to announce a service that is leaving a network.
Probe	Used to find a service on the network, based on service type.
ProbeMatch	Used to respond to a Probe message to indicate that the service matches the requested type.
Resolve	Used to locate a particular target service and retrieve network transport information.
ResolveMatch	Used to return the network transport information for a target service requested using a Resolve message.

The server MUST verify that each received message matches the schema, as specified in [\[WS-Discovery\]](#) Appendix III, and discard malformed messages. Further parsing depends on the message type.

All other messages are discarded without further processing.

3.1.4.1 Hello

A server of the BITS Peer-Caching: Peer Discovery Protocol uses the Hello message to announce its presence.

The format of the Hello message is as specified in [\[WS-Discovery\]](#) section 4.1. The following additional constraints are placed on the `/s:Envelope/s:Body/d:Hello` element:

- The **a:EndpointReference** child element MUST conform to section [2.2.3](#) of this document. It MUST contain exactly one `msbits:Fqdn` child element and exactly one `msbits:version` child element. These elements carry metadata about the server, even though they are child elements of the `a:EndpointReference` child element, and SHOULD NOT be copied into subsequent messages addressed to the Endpoint Reference in question.
- A single **d:Types** child element MUST be present and include the type "msbits:PeerServer".
- A single `d:Scopes` child element MUST be present and contain at least one scope. [<3>](#)
- A single `d:XAddrs` child element MUST be present. The **URI** list MUST contain at least one IP address in each of the subnets to which the message is sent. [<4>](#) The format of address URIs is specified in section [2.2.3](#).

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
HelloMsg	Used to announce that a service is joining a network.

3.1.4.2 Bye

A server of the BITS Peer-Caching: Peer Discovery Protocol uses the Bye message to indicate that it is disconnecting from a network.

The format of the Bye message is specified in [\[WS-Discovery\]](#) section 4.2.

The BITS Peer-Caching: Peer Discovery Protocol places no new requirements on the Bye message.

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ByeMsg	Used to announce that a service is leaving a network.

3.1.4.3 Probe

The server adheres to the requirements, as specified in [\[WS-Discovery\]](#) section 5. In addition, the BITS Peer-Caching: Peer Discovery Protocol adds the following requirements:

- When the server receives a Probe message, it MUST verify that the message satisfies the requirements specified in sections [2.2.3](#) and [3.2.4.3](#). If not, the message MUST be discarded.
- When a matching Probe message is received, the server MUST reply with a [Probe-Match](#) message, following the rules specified in [\[WS-Discovery\]](#) section 5.3 and in section [3.1.4.4](#) of this document.
- When a Probe-Match message is sent to a particular subnet, the **/s:Envelope/s:Body/d:Probe-Match/d:XAddr** element MUST contain the server addresses in that subnet from the table of connected subnets. The message SHOULD NOT contain addresses in other subnets. [<5>](#) For the URI encoding of server addresses, see section [2.2.3](#).

The server MAY limit the number and rate of Probe messages processed.

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ProbeMsg	Used to find a service on the network based on service type.

3.1.4.4 ProbeMatch

A server of the BITS Peer-Caching: Peer Discovery Protocol sends a Probe-Match message after it receives a Probe message that matches the server's WS-Discovery type and scope.

The format of the Probe-Match message is as specified in [\[WS-Discovery\]](#) section 5.3. The following additional constraints are placed on the **/s:Envelope/s:Body/d:Probe-Match** element:

- The **a:EndpointReference** child element MUST conform to section [2.2.3](#) of this document. It MUST contain exactly one msbits:Fqdn child element and exactly one msbits:version child element. These elements carry metadata about the server, even though they are child elements of the a:EndpointReference child element, and SHOULD NOT be copied into subsequent messages addressed to the Endpoint Reference in question.
- A single **d:Types** child element MUST be present and include the type "msbits:PeerServer".
- A single **d:Scopes** child element MUST be present and contain at least one scope conforming to section [2.2.3](#) of this document. [<6>](#)
- A single **d:XAddr**s child element MUST be present and its URI list MUST contain at least one address in the subnet to which the message is sent. [<7>](#)

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ProbeMatchMsg	Used for responding to a Probe message to indicate that the service matches the requested type.

3.1.4.5 Resolve

A server is required to respond to a Resolve message that matches its Endpoint Reference, as specified in [\[WS-Discovery\]](#) section 6.1. The BITS Peer-Caching: Peer Discovery Protocol relaxes that requirement.

When the server receives a Resolve message, it MAY ignore the message. [<8>](#) If the server chooses to process Resolve messages, it MUST follow the rules specified in [\[WS-Discovery\]](#) section 6.2.

In WS-Discovery, the Resolve/Resolve-Match message exchange is used when a client knows the Endpoint Reference of a server but not its XAddr, and it requires the XAddr. All [Hello](#) and [Probe-Match](#) messages sent by the BITS Peer-Caching: Peer Discovery Protocol server role carry the server's XAddr in addition to the Endpoint Reference, so the additional message exchange is not necessary.

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ResolveMsg	Used to locate a particular target service and retrieve network transport information.

3.1.4.6 ResolveMatch

The BITS Peer-Caching: Peer Discovery Protocol does not use WS-Discovery's Resolve and Resolve-Match messages and makes no changes to the definitions as specified in [\[WS-Discovery\]](#) sections

6.1 and 6.2. They SHOULD NOT be sent by an implementation of this protocol and also SHOULD be ignored or treated as not matching if received. <9>

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ResolveMatchMsg	Used to return the network transport information for a target service requested by a Resolve message.

3.1.5 Timer Events

Timers are defined in [\[WS-Discovery\]](#) sections 2.4, 3, and 7.

BITS Peer-Caching: Peer Discovery Protocol defines no additional requirements.

3.1.6 Other Local Events

3.1.6.1 Shutdown

The server MUST ignore further incoming messages.

The server MAY send a [Bye](#) message as specified in [\[WS-Discovery\]](#) sections 3 and 4.2. <10>

The server SHOULD close the network ports specified in [\[WS-Discovery\]](#) section 2.4. <11>

3.1.6.2 Add a Local IP Address

When a local IP address is added, the server checks whether it is a loopback address or a temporary IPv6 address. If it is either address, the notification MUST be ignored.

Administrative policy may require that the address not be included in the server's table of subnets. If so, then the notification is ignored.

Otherwise, the server MUST compare the subnet ID and subnet mask to those in each row in the table of connected subnets. If a matching row is not found, the server MUST create one.

The server MUST then add the local address to the list of server addresses in the row for its subnet.

The server SHOULD then increment its metadata version. <12>

Then the server SHOULD send a [Hello](#) message to announce the new address, as specified in [\[WS-Discovery\]](#) section 4.1. <13>

When a Hello message is sent, the server MUST send the message to the subnet whose address list changed, implying that the **/s:Envelope/s:Body/d:Hello/d:XAddrs** element MUST contain the server addresses in that subnet from the table of connected subnets. The server SHOULD send the message only to that subnet, in which case it SHOULD NOT contain addresses in other subnets. <14>

If the server sends the message to multiple subnets, the **/s:Envelope/s:Body/d:Hello/d:XAddrs** element MUST contain the server addresses in each of those subnets.

3.1.6.3 Remove an IP Address

When an IP address is to be deleted, the server MUST check whether the address is a member of the address list in any row of the table of connected subnets. If not, the notification is ignored.

Otherwise, the server MUST remove the address from the list for that row. The server SHOULD then increment its metadata version.<15>

If the list contains other addresses, the server SHOULD send a [Hello](#) message to update the address list, as specified in [\[WS-Discovery\]](#) section 4.1.<16> If the list contains no other addresses, then the server MUST delete the row from the table. The server MAY send a [Bye](#) message to the subnet of the deleted address, using the current instance GUID for the **/s:Body/d:Bye/a:EndpointReference/a:Address** child element, as specified in [\[WS-Discovery\]](#) section 4.2.

When a Hello message is sent, the server MUST send the message to the subnet whose address list changed, implying that the **/s:Envelope/s:Body/d:Hello/d:XAddr**s element MUST contain the server addresses in that subnet from the table of connected subnets. The server SHOULD send the message only to that subnet, in which case it SHOULD NOT contain addresses in other subnets.<17>

If the server sends the Hello message to multiple connected subnets, the **/s:Envelope/s:Body/d:Hello/d:XAddr**s element MUST contain the server addresses in each of those subnets.

3.2 Client Details

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The client behaves as a WS-Discovery client, as indicated throughout [\[WS-Discovery\]](#).

3.2.1.1 Table of Subnets

The client maintains a table of all IP subnets for which it currently holds the following:

- A local IP address.
- A table of server addresses.

Each row of the table represents a single subnet and includes the following data:

- A flag M_ATTACHED that is true if the client is currently attached to this subnet.
- A pointer to a table of server addresses.
- For each IPv4 subnet, the client saves its subnet ID, subnet mask, and DNS domain suffix (or an empty string if not available).
- For each IPv6 subnet, the client saves its subnet ID and subnet mask.

3.2.1.2 Table of Servers

The client maintains a table of all servers that are present or cached. Each row of the table represents a single server and includes:

- Its fully qualified domain name (FQDN).
- The version of the BITS Peer-Caching: Peer Discovery Protocol that it supports, as specified in section [2.2.3](#).
- A Boolean that is true if the server has been authenticated by implementation-dependent means. [<18>](#)
- (OPTIONAL) A unique GUID representing the server instance. This data is used only if the client processes [Bye](#) messages. [<19>](#)

3.2.1.3 Tables of Server Addresses

For each subnet, the client maintains a table of servers and their local addresses. Each row of the table represents a single server address and includes:

- Its FQDN.
- Its last known address in this subnet.
- The **UTC (Coordinated Universal Time)** of the last time this address was refreshed.

The **UTC** time of the address is updated whenever a [Hello](#) or [Probe-Match](#) from the server is processed successfully and contains this address. A higher-layer protocol SHOULD also update the time when the server is successfully contacted through content retrieval ([BITS Peer-Caching: Content Retrieval Protocol](#)).

3.2.1.4 Scope List

The client maintains a list of active WS-Discovery scopes defined by implementation-dependent means. [<20>](#)

3.2.2 Timers

3.2.2.1 Discovery Timer

A higher-layer protocol may signal the BITS Peer-Caching: Peer Discovery Protocol to discover more servers. Each such request is called a **discovery**. Each discovery has a finite lifetime after which the higher-layer protocol is notified that the discovery has completed. Each discovery contains a discovery timer to track the lifetime of the discovery. The default value is 30 seconds.

An implementation MAY modify the default to any positive number of seconds, but it SHOULD not set it to a value lower than the completion time of the SOAP-over-UDP transmission algorithm. WS-Discovery's use of SOAP-over-UDP is as specified in [\[WS-Discovery\]](#) section 2.4. For more information about SOAP-over-UDP, see [\[SOAP-UDP\]](#).

3.2.2.2 Discovery Suppression Timer

The protocol imposes a waiting period after sending a [Probe](#) message to avoid an inundation of network traffic from repeated discoveries. During this waiting period, new discovery requests from a

higher-layer protocol complete immediately, without triggering a Probe message. The default value for this timer is 10 minutes; it may be any nonnegative value.

3.2.2.3 Address Scavenger Timer

To reduce accumulation of obsolete server and address entries, each address contains a scavenger timer. The default timer interval is seven days and MAY be any positive value.

3.2.3 Initialization

The client MUST identify its WS-Discovery scope(s) through defining a single scope by prepending the string "https://" to the FQDN of the host.

The client MUST begin listening for messages. Transport information is as specified in [\[WS-Discovery\]](#) section 2.4.

The client MUST enumerate the subnets to which it is attached and send itself an "attach to subnet" notification for each (see section [3.2.6.1](#) for details).

3.2.4 Message Processing Events and Sequencing Rules

The client MUST verify that each received message matches the schema as specified in [\[WS-Discovery\]](#), Appendix III, while discarding malformed messages. Further parsing depends on the message type.

The following subsections define message formatting and processing requirements for a subset of the operations defined in section [3.1.4](#).

Other messages not listed in the following subsections MUST be ignored.

3.2.4.1 Hello

The client adheres to the requirements as specified in [\[WS-Discovery\]](#) section 4.1. In addition, BITS Peer-Caching: Peer Discovery Protocol adds the following requirements:

- The client MUST verify that the message satisfies the requirements in section [2.2.3](#) and section [3.1.4.1](#), discarding the message if not.
- The client MUST verify that the message's **/s:Envelope/s:Body/d:Hello/d:Types** element includes the type **msbits:PeerServer**, discarding the message if not.
- The client MAY verify other administratively defined criteria, discarding the message if they are not satisfied. [<21>](#)
- The client SHOULD add the server data to its tables as follows:
 1. *Find or create the server row.* From the **/s:Body/d:Hello/a:EndpointReference** element, set M_INSTANCE to the value of the **a:Address** child element, M_VERSION to the value of the **msbits:version** child element, and M_FQDN to the value of the **msbits:Fqdn** child element. Then, for each row in the table of servers, perform a case-insensitive comparison of the row's FQDN with M_FQDN. If a row matches, update the row's protocol version with M_VERSION and skip to step 2; otherwise, create a new row using M_FQDN, M_VERSION, and M_INSTANCE.
 2. *Integrate server addresses.* For each address URI in the **/s:Body/d:Hello/d:XAddrs** element, convert into an IPv4 or an IPv6 address as appropriate, then check whether the

address matches an existing row in the table of subnets. If no row matches, the address MUST be discarded. Otherwise, search in the associated table of server addresses for a row matching M_FQDN. If no row matches, create a new row by using the address from the message. Set the timestamp of the row to the current UTC time; set the address of the row to the current message address.

3.2.4.2 Bye

The client adheres to the requirements as specified in [\[WS-Discovery\]](#) section 4.2. In addition, (BITS) Peer-Caching: Peer Discovery Protocol adds the following requirements.

When a client receives a Bye message, it MAY discard the message. [<22>](#)

Otherwise, it MUST verify that the **/s:Body/d:Bye/a:EndpointReference/a:Address** element contains a valid instance GUID; if not, the message MUST be discarded. The client MUST search the table of servers for a row whose instance GUID matches the GUID in the element. If a matching row is found, the client MUST delete the associated table of server addresses and the matching row.

3.2.4.3 Probe

A client of the BITS Peer-Caching: Peer Discovery Protocol uses the Probe message to solicit potential servers.

The format of the Probe message is as specified in [\[WS-Discovery\]](#) section 5.2. The following additional constraints are placed on the **/s:Envelope/s:Body/d:Probe** element:

- A single **d:Types** child element MUST be present and include the type "msbits:PeerServer".
- A single **d:Scopes** child element MUST be present and contain at least one scope. [<23>](#)

A client or server MUST support the "http://schemas.xmlsoap.org/ws/2005/04/discovery/rfc2396" matching rule and MAY support other rules.

3.2.4.4 ProbeMatch

The client adheres to the requirements as specified in [\[WS-Discovery\]](#) section 5. In addition, BITS Peer-Caching: Peer Discovery Protocol adds the following requirements:

- The client MUST verify that the message satisfies the requirements in section [2.2.3](#) and section [3.1.4.4](#); if not, the message MUST be discarded.
- The client MUST verify that the message's **/s:Envelope/s:Body/d:Probe-Match/d:Types** element includes the type **msbits:PeerServer**, discarding the message if not.
- The client MUST verify that at least one of its scopes matches a scope in the message by using the rules as specified in [\[WS-Discovery\]](#) section 5.1, discarding the message if not.
- The client SHOULD add the server data to the table of servers as described in section [3.2.4.1](#), with references to the **/s:Envelope/s:Body/d:Hello** element replaced by **/s:Envelope/s:Body/d:Probe-Match**.
- The client MAY enforce limits on the number or rate of Probe-Match messages processed.

3.2.5 Timer Events

3.2.5.1 Discovery Time-Out

When a discovery's timer expires, the higher-layer protocol MUST be notified that the discovery has completed; then, the discovery MUST be deleted.

3.2.5.2 Discovery Suppression Time-Out

When the discovery suppression timer expires, nothing happens. However, the next discovery will trigger a [Probe](#) message because the client will see that the timer is expired.

3.2.5.3 Address Scavenger Time-Out

When a server's address scavenger timer expires, the address SHOULD be deleted from its table of server addresses. If its table is for a detached subnet and no other addresses remain, the table SHOULD be deleted. If no other addresses of that server remain in any subnet's table of addresses, the server SHOULD be deleted from the table of servers.

3.2.6 Other Local Events

3.2.6.1 Attach to a Subnet

When the client host attaches to an IP subnet, the client MUST check whether any existing row in the table of subnets matches the new subnet. If no row matches, the client MUST:

1. Create a new row containing the data for the new subnet.
2. Associate a new empty table of server addresses with the row.
3. Set the row's M_ATTACHED flag to true.

3.2.6.2 Detach from a Subnet

When the client host detaches from an IP subnet, the client MUST find the row with matching subnet information in the table of subnets. Then the client MUST:

1. Set the row's ATTACHED flag to false.
2. Check if the associated table of server addresses is empty. If so, the client MUST delete the associated table and the current row.

3.2.6.3 Clear the Table of Servers

A higher-layer protocol MAY signal the BITS Peer-Caching: Peer Discovery Protocol to remove all servers from the table of servers.

When this occurs, the client MUST clear the table of servers. The client first checks the M_ATTACHED flag in each row in the table of subnets. For rows where M_ATTACHED is false, the client MUST delete the associated table of server addresses and then delete the row. For the remaining rows, the client MUST clear the associated table of server addresses.

The client MUST mark the Discovery Suppression timer as not-pending, so that the next discovery request will not be suppressed.

3.2.6.4 Discovery Request

A higher-layer protocol MAY signal the protocol to discover more servers.

When this occurs, the client MUST check the Discovery Suppression timer. If it is still pending, then a discovery has completed recently and the client MUST immediately notify the higher layer that the discovery has terminated.

Otherwise, the client MUST send a [Probe](#) message.

3.2.6.5 Cancel Discovery Request

When a discovery request is canceled, the client MUST cancel the discovery's timer and immediately notify the higher layer that the discovery has terminated.

3.2.6.6 Enumerate Server Addresses

A higher-layer protocol MAY ask for a list of all online servers. When this occurs, the client MUST create a list of servers as follows:

- The client creates an empty list of servers. It then enumerates the table of addresses for each subnet with `M_ATTACHED == true`. For each address, the client adds the server to the list if it is not already there, then it appends the address to the server entry.

The result is a list of all servers currently sharing at least one subnet with the client, together with the relevant server addresses. This list is returned to the higher-layer protocol.

3.2.6.7 Update Server Address Time Stamp

A higher-layer protocol MAY signal the client to update the time stamp of a particular server address. When this occurs, the client SHOULD set the time stamp of the address to the current UTC time and restart the address's scavenger timer.

3.2.6.8 Shut Down

When the protocol is shut down, the client:

- MUST stop listening for new messages from the transport. Queued messages MAY be processed.
- SHOULD close the network ports as specified in [\[WS-Discovery\]](#) section 2.4.<24>
- MUST cancel all active discovery requests, notifying the higher-layer protocol for each one.
- SHOULD save all tables in section [3.2.1](#) for use in the next instantiation.

4 Protocol Examples

4.1 Hello Message at Server Startup and Bye Message at Shutdown

A host named \\myclient is a member of the **Active Directory** domain MyDomain. The host is connected to a single network, holding both an IPv4 address and an IPv6 address. When the BITS Peer-Caching: Peer Discovery Protocol server is started, the host sends the following message:

```
(1) <?xml version="1.0" encoding="utf-8"?>
(2) <soap:Envelope
(3)   xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
(4)   xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
(5)   xmlns:wsd="http://schemas.xmlsoap.org/ws/2005/04/discovery"
(6)   xmlns:msbits="http://schemas.microsoft.com/windows/2005/05/BITS/cache">
(7)   <soap:Header>
(8)     <wsa:To>
(9)       urn:schemas-xmlsoap-org:ws:2005:04:discovery
(10)    </wsa:To>
(11)   <wsa:Action>
(12)     http://schemas.xmlsoap.org/ws/2005/04/discovery/Hello
(13)   </wsa:Action>
(14)   <wsa:MessageID>
(15)     urn:uuid:16dlca53-23c0-4e27-accf-2bf71377f49e
(16)   </wsa:MessageID>
(17)   <wsd:AppSequence
(18)     InstanceId="1169067015" MessageNumber="2">
(19)   </wsd:AppSequence>
(20) </soap:Header>
(21) <soap:Body>
(22)   <wsd:Hello>
(23)     <wsa:EndpointReference>
(24)       <wsa:Address>
(25)         uuid:A99558EB-C1D8-49D3-9476-8B9A6571800B
(26)       </wsa:Address>
(27)       <msbits:Fqdn>
(28)         myclient.mydomain.com
(29)       </msbits:Fqdn>
(30)       <msbits:version>
(31)         1
(32)       </msbits:version>
(33)     </wsa:EndpointReference>
(34)     <wsd:Types>
(35)       msbits:PeerServer
(36)     </wsd:Types>
(37)     <wsd:Scopes>
(38)       http://mydomain.com
(39)     </wsd:Scopes>
(40)     <wsd:XAddr>
(41)       https://[2001:4898:2c:2:1db1:40d8:28fb:79d0]
(42)       https://192.68.1.1
(43)     </wsd:XAddr>
(44)     <wsd:MetadataVersion>
(45)       1
(46)     </wsd:MetadataVersion>
(47)   </wsd:Hello>
(48) </soap:Body>
```



```
(49) </soap:Envelope>
```

The packet is sent four times: twice to the IPv4 address 239.255.255.250 port 3702, and twice to the IPv6 address FF02::C port 3702. This follows the algorithm in [\[SOAP-UDP\]](#) Appendix I.

When the BITS Peer-Caching: Peer Discovery Protocol server is shut down, the following [Bye](#) message is sent. Like the [Hello](#) message, it is sent twice to each multicast address.

```
(1) <?xml version="1.0" encoding="utf-8"?>
(2) <soap:Envelope
(3)   xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
(4)   xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
(5)   xmlns:wsd="http://schemas.xmlsoap.org/ws/2005/04/discovery">
(6)   <soap:Header>
(7)     <wsa:To>
(8)       urn:schemas-xmlsoap-org:ws:2005:04:discovery
(9)     </wsa:To>
(10)    <wsa:Action>
(11)      http://schemas.xmlsoap.org/ws/2005/04/discovery/Bye
(12)    </wsa:Action>
(13)    <wsa:MessageID>
(14)      urn:uuid:e1c429f4-661d-4f98-a6d3-ce712efa28b7
(15)    </wsa:MessageID>
(16)    <wsd:AppSequence
(17)      InstanceId="1169067015"
(18)      MessageNumber="3">
(19)    </wsd:AppSequence>
(20)  </soap:Header>
(21)  <soap:Body>
(22)    <wsd:Bye>
(23)      <wsa:EndpointReference>
(24)        <wsa:Address>
(25)          uuid:A99558EB-C1D8-49D3-9476-8B9A6571800B
(26)        </wsa:Address>
(27)      </wsa:EndpointReference>
(28)    </wsd:Bye>
(29)  </soap:Body>
(30) </soap:Envelope>
```

4.2 Client Probe with Probe-Match Replies

A host named \\client1 is a member of the Active Directory domain MyDomain. The host is connected to a single network, holding both an IPv4 address and an IPv6 address.

When the BITS Peer-Caching: Peer Discovery Protocol client initiates a discovery, the host sends the following message. Line 21 indicates that the search is for Peer Discovery servers, and line 25 indicates the scope to match (here, an Active Directory domain).

```
(1) <?xml version="1.0" encoding="utf-8"?>
(2) <soap:Envelope
(3)   xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
(4)   xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
(5)   xmlns:wsd="http://schemas.xmlsoap.org/ws/2005/04/discovery"
(6)   xmlns:msbits="http://schemas.microsoft.com/windows/2005/05/BITS/cache">
(7)   <soap:Header>
```

```

(8)   <wsa:To>
(9)   urn:schemas-xmlsoap-org:ws:2005:04:discovery
(10)  </wsa:To>
(11)  <wsa:Action>
(12)  http://schemas.xmlsoap.org/ws/2005/04/discovery/Probe
(13)  </wsa:Action>
(14)  <wsa:MessageID>
(15)  urn:uuid:7895122d-f9d6-4cb9-b819-872f24c271b9
(16)  </wsa:MessageID>
(17)  </soap:Header>
(18)  <soap:Body>
(19)  <wsd:Probe>
(20)  <wsd:Types>
(21)  msbits:PeerServer
(22)  </wsd:Types>
(23)  <wsd:Scopes>
(24)  MatchBy="http://schemas.xmlsoap.org/ws/2005/04/discovery/rfc2396">
(25)  http://mydomain.com
(26)  </wsd:Scopes>
(27)  </wsd:Probe>
(28)  </soap:Body>
(29) </soap:Envelope>

```

The message is sent four times: twice to the IPv4 address 239.255.255.250 port 3702, and twice to the IPv6 address FF02::C port 3702. This follows the algorithm in Appendix I of [\[SOAP-UDP\]](#).

Two Peer Discovery servers in the same Active Directory domain and one in a different domain receive the [Probe](#).

The host \\peer1 is a member of the MyDomain domain; after 150 milliseconds it replies with the following message:

```

(1) <?xml version="1.0" encoding="utf-8"?>
(2) <soap:Envelope
(3) xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
(4) xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
(5) xmlns:wsd="http://schemas.xmlsoap.org/ws/2005/04/discovery"
(6) xmlns:msbits="http://schemas.microsoft.com/windows/2005/05/BITS/cache">
(7) <soap:Header>
(8)   <wsa:To>
(9)   http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous
(10)  </wsa:To>
(11)  <wsa:Action>
(12)  http://schemas.xmlsoap.org/ws/2005/04/discovery/ProbeMatches
(13)  </wsa:Action>
(14)  <wsa:MessageID>
(15)  urn:uuid:769dfff7-e778-4506-a764-0cbb26cb0f60
(16)  </wsa:MessageID>
(17)  <wsa:RelatesTo>
(18)  urn:uuid:7895122d-f9d6-4cb9-b819-872f24c271b9
(19)  </wsa:RelatesTo>
(20)  <wsd:AppSequence
(21)  InstanceId="1168888181"
(22)  MessageNumber="434">
(23)  </wsd:AppSequence>
(24) </soap:Header>
(25) <soap:Body>

```

```

(26) <wsd:ProbeMatches>
(27)   <wsd:ProbeMatch>
(28)     <wsa:EndpointReference>
(29)       <wsa:Address>
(30)         uuid:FDEF35B-3B18-4E1C-B970-09F811D00304
(31)       </wsa:Address>
(32)     <msbits:Fqdn>
(33)       peer1.mydomain.com
(34)     </msbits:Fqdn>
(35)     <msbits:version>
(36)       1
(37)     </msbits:version>
(38)   </wsa:EndpointReference>
(39) </wsd:Types>
(40)   msbits:PeerServer
(41) </wsd:Types>
(42) <wsd:Scopes>
(43)   http://mydomain.com
(44) </wsd:Scopes>
(45) <wsd:XAddrs>
(46)   https://[2001:4898:2c:2:dc2c:a67c:68ed:4c0b]
(47)   https://192.168.1.20
(48) </wsd:XAddrs>
(49) <wsd:MetadataVersion>
(50)   1
(51) </wsd:MetadataVersion>
(52) </wsd:ProbeMatch>
(53) </wsd:ProbeMatches>
(54) </soap:Body>
(55) </soap:Envelope>

```

The **UUID** in line 18 matches the one in line 15 of the Probe. Line 33 reflects the host's FQDN, line 43 reflects the host's Active Directory domain, and lines 46-47 contain the host's IP addresses.

The host \\peer2 is a member of the MyDomain domain; after 800 milliseconds it replies with the following message:

```

(1) <?xml version="1.0" encoding="utf-8"?>
(2) <soap:Envelope
(3)   xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
(4)   xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
(5)   xmlns:wsd="http://schemas.xmlsoap.org/ws/2005/04/discovery"
(6)   xmlns:msbits="http://schemas.microsoft.com/windows/2005/05/BITS/cache">
(7) <soap:Header>
(8)   <wsa:To>
(9)     http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous
(10)  </wsa:To>
(11) <wsa:Action>
(12)   http://schemas.xmlsoap.org/ws/2005/04/discovery/ProbeMatches
(13) </wsa:Action>
(14) <wsa:MessageID>
(15)   urn:uuid:a7eb1f92-cc38-434a-a619-bcb0f6a85de4
(16) </wsa:MessageID>
(17) <wsa:RelatesTo>
(18)   urn:uuid:7895122d-f9d6-4cb9-b819-872f24c271b9
(19) </wsa:RelatesTo>
(20) <wsd:AppSequence

```

```
(21) InstanceId="1168539790"
(22) MessageNumber="666">
(23) </wsd:AppSequence>
(24) </soap:Header>
(25) <soap:Body>
(26) <wsd:ProbeMatches>
(27) <wsd:ProbeMatch>
(28) <wsa:EndpointReference>
(29) <wsa:Address>
(30) uuid:80991AC9-6A0F-440D-9ACB-45D48F1A2D7F
(31) </wsa:Address>
(32) <msbits:Fqdn>
(33) peer2.mydomain.com
(34) </msbits:Fqdn>
(35) <msbits:version>
(36) 1
(37) </msbits:version>
(38) </wsa:EndpointReference>
(39) <wsd:Types>
(40) msbits:PeerServer
(41) </wsd:Types>
(42) <wsd:Scopes>
(43) http://mydomain.com
(44) </wsd:Scopes>
(45) <wsd:XAddr>
(46) https://[2001:4898:2c:2:2cc8:dae1:1bfb:4aea]
(47) https://192.168.1.21
(48) </wsd:XAddr>
(49) <wsd:MetadataVersion>
(50) 1
(51) </wsd:MetadataVersion>
(52) </wsd:ProbeMatch>
(53) </wsd:ProbeMatches>
(54) </soap:Body>
(55) </soap:Envelope>
```

The host \\products is a member of a different Active Directory domain. Line 25 of the Probe message fails to match the host's own WS-Discovery scope, and so the Probe is discarded without response.

5 Security

5.1 Security Considerations for Implementers

5.1.1 Potential for High Unicast Traffic

[WS-Discovery](#) does not provide a way to control the number or pace of replies to a [Probe](#) message. In a very large network, a client may be overwhelmed by many server replies.

5.1.2 Lack of Message Authentication

This protocol does not provide any authentication for messages. It is possible for a malicious host to send incorrect [Hello](#), [Bye](#), and [Probe-Match](#) messages in order to confuse a client. A client MUST consider all information gained from this protocol as insecure until corroborated by other means.

5.2 Index of Security Parameters

This protocol does not define any security parameters.

6 Appendix A: Full WSDL

For the full WSDL description for this specification, see [WSDL for WS-Discovery](#).

7 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Windows Vista operating system
- Windows Server 2008 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 3.1.3:](#) In server role, Windows resets the metadata version to one each time the protocol is initialized.

[<2> Section 3.1.3:](#) In server role, Windows defines a single scope by prepending the string "https://" to the FQDN of the host.

[<3> Section 3.1.4.1:](#) In server role, Windows always sends a single scope, defined by prepending the string "https://" to the FQDN of the host.

[<4> Section 3.1.4.1:](#) In server role, Windows includes one **XAddr** for each active non-loopback IPv4 address and each globally aggregatable IPv6 address.

[<5> Section 3.1.4.3:](#) In server role, Windows sends a URI list containing all server addresses from the table of connected subnets.

[<6> Section 3.1.4.4:](#) In server role, Windows always sends a single scope, defined by prepending the string "https://" to the FQDN of the host.

[<7> Section 3.1.4.4:](#) In server role, Windows includes one **XAddr** for each active non-loopback IPv4 address and each globally aggregatable IPv6 address.

[<8> Section 3.1.4.5:](#) In server role, Windows ignores [Resolve](#) messages.

[<9> Section 3.1.4.6:](#) In server role, Windows does not send these messages, and ignores them if received.

[<10> Section 3.1.6.1:](#) In server role, Windows sends a [Bye](#) message.

[<11> Section 3.1.6.1:](#) In server role, Windows closes the ports if and only if no other WS-Discovery-based protocols are active on the host.

[<12> Section 3.1.6.2:](#) In server role, Windows does not increment its metadata version when the address list changes.

[<13> Section 3.1.6.2:](#) In server role, Windows does not send the [Hello](#) message.

[<14> Section 3.1.6.2:](#) In server role, Windows sends a URI list containing all server addresses from the table of connected subnets.

<15> [Section 3.1.6.3](#): In server role, Windows does not increment its metadata version when the address list changes.

<16> [Section 3.1.6.3](#): Windows Vista and Windows Server 2008 do not send a [Hello](#) message.

<17> [Section 3.1.6.3](#): In server role, Windows sends a URI list containing all server addresses from the table of connected subnets.

<18> [Section 3.2.1.2](#): In client role, Windows authenticates servers by using the BITS Peer-Caching: Peer Authentication Protocol, as specified in [\[MS-BPAU\]](#).

<19> [Section 3.2.1.2](#): In client role, Windows always discards [Bye](#) messages.

<20> [Section 3.2.1.4](#): In client role, Windows defines a single scope by prepending the string "https://" to the FQDN of the host.

<21> [Section 3.2.4.1](#): In client role, Windows verifies that the **/s:Body/d:Hello/a:EndpointReference/msbits:Fqdn** element matches the Active Directory domain to which the client belongs. Windows supports the protocol only on hosts that are members of an Active Directory domain.

<22> [Section 3.2.4.2](#): In client role, Windows always discards [Bye](#) messages.

<23> [Section 3.2.4.3](#): In client role, Windows always sends a single scope, defined by prepending the string "https://" to the FQDN of the host.

<24> [Section 3.2.6.8](#): In client role, Windows closes the ports if and only if no other WS-Discovery-based protocols are active on the host.

8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

9 Index

A

Abstract data model
 [client](#) 18
 [server](#) 13
[Adding local IP address](#) 17
[Address scavenger time-out](#) 22
[Address scavenger timer](#) 20
[Applicability](#) 9
[Attribute groups](#) 12
[Attributes](#) 12
[Authentication - lack of](#) 29

B

[Bye message](#) 21

C

[Capability negotiation](#) 9
[Change tracking](#) 33
[Clearing table of servers](#) 22
Client
 [abstract data model](#) 18
 [address scavenger timer](#) 20
 [attaching to subnet](#) 22
 [Bye message](#) 21
 [detaching from subnet](#) 22
 [Discovery request](#) 23
 [Discovery request - canceling](#) 23
 [discovery suppression timer](#) 19
 [discovery timer](#) 19
 [enumerated server addresses](#) 23
 [Hello message](#) 20
 [initialization](#) 20
 [local events](#) 22
 [message processing](#) 20
 [Probe-Match message](#) 21
 [scope list](#) 19
 [sequencing rules](#) 20
 [server addresses table](#) 19
 [servers table](#) 19
 [servers table - clearing](#) 22
 [shut down](#) 23
 [subnets table](#) 18
 [timer events](#) 22
 [timers](#) 19
 [update server address time stamp](#) 23
[Client Probe with Probe-Match replies](#) 25
[Complex types](#) 12
[Connected subnets table](#) 13

D

Data model - abstract
 [client](#) 18
 [server](#) 13
[Discovery request](#) 23
[Discovery request - canceling](#) 23

[Discovery suppression time-out](#) 22
[Discovery suppression timer](#) 19
[Discovery time-out](#) 22
[Discovery timer](#) 19

E

[Enumerated server addresses](#) 23
Examples
 [Client Probe with Probe-Match replies example](#) 25
 [Hello message at server startup example and Bye Message at Shutdown](#) 24

F

[Fields - vendor-extensible](#) 10

G

[Glossary](#) 7
[Groups](#) 12

H

[Hello message](#) 20
[Hello message at server startup example and Bye Message at Shutdown](#) 24

I

[Implementer - security considerations](#) 29
[Index of security parameters](#) 29
[Informative references](#) 8
Initialization
 [client](#) 20
 [server](#) 13
[Introduction](#) 7

L

Local events
 [client](#) 22
 [server](#) 17
Local IP address
 [adding](#) 17
 [removing](#) 18

M

Message processing
 [client](#) 20
 [server](#) 14
Messages
 [attribute groups](#) 12
 [attributes](#) 12
 [Bye message](#) 21
 [complex types](#) 12
 [elements](#) 11
 [enumerated](#) 11

- [groups](#) 12
- [Hello message](#) 20
- [namespaces](#) 11
- [Probe message](#) 15
- [Probe-Match message](#) 21
- [Resolve message](#) 16
- [simple types](#) 12
- [syntax](#) 11
- [transport](#) 11
- [Metadata - server](#) 13

N

- [Namespaces](#) 11
- [Normative references](#) 7

O

- [Overview \(synopsis\)](#) 8

P

- [Parameters - security index](#) 29
- [Preconditions](#) 9
- [Prerequisites](#) 9
- [Probe message](#) 15
- [Probe-Match message](#) 21
- [Product behavior](#) 31

R

- References
 - [informative](#) 8
 - [normative](#) 7
- [Relationship to other protocols](#) 9
- [Removing local IP address](#) 18
- [Resolve message](#) 16

S

- [Scope list](#) 19
- Security
 - [high traffic effect](#) 29
 - [implementer considerations](#) 29
 - [lack of authentication](#) 29
 - [parameter index](#) 29
- Sequencing rules
 - [client](#) 20
 - [server](#) 14
- Server
 - [abstract data model](#) 13
 - [addresses table](#) 19
 - client table ([section 3.2.1.2](#) 19, [section 3.2.6.3](#) 22)
 - [connected subnets table](#) 13
 - [initialization](#) 13
 - [local events](#) 17
 - [message processing](#) 14
 - [metadata](#) 13
 - [Probe message](#) 15
 - [Resolve message](#) 16
 - [sequencing rules](#) 14

- [timer events](#) 17
- [timers](#) 13
- [Shut down](#) 23
- [Shutdown](#) 17
- [Simple types](#) 12
- Subnet
 - [attaching to client](#) 22
 - [detaching from client](#) 22
- [Subnets - client - table](#) 18
- [Subnets - connected - table](#) 13
- [Subnets table](#) 18
- [Syntax - messages - overview](#) 11

T

- Table - client servers ([section 3.2.1.2](#) 19, [section 3.2.6.3](#) 22)
- [Table - client subnets](#) 18
- [Table - connected subnets](#) 13
- [Table - server addresses](#) 19
- Timer events
 - [client](#) 22
 - [server](#) 17
- Timers
 - [client](#) 19
 - [server](#) 13
- [Tracking changes](#) 33
- [Traffic effect - security](#) 29
- [Transport](#) 11
- Types
 - [complex](#) 12
 - [simple](#) 12

U

- [Update server address time stamp](#) 23

V

- [Vendor-extensible fields](#) 10
- [Versioning](#) 9