

[MS-CIFS]: Common Internet File System (CIFS) Protocol

This topic lists the Errata found in the MS-CIFS document since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V28.0 – 2017/12/01](#).

Errata Published*	Description
2018/07/30	<p>In Section 2.2.7.1.1, Request, the description of FILE_OVERWRITE and FILE_OVERWRITE_IF have been changed from:</p> <p>FILE_OVERWRITE: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, the operation MUST fail. The client MUST open the file with at least GENERIC_WRITE access for the command to succeed.</p> <p>FILE_OVERWRITE_IF: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, it SHOULD be created. The client MUST open the file with at least GENERIC_WRITE access.</p> <p>Changed to:</p> <p>FILE_OVERWRITE: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, the operation MUST fail.</p> <p>FILE_OVERWRITE_IF: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, it SHOULD be created.</p>
2017/12/18	<p>In Section 2.2.4.64.1, Request, the description of FILE_OVERWRITE and FILE_OVERWRITE_IF have been changed from:</p> <p>FILE_OVERWRITE: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, the operation MUST fail. The client MUST open the file with at least GENERIC_WRITE access for the command to succeed.</p> <p>FILE_OVERWRITE_IF: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, it SHOULD be created. The client MUST open the file with at least GENERIC_WRITE access.</p> <p>Changed to:</p> <p>FILE_OVERWRITE: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, the operation MUST fail.</p> <p>FILE_OVERWRITE_IF: If the file already exists, it SHOULD be opened and truncated. If the file does not already exist, it SHOULD be created.</p>

*Date format: YYYY/MM/DD