

# [MS-DCHT]: Desktop Chat Protocol

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
08/14/2009	0.1	Major	First Release.
09/25/2009	0.1.1	Editorial	Revised and edited the technical content.
11/06/2009	0.1.2	Editorial	Revised and edited the technical content.
12/18/2009	0.1.3	Editorial	Revised and edited the technical content.
01/29/2010	0.2	Minor	Updated the technical content.
03/12/2010	0.2.1	Editorial	Revised and edited the technical content.
04/23/2010	0.2.2	Editorial	Revised and edited the technical content.
06/04/2010	0.3	Minor	Updated the technical content.
07/16/2010	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2010	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	0.3	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	0.4	Minor	Clarified the meaning of the technical content.
09/23/2011	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
03/30/2012	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
07/12/2012	0.4	No change	No changes to the meaning, language, or formatting of

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
			the technical content.
10/25/2012	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
01/31/2013	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
08/08/2013	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
11/14/2013	0.4	No change	No changes to the meaning, language, or formatting of the technical content.
02/13/2014	0.5	Minor	Clarified the meaning of the technical content.

# Contents

<b>1 Introduction</b>	<b>6</b>
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	7
1.3 Overview	7
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	8
1.8 Vendor-Extensible Fields	8
1.9 Standards Assignments	8
<b>2 Messages</b>	<b>9</b>
2.1 Commonly Referenced Data Structures, Values, and Definitions	9
2.1.1 Common Definitions	9
2.1.2 Common Field Values	9
2.1.2.1 ChatMessageType	9
2.2 Transport	9
2.3 Message Syntax	10
2.3.1 Session Information	10
2.3.1.1 CHATDATA_PROTOCOL	10
2.3.1.2 CHATDATA_UNICODE	10
2.3.2 Chat Information	11
2.3.2.1 CHATDATA_CHAR	11
2.3.2.2 CHATDATA_FONTA	11
2.3.2.3 CHATDATA_PASTE	13
2.3.2.4 CHATDATA_DBCS_STRING	14
2.3.2.5 CHATDATA_FONTW	15
2.3.2.6 CHATDATA_PASTEW	17
<b>3 Protocol Details</b>	<b>18</b>
3.1 Desktop Chat Details	18
3.1.1 Abstract Data Model	18
3.1.2 Timers	18
3.1.3 Initialization	18
3.1.4 Higher-Layer Triggered Events	19
3.1.5 Message Processing Events and Sequencing Rules	19
3.1.5.1 CHATDATA_PROTOCOL	19
3.1.5.2 CHATDATA_UNICODE	19
3.1.5.3 CHATDATA_CHAR	19
3.1.5.4 CHATDATA_FONTA	19
3.1.5.5 CHATDATA_PASTE	20
3.1.5.6 CHATDATA_DBCS_STRING	20
3.1.5.7 CHATDATA_FONTW	20
3.1.5.8 CHATDATA_PASTEW	20
<b>4 Protocol Examples</b>	<b>21</b>
4.1 Sample Chat Session	21
<b>5 Security</b>	<b>23</b>

5.1 Security Considerations for Implementers .....	23
5.2 Index of Security Parameters .....	23
<b>6 Appendix A: Product Behavior .....</b>	<b>24</b>
<b>7 Change Tracking.....</b>	<b>25</b>
<b>8 Index .....</b>	<b>27</b>

# 1 Introduction

The Desktop Chat Protocol specifies the mechanism by which the Windows Chat application in Windows communicates information between remote users.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**client**  
**device**  
**marshal**  
**NetBIOS**  
**server**  
**Unicode**

The following terms are specific to this document:

**chat session:** An active communication channel established between two computers using the Microsoft Desktop Chat Protocol.

**dynamic data exchange (DDE):** A protocol through which applications can exchange messages and use shared memory to exchange data. Applications can use DDE for one-time data transfers and for continuous exchanges in which applications send updates to each other as new data becomes available.

**network Dynamic Data Exchange (NetDDE):** A technology that allows applications using **dynamic data exchange (DDE)** to transparently share data over a network.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

A reference marked "(Archived)" means that the reference document was either retired and is no longer being maintained or was replaced with a new document that provides current implementation details. We archive our documents online [\[Windows Protocol\]](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[ISO/IEC-8859-1] International Organization for Standardization, "Information Technology -- 8-Bit Single-Byte Coded Graphic Character Sets -- Part 1: Latin Alphabet No. 1", ISO/IEC 8859-1, 1998, [http://www.iso.org/iso/home/store/catalogue\\_tc/catalogue\\_detail.htm?csnumber=28245](http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=28245)

**Note** There is a charge to download the specification.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

## 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MSDN-DDE] Microsoft Corporation, "Dynamic Data Exchange (DDE) and DDE Management Library", [http://msdn.microsoft.com/en-us/library/ms648712\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/ms648712(VS.85).aspx)

[MSDN-LOGFONT] Microsoft Corporation, "LOGFONT data structure", [http://msdn.microsoft.com/en-us/library/dd145037\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/dd145037(VS.85).aspx)

[MSDN-NETDDE] Microsoft Corporation, "Network Dynamic Data Exchange", [http://msdn.microsoft.com/en-us/library/aa365778\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/aa365778(VS.85).aspx)


[MSDN-Win32Edit] Microsoft Corporation, "Win32 Edit control", [http://msdn.microsoft.com/en-us/library/cc656455\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/cc656455(VS.85).aspx)

## 1.3 Overview

This document specifies the Desktop Chat Protocol, used by the Windows Chat application. This Desktop Chat Protocol initiates a **chat session** between two machines and allows for the real-time transfer of textual data between them.

## 1.4 Relationship to Other Protocols

The Desktop Chat Protocol is implemented on top of the NetDDE protocol [\[MSDN-NETDDE\]](#).



**Figure 1: The Desktop Chat Protocol relationship to other protocols**

## 1.5 Prerequisites/Preconditions

The Desktop Chat Protocol requires the NetDDE API. The NetDDE protocol [\[MSDN-NETDDE\]](#) service is required to be running on the participant machines.

## 1.6 Applicability Statement

The Desktop Chat Protocol is used for real-time text communication.

## **1.7 Versioning and Capability Negotiation**

The Desktop Chat Protocol does not have multiple versions.

## **1.8 Vendor-Extensible Fields**

None.

## **1.9 Standards Assignments**

None.

## 2 Messages

This protocol references commonly used data types as defined in [\[MS-DTYP\]](#)

### 2.1 Commonly Referenced Data Structures, Values, and Definitions

The Desktop Chat Protocol specifies the following data structures.

#### 2.1.1 Common Definitions

#### 2.1.2 Common Field Values

##### 2.1.2.1 ChatMessageType

The **ChatMessageType** enumeration describes the type of message sent between participants in a desktop chat session.

Value	Meaning
CHT_CHAR 0x0100	The message contains information about a single character that has been inputted in a chat session.
CHT_FONTA 0x0101	The message contains information about the font being used in a chat session that does not support <b>Unicode</b> .
CHT_PASTE 0x0102	The message contains information about a text paste operation that has been performed in a chat session that does not support Unicode.
CHT_DBCS_STRING 0x0103	The message contains multi-byte encoded string data entered into a chat session that does not support Unicode.
CHT_PROTOCOL 0x0105	The message contains protocol information related to establishing a chat session.
CHT_UNICODE 0x0110	The message describes the ability of the chat participant to use Unicode data.
CHT_FONTW 0x0111	The message contains information about the font being used in a chat session that supports Unicode.
CHT_PASTEW 0x0112	The message contains information about a text paste operation that has been performed in a chat session that supports Unicode.

## 2.2 Transport

The NetDDE API MUST be present. The NetDDE protocol service [\[MSDN-NETDDE\]](#) MUST be running on the participant machines.

Desktop Chat protocol messages are encapsulated in data blocks delivered using NetDDE [\[MSDN-NETDDE\]](#), as described in detail in section [3.1.3](#).

## 2.3 Message Syntax

All **CHATDATA** structures defined in section [2.3.1](#) and [2.3.2](#) begin with a **ChatMessageType** defining the type of message.

**Note** All unsigned 16-bit and unsigned 32-bit values are specified in little-endian format. Depending on the hardware architectures of the **client** and the **server**, multiple-byte little-endian versus big-endian reordering can determine how this variable is **marshaled** by the sender and interpreted by the receiver.

### 2.3.1 Session Information

The Desktop Chat Protocol uses session information to establish the capabilities of the remote participant.

#### 2.3.1.1 CHATDATA\_PROTOCOL

The CHATDATA\_PROTOCOL structure specifies version information for future use.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																Version															
...																PacketsSupported															
...																															

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0105 (**CHT\_PROTOCOL**).

**Version (4 bytes):** A 32-bit unsigned integer specifying the version information. MUST be set to 0x00000100.

**PacketsSupported (4 bytes):** A 32-bit unsigned integer specifying capability information. MUST be set to 0x00000001.

#### 2.3.1.2 CHATDATA\_UNICODE

The CHATDATA\_UNICODE structure indicates that the sender supports Unicode text.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																															

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0110 (**CHT\_UNICODE**).

## 2.3.2 Chat Information

The Desktop Chat Protocol transfers chat information between two participants, representing textual user input that has been entered into the chat application.

### 2.3.2.1 CHATDATA\_CHAR

The CHATDATA\_CHAR structure defines a user-input character that is sent in the chat session.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																SelPosEnd															
SelPosBegin																Char															

**Type (2 bytes):** A 16-bit unsigned integer (ChatMessageType) specifying the type of this message. MUST be set to 0x0100 (CHT\_CHAR).

**SelPosEnd (2 bytes):** A 16-bit unsigned integer that specifies the zero-based position of the first character after the last selected character. [<1>](#)

**SelPosBegin (2 bytes):** A 16-bit unsigned integer that specifies the zero-based starting position of the selection. [<2>](#)

**Char (2 bytes):** A 16-bit unsigned integer that specifies the character that the user has inputted. If the Desktop chat session has been negotiated as Unicode (**SessionState.Unicode** field is true), this MUST be a Unicode character. If the Desktop chat session has not been negotiated as Unicode (**SessionState.Unicode** field is false), this MUST be an ANSI (as specified in [\[ISO/IEC-8859-1\]](#)) or Double-Byte Character Sets (DBCS) character.

### 2.3.2.2 CHATDATA\_FONTA

The CHATDATA\_FONTA structure defines the font that is being used in the **chat session** by a user. [<3>](#)

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																lfHeight															
lfWidth																lfEscapement															
lfOrientation																lfWeight															
lfItalic				lfUnderline				lfStrikeOut				lfCharSet																			
lfOutPrecision				lfClipPrecision				lfQuality				lfPitchAndFamily																			
lfFaceName																															

...
...
...
...
...
...
...
...
ColorRef
Brush

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0101 (**CHT\_FONTA**).

**IfHeight (2 bytes):** A 16-bit signed integer that specifies the height, in logical units, of the font's character cell or character.

**IfWidth (2 bytes):** A 16-bit signed integer that specifies the average width, in logical units, of characters in the font.

**IfEscapement (2 bytes):** A 16-bit signed integer that specifies the angle, in tenths of degrees, between the escapement vector and the x-axis of the **device**. The escapement vector is parallel to the base line of a row of text.

**IfOrientation (2 bytes):** A 16-bit signed integer that specifies the angle, in tenths of degrees, between each character's base line and the x-axis of the device.

**IfWeight (2 bytes):** A 16-bit signed integer that specifies the weight of the font in the range 0 through 1000. For example, 400 is normal and 700 is bold. If this value is zero, a default weight is used.

**IfItalic (1 byte):** An 8-bit unsigned integer that specifies an italic font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfUnderline (1 byte):** An 8-bit unsigned integer that specifies an underlined font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfStrikeOut (1 byte):** An 8-bit unsigned integer that specifies a strikeout font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfCharSet (1 byte):** An 8-bit unsigned integer that specifies the character set.

**IfOutPrecision (1 byte):** An 8-bit unsigned integer that specifies the output precision.

**IfClipPrecision (1 byte):** An 8-bit unsigned integer that specifies the clipping precision.

**IfQuality (1 byte):** An 8-bit unsigned integer that specifies the output quality.

**IfPitchAndFamily (1 byte):** An 8-bit unsigned integer that specifies the pitch and family of the font.

**IfFaceName (32 bytes):** A NULL-terminated ANSI character string that specifies the typeface name of the font.

**ColorRef (4 bytes):** A **COLORREF** 32-bit value that specifies the RGB color used for the edit control text [\[MSDN-Win32Edit\]](#).

**Brush (4 bytes):** A **COLORREF** 32-bit value that specifies the RGB color used for the edit control background [\[MSDN-Win32Edit\]](#).

### 2.3.2.3 CHATDATA\_PASTE

The CHATDATA\_PASTE structure indicates that a user has pasted text from the clipboard into the chat session.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																SelPosEnd															
SelPosBegin																Size															
...																Unused															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
(Unused cont'd for 5 rows)																															
PastedText (variable)																															
...																															

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0102 (**CHT\_PASTE**).

**SelPosEnd (2 bytes):** A 16-bit unsigned integer that specifies the zero-based position of the first character after the last selected character. <4>

**SelPosBegin (2 bytes):** A 16-bit unsigned integer that specifies the zero-based starting position of the selection. <5>

**Size (4 bytes):** A 32-bit unsigned integer that specifies the length of the pasted text in bytes, not including the NULL terminator.

**Unused (50 bytes):** Unused. MUST be set to zero.

**PastedText (variable):** A NULL-terminated ANSI character string specifying the pasted text.

### 2.3.2.4 CHATDATA\_DBCS\_STRING

The CHATDATA\_DBCS\_STRING structure indicates that a user has entered text into the chat session that is being sent to a receiver that does not support Unicode.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																SelPosEnd															
SelPosBegin																Size															
...																unused															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
(unused cont'd for 5 rows)																															
DBCSText (variable)																															
...																															

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0103 (**CHT\_DBCS\_STRING**).

**SelPosEnd (2 bytes):** A 16-bit unsigned integer that specifies the zero-based position of the first character after the last selected character. [<6>](#)

**SelPosBegin (2 bytes):** A 16-bit unsigned integer that specifies the zero-based starting position of the selection. [<7>](#)

**Size (4 bytes):** A 32-bit unsigned integer that specifies the length of the DBCS string in bytes, not including the NULL terminator.

**unused (50 bytes):** Unused. MUST be zeroed.

**DBCSText (variable):** A NULL-terminated DBCS character string.

### 2.3.2.5 CHATDATA\_FONTW

The CHATDATA\_FONTW structure defines the font that is being used in the chat session by a user. [<8>](#)

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																lfHeight															
lfWidth																lfEscapement															
lfOrientation																lfWeight															
lfItalic				lfUnderline				lfStrikeOut				lfCharSet																			
lfOutPrecision				lfClipPrecision				lfQuality				lfPitchAndFamily																			
lfFaceName																															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
(lfFaceName cont'd for 8 rows)																															

ColorRef
Brush

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0111 (**CHT\_FONTW**).

**IfHeight (2 bytes):** A 16-bit signed integer that specifies the height, in logical units, of the font's character cell or character.

**IfWidth (2 bytes):** A 16-bit signed integer that specifies the average width, in logical units, of characters in the font.

**IfEscapement (2 bytes):** A 16-bit signed integer that specifies the angle, in tenths of degrees, between the escapement vector and the x-axis of the device. The escapement vector is parallel to the baseline of a row of text.

**IfOrientation (2 bytes):** A 16-bit signed integer that specifies the angle, in tenths of degrees, between each character's baseline and the x-axis of the device.

**IfWeight (2 bytes):** A 16-bit signed integer that specifies the weight of the font in the range 0 through 1000. For example, 400 is normal and 700 is bold. If this value is zero, a default weight is used.

**IfItalic (1 byte):** An 8-bit unsigned integer that specifies an italic font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfUnderline (1 byte):** An 8-bit unsigned integer that specifies an underlined font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfStrikeOut (1 byte):** An 8-bit unsigned integer that specifies a strikeout font if set to 0x01. MUST be set to 0x00 or 0x01.

**IfCharSet (1 byte):** An 8-bit unsigned integer that specifies the character set.

**IfOutPrecision (1 byte):** An 8-bit unsigned integer that specifies the output precision.

**IfClipPrecision (1 byte):** An 8-bit unsigned integer that specifies the clipping precision.

**IfQuality (1 byte):** An 8-bit unsigned integer that specifies the output quality.

**IfPitchAndFamily (1 byte):** An 8-bit unsigned integer that specifies the pitch and family of the font.

**IfFaceName (64 bytes):** A NULL-terminated Unicode string that specifies the typeface name of the font.

**ColorRef (4 bytes):** A COLORREF 32-bit value that specifies the RGB color used for the edit control text [\[MSDN-Win32Edit\]](#).

**Brush (4 bytes):** A COLORREF 32-bit value that specifies the RGB color used for the edit control background [\[MSDN-Win32Edit\]](#).

### 2.3.2.6 CHATDATA\_PASTEW

The CHATDATA\_PASTEW structure indicates that a user has pasted Unicode text from the clipboard into the chat session.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Type																SelPosEnd															
SelPosBegin																Size															
...																unused															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
...																															
(unused cont'd for 13 rows)																															
PastedText (variable)																															
...																															

**Type (2 bytes):** A 16-bit unsigned integer (**ChatMessageType**) specifying the type of this message. MUST be set to 0x0112 (**CHT\_PASTEW**).

**SelPosEnd (2 bytes):** A 16-bit unsigned integer that specifies the zero-based position of the first character after the last selected character. [<9>](#)

**SelPosBegin (2 bytes):** A 16-bit unsigned integer that specifies the zero-based starting position of the selection. [<10>](#)

**Size (4 bytes):** A 32-bit unsigned integer that specifies the length of the pasted text, in bytes, not including the NULL terminator.

**unused (82 bytes):** Unused. MUST be zeroed.

**PastedText (variable):** A NULL-terminated Unicode character string specifying the pasted text.

## 3 Protocol Details

### 3.1 Desktop Chat Details

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

Participants in the Desktop Chat Protocol SHOULD maintain the following state.

**Session:** An application using the Desktop Chat Protocol has a certain state associated with the chat.

**Session.Unicode:** Initialized to false. If true, the participant MUST NOT send **CHATDATA\_PASTE** or **CHATDATA\_FONTA** messages and MUST pass Unicode information in the char field of **CHATDATA\_CHAR** messages. If false, the participant MUST NOT send **CHATDATA\_PASTE** or **CHATDATA\_FONTW** messages and MUST pass ANSI or DBCS information in the char field of **CHATDATA\_CHAR** messages.

In addition to the above state, the server participant in the Desktop Chat protocol MUST maintain the following state.

Session.ClientName: The **NetBIOS** name of the client.

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

A NetDDE conversation is first established between a client and server machine as follows (see [\[MSDN-NETDDE\]](#) and [\[MSDN-DDE\]](#) for further details):

- The NetDDE server machine creates a static network DDE share using **NddeShareAdd** method. The DDE share MUST be named "CHAT\$" and MUST have the static topic name of "Chat".
- The NetDDE client machine initiates the DDE conversation using **DdeConnect** method. The DdeConnect service name MUST be of the form "\\computername\NDDE\$", where **computername** is the NetBIOS name of the server machine. The DdeConnect topic name MUST be "CHAT\$".
- The NetDDE server machine MUST acquire the client name using **DdeQueryString** method during the XTYP\_ADVSTART callback. This name is stored as **Session.ClientName**.
- Chat message data as defined in section [2.3](#) is encapsulated in NetDDE data blocks for transfer between chat participants.

**Storing message in DDE data block:** The participant uses **DdeCreateDataHandle** method to create a data block of the correct size as specified by section [2.3](#). The string specifying the data item MUST be "ChatText". The clipboard format MUST be the result from RegisterClipboardFormat ("Chat

Data"). The participant copies the **CHATDATA** message to the DDE data block using **DdeAddData method**.

**Extracting message from DDE data block:** The participant uses **DdeGetData** method to retrieve the first two bytes of data from the DDE data block, which it interprets as **ChatMessageType**. Based on this, the participant determines the message type and the remaining message size as specified by section [2.3](#) and reads the data with subsequent **DdeGetData** method calls.

**Message sent from client to server:** The client **stores** the message in a DDE data block. The DDE data is sent using **DdeClientTransaction** with XTYP\_POKE as the transaction type. The server receives this information via an XTYP\_POKE transaction processed by its **DdeCallback** function, and **extracts** the message from the DDE data block.

**Message sent from server to client:** The server **MUST** use **DdePostAdvise method** to inform the client that data is available. The DDE topic name **MUST** be "Chat" and the DDE item name **MUST** be **Session.ClientName**. The client will present the server with an XTYP\_ADVREQ transaction. The server **stores** the message and returns the resulting data block to complete the XTYP\_ADVREQ transaction. The client receives an XTYP\_ADVDATA transaction in its **DdeCallback** function, and **extracts** the message from the DDE data block.

After initialization of the NetDDE conversation, the participant **SHOULD** send a **CHATDATA\_PROTOCOL** message. If the participant supports Unicode, the participant **MUST** send a **CHATDATA\_UNICODE** message.

### 3.1.4 Higher-Layer Triggered Events

None.

### 3.1.5 Message Processing Events and Sequencing Rules

Malformed, unrecognized, and out-of-sequence packets **MUST** be ignored by the server and the client.

The participant inspects the first two bytes of the message to determine the message type, as indicated by the **ChatMessageType** enumeration and the message structures in section [2.3](#).

#### 3.1.5.1 CHATDATA\_PROTOCOL

This message **MUST** be ignored.

#### 3.1.5.2 CHATDATA\_UNICODE

Upon receiving this message, if the participant supports Unicode, the participant **MUST** set **SessionState.Unicode** to true.

#### 3.1.5.3 CHATDATA\_CHAR

Upon receiving this message, the participant **MAY** present the remote user's text using the data in the message.

#### 3.1.5.4 CHATDATA\_FONTA

Upon receiving this message, if presenting the chat data in visual form to the user, the participant **SHOULD** adjust the visual representation of the remote user's text using the data in the message.

### **3.1.5.5 CHATDATA\_PASTE**

Upon receiving this message, the participant MAY present the remote user's text using the data in the message.

### **3.1.5.6 CHATDATA\_DBCS\_STRING**

Upon receiving this message, the participant MAY present the remote user's text using the data in the message.

### **3.1.5.7 CHATDATA\_FONTW**


Upon receiving this message, if presenting the chat data in visual form to the user, the participant SHOULD adjust the visual representation of the remote user's text using the data in the message.

### **3.1.5.8 CHATDATA\_PASTEW**

Upon receiving this message, the participant MAY present the remote user's text using the data in the message.

## 4 Protocol Examples

### 4.1 Sample Chat Session



**Figure 2: Sample chat session**

In the preceding diagram, a client and server first negotiate a DDE conversation as described in section [3.1.3](#).

The following messages are then transmitted:

1. The client sends a CHATDATA\_UNICODE message, indicating Unicode support.
2. The client sends a CHATDATA\_PROTOCOL message, indicating versioning information.
3. The server sends a CHATDATA\_UNICODE message, indicating Unicode support.
4. The server sends a CHATDATA\_PROTOCOL message, indicating versioning information.
5. The client sends a CHATDATA\_FONTW message, providing the font information that is currently being used by the client. The server updates the font used for display of the client's text.
6. The server sends a CHATDATA\_FONTW message, providing the font information that is currently being used by the server. The client updates the font used for display of the server's text.

7. The client sends CHATDATA\_CHAR messages, corresponding to user input in the chat application on the client machine. The server processes these messages and displays the received text in an edit control presented to the user on the server.

## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Windows 2000 operating system Service Pack 4 (SP4)
- Windows XP operating system
- Windows Server 2003 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.3.2.1:](#) In Windows environments, **SelfPosEnd** is equivalent to the high-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<2> Section 2.3.2.1:](#) In Windows environments, **SelfPosBegin** is equivalent to the low-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<3> Section 2.3.2.2:](#) In Windows environments, these "lf" structure fields map to the LOGFONT structure [\[MSDN-LOGFONT\]](#).

[<4> Section 2.3.2.3:](#) In Windows environments, **SelfPosEnd** is equivalent to the high-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<5> Section 2.3.2.3:](#) In Windows environments, **SelfPosBegin** is equivalent to the low-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<6> Section 2.3.2.4:](#) In Windows environments, **SelfPosEnd** is equivalent to the high-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<7> Section 2.3.2.4:](#) In Windows environments, **SelfPosBegin** is equivalent to the low-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<8> Section 2.3.2.5:](#) In Windows environments, these "lf" structure fields map to the **LOGFONT** structure [\[MSDN-LOGFONT\]](#).

[<9> Section 2.3.2.6:](#) In Windows environments, **SelfPosEnd** is equivalent to the high-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

[<10> Section 2.3.2.6:](#) In Windows environments, **SelfPosBegin** is equivalent to the low-order word of the return value of the **EM\_GETSEL** window message sent to an edit control [\[MSDN-Win32Edit\]](#).

## 7 Change Tracking

This section identifies changes that were made to the [MS-DCHT] protocol document between the November 2013 and February 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">1.5 Prerequisites/Preconditions</a>	69171 Updated that the NetDDE protocol service is required to be running on the participant machines.	N	Content updated.

## 8 Index

### A

[Abstract data model](#) 18  
[Applicability](#) 7

### C

[Capability negotiation](#) 8  
[Change tracking](#) 25  
[CHATDATA\\_CHAR packet](#) 11  
[CHATDATA\\_DBCS\\_STRING packet](#) 14  
[CHATDATA\\_FONTA packet](#) 11  
[CHATDATA\\_FONTW packet](#) 15  
[CHATDATA\\_PASTEА packet](#) 13  
[CHATDATA\\_PASTEW packet](#) 17  
[CHATDATA\\_PROTOCOL packet](#) 10  
[CHATDATA\\_UNICODE packet](#) 10

### D

[Data model - abstract](#) 18  
[Data structures](#) 9

#### Details

[abstract data model](#) 18  
[higher-layer triggered events](#) 19  
[initialization](#) 18  
message processing  
  [CHATDATA\\_CHAR](#) 19  
  [CHATDATA\\_DBCS\\_STRING](#) 20  
  [CHATDATA\\_FONTA](#) 19  
  [CHATDATA\\_PASTEА](#) 20  
  [CHATDATA\\_PASTEW](#) 20  
  [CHATDATA\\_PROTOCOL](#) 19  
  [CHATDATA\\_UNICODE](#) 19  
  [CHATDATA\\_FONTW](#) 20  
  [overview](#) 19  
sequencing rules  
  [CHATDATA\\_CHAR](#) 19  
  [CHATDATA\\_DBCS\\_STRING](#) 20  
  [CHATDATA\\_FONTA](#) 19  
  [CHATDATA\\_PASTEА](#) 20  
  [CHATDATA\\_PASTEW](#) 20  
  [CHATDATA\\_PROTOCOL](#) 19  
  [CHATDATA\\_UNICODE](#) 19  
  [CHATDATA\\_FONTW](#) 20  
  [overview](#) 19  
[timers](#) 18

### E

[Examples – sample chat session](#) 21

### F

[Fields – vendor extensible](#) 8

### G

[Glossary](#) 6

### H

[Higher-layer triggered events](#) 19

### I

[Implementer – security considerations](#) 23  
[Index of security parameters](#) 23  
[Informative references](#) 7  
[Initialization](#) 18  
[Introduction](#) 6

### M

#### Message processing

[CHATDATA\\_CHAR](#) 19  
  [CHATDATA\\_PASTEА](#) 20  
  [CHATDATA\\_UNICODE](#) 19  
  [CHATDATA\\_DBCS\\_STRING](#) 20  
  [CHATDATA\\_FONTA](#) 19  
  [CHATDATA\\_FONTW](#) 20  
  [CHATDATA\\_PASTEW](#) 20  
  [CHATDATA\\_PROTOCOL](#) 19  
  [overview](#) 19

#### Messages

[ChatMessageType](#) 9  
  [data structures](#) 9  
  syntax  
    chat information  
      [CHATDATA\\_CHAR](#) 11  
      [CHATDATA\\_DBCS\\_STRING](#) 14  
      [CHATDATA\\_FONTA](#) 11  
      [CHATDATA\\_FONTW](#) 15  
      [CHATDATA\\_PASTEА](#) 13  
      [CHATDATA\\_PASTEW](#) 17  
      [overview](#) 11  
      [overview](#) 10  
    session information  
      [CHATDATA\\_PROTOCOL](#) 10  
      [CHATDATA\\_UNICODE](#) 10  
      [overview](#) 10  
  [transport](#) 9

### N

[Normative references](#) 6

### O

[Overview](#) 7

### P

[Parameters – security index](#) 23  
[Preconditions](#) 7  
[Prerequisites](#) 7

[Product behavior](#) 24

## R

References

[informative](#) 7

[normative](#) 6

[Relationship to other protocols](#) 7

## S

Security

[implementer considerations](#) 23

[parameter index](#) 23

Sequencing rules

[CHATDATA\\_CHAR](#) 19

[CHATDATA\\_DBCS\\_STRING](#) 20

[CHATDATA\\_FONTA](#) 19

[CHATDATA\\_PASTE\\_A](#) 20

[CHATDATA\\_PASTE\\_W](#) 20

[CHATDATA\\_PROTOCOL](#) 19

[CHATDATA\\_UNICODE](#) 19

[CHATDATA\\_FONT\\_W](#) 20

[overview](#) 19

[Standards assignments](#) 8

Syntax

chat information

[CHATDATA\\_CHAR](#) 11

[CHATDATA\\_DBCS\\_STRING](#) 14

[CHATDATA\\_FONTA](#) 11

[CHATDATA\\_FONT\\_W](#) 15

[CHATDATA\\_PASTE\\_A](#) 13

[CHATDATA\\_PASTE\\_W](#) 17

[overview](#) 11

[overview](#) 10

session information

[CHATDATA\\_PROTOCOL](#) 10

[CHATDATA\\_UNICODE](#) 10

[overview](#) 10

## T

[Timers](#) 18

[Tracking changes](#) 25

[Transport](#) 9

[Triggered events – higher layer](#) 19

## V

[Vendor-extensible fields](#) 8

[Versioning](#) 8