

[MS-DSCPM]: Desired State Configuration Pull Model Protocol

This topic lists the Errata found in the MS-DSCPM document since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V4.0 – 2015/10/16](#).

Errata Published*	Description																
2015/11/23	<p>In Section 2.2.2.1, Content-Type, changed from: Example: Content-Type: application/octetstring</p> <p>Changed to: Example: Content-Type: application/octet-stream</p>																
2015/11/23	<p>In Section 3.4.5, Message Processing Events and Sequencing Rules, and Section 3.5.5, Message Processing Events and Sequencing Rules, corrected the name of the resource.</p> <p>In Section 3.4.5, Message Processing Events and Sequencing Rules, changed from:</p> <table border="1"> <thead> <tr> <th>Resource</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Nodes(ConfigurationID={ConfigurationId})/SendStatusReport</td> <td>Send the status report to the server.</td> </tr> </tbody> </table> <p>Changed to:</p> <table border="1"> <thead> <tr> <th>Resource</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Node(ConfigurationID={ConfigurationId})/SendStatusReport</td> <td>Send the status report to the server.</td> </tr> </tbody> </table> <p>In Section 3.5.5, Message Processing Events and Sequencing Rules, changed from:</p> <table border="1"> <thead> <tr> <th>Resource</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Nodes(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))</td> <td>Get the status report from the server.</td> </tr> </tbody> </table> <p>Changed to:</p> <table border="1"> <thead> <tr> <th>Resource</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Node(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))</td> <td>Get the status report from the server.</td> </tr> </tbody> </table>	Resource	Description	Nodes(ConfigurationID={ConfigurationId})/SendStatusReport	Send the status report to the server.	Resource	Description	Node(ConfigurationID={ConfigurationId})/SendStatusReport	Send the status report to the server.	Resource	Description	Nodes(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))	Get the status report from the server.	Resource	Description	Node(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))	Get the status report from the server.
Resource	Description																
Nodes(ConfigurationID={ConfigurationId})/SendStatusReport	Send the status report to the server.																
Resource	Description																
Node(ConfigurationID={ConfigurationId})/SendStatusReport	Send the status report to the server.																
Resource	Description																
Nodes(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))	Get the status report from the server.																
Resource	Description																
Node(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))	Get the status report from the server.																

*Date format: YYYY/MM/DD

