

[MS-DSCPM]: Desired State Configuration Pull Model Protocol

This topic lists the Errata found in the MS-DSCPM document since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V6.0 – 2017/09/15](#).

Errata Published*	Description
2017/11/27	<p>In Section 2.2.2.2, Checksum, the value that is passed if a Checksum is not available was changed from a Null Character to an empty string "" and the example to show a BASE16 character string was updated.</p> <p>Changed from:</p> <p>The Checksum header field is defined only for use in a response message sent to a client as part of a GET request for the module and configuration. Checksum = "Checksum" : DQUOTE Check-sumvalue DQUOTE CRLF Check-sumvalue = BASE16 ; specified in [RFC4648] / 0x00 (Null Character)</p> <p>Example: "Checksum": "8eDMbsSDig15Xx+B3msvRrDa5N1njaf5smVujQjhOeI=" "Checksum": ""</p> <p>Changed to:</p> <p>The Checksum header field is defined only for use in a response message sent to a client as part of a GET request for the module and configuration. Checksum = "Checksum" : Check-SumValue CRLF Check-SumValue = DQUOTE check-basevalue DQUOTE/ DQUOTE DQUOTE Check-basevalue = BASE16 ; specified in [RFC4648] / "" (Empty String)</p> <p>Example: "Checksum": "ef52442708671f7af8dc5a1fc444a601fa25d8290d6b91cda945427b26e07a15" "Checksum": ""</p>

*Date format: YYYY/MM/DD