

## [MS-DTYP]: Windows Data Types

This topic lists the Errata found in the MS-DTYP document since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V32.0 – 2017/06/01](#).

Errata Published*	Description										
2017/09/05	<p>In Section 2.4.2.4, Well-Known SIDs, entries were added for the SIDs listed below.</p> <p>Added:</p> <table border="1" data-bbox="500 747 1404 1892"> <thead> <tr> <th data-bbox="508 747 1097 793">Constant/value</th> <th data-bbox="1105 747 1396 793">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="508 804 1097 926">KRBTGT S-1-5-21-&lt;domain&gt;-502</td> <td data-bbox="1105 804 1396 926">A service account that is used by the Key Distribution Center (KDC) service.</td> </tr> <tr> <td data-bbox="508 936 1097 1360">KEY_ADMINS S-1-5-21-&lt;domain&gt;-526</td> <td data-bbox="1105 936 1396 1360">A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted administrators should be made a member of this group.&lt;13&gt;</td> </tr> <tr> <td data-bbox="508 1371 1097 1795">ENTERPRISE_KEY_ADMINS S-1-5-21-&lt;domain&gt;-527</td> <td data-bbox="1105 1371 1396 1795">A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted enterprise administrators should be made a member of this group.&lt;14&gt;</td> </tr> <tr> <td data-bbox="508 1806 1097 1892">ALLOWED_RODC_PASSWORD_REPLICATION_GROUP S-1-5-21-&lt;domain&gt;-571</td> <td data-bbox="1105 1806 1396 1892">Members in this group can have their passwords replicated to all read-only</td> </tr> </tbody> </table>	Constant/value	Description	KRBTGT S-1-5-21-<domain>-502	A service account that is used by the Key Distribution Center (KDC) service.	KEY_ADMINS S-1-5-21-<domain>-526	A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted administrators should be made a member of this group.<13>	ENTERPRISE_KEY_ADMINS S-1-5-21-<domain>-527	A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted enterprise administrators should be made a member of this group.<14>	ALLOWED_RODC_PASSWORD_REPLICATION_GROUP S-1-5-21-<domain>-571	Members in this group can have their passwords replicated to all read-only
Constant/value	Description										
KRBTGT S-1-5-21-<domain>-502	A service account that is used by the Key Distribution Center (KDC) service.										
KEY_ADMINS S-1-5-21-<domain>-526	A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted administrators should be made a member of this group.<13>										
ENTERPRISE_KEY_ADMINS S-1-5-21-<domain>-527	A security group for delegated write access on the msdsKeyCredentialLink attribute only. The group is intended for use in scenarios where trusted external authorities (for example, Active Directory Federated Services) are responsible for modifying this attribute. Only trusted enterprise administrators should be made a member of this group.<14>										
ALLOWED_RODC_PASSWORD_REPLICATION_GROUP S-1-5-21-<domain>-571	Members in this group can have their passwords replicated to all read-only										

Errata Published*	Description	
		domain controllers in the domain.<15>
	DENIED_RODC_PASSWORD_REPLICATION_GROUP S-1-5-21-<domain>-572	Members in this group cannot have their passwords replicated to all read-only domain controllers in the domain.<16>
	ML_SECURE_PROCESS S-1-16-28672	A secure process integrity level.<33>
<p>&lt;13&gt; Section 2.4.2.4: Not supported in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, or Windows Server 2012 R2.</p> <p>&lt;14&gt; Section 2.4.2.4: Not supported in Windows NT, Windows 2000, Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, or Windows Server 2012 R2.</p> <p>&lt;15&gt; Section 2.4.2.4: Not supported in Windows NT, Windows 2000, Windows XP, Windows Server 2003, or Windows Vista.</p> <p>&lt;16&gt; Section 2.4.2.4: Not supported in Windows NT, Windows 2000, Windows XP, Windows Server 2003, or Windows Vista.</p> <p>&lt;33&gt; Section 2.4.2.4: Not supported in Windows NT, Windows 2000, Windows XP, or Windows Server 2003.</p>		

\*Date format: YYYY/MM/DD