

[MS-NCT-Diff]:

Network Cost Transfer Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
7/14/2016	1.0	New	Released new document.
6/1/2017	2.0	Major	Significantly changed the technical content.
9/15/2017	3.0	Major	Significantly changed the technical content.
12/1/2017	3.0	None	No changes to the meaning, language, or formatting of the technical content.
9/12/2018	4.0	Major	Significantly changed the technical content.
4/7/2021	5.0	Major	Significantly changed the technical content.
6/25/2021	6.0	Major	Significantly changed the technical content.
4/23/2024	7.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	4
1.1	Glossary	4
1.2	References	4
1.2.1	(Updated Section) Normative References	5
1.2.2	Informative References	5
1.3	Overview	5
1.4	Relationship to Other Protocols	5
1.5	Prerequisites/Preconditions	5
1.6	Applicability Statement	5
1.7	Versioning and Capability Negotiation	6
1.8	Vendor-Extensible Fields	6
1.9	Standards Assignments	6
2	Messages	7
2.1	Transport	7
2.2	Message Syntax	7
2.2.1	Network Cost IE	7
2.2.1.1	Cost Flags	7
2.2.1.2	Cost Level	8
2.2.2	Tethering Identifier IE	8
3	Protocol Details	10
3.1	AP Role Details	10
3.1.1	Abstract Data Model	10
3.1.2	Timers	10
3.1.3	Initialization	10
3.1.4	Higher-Layer Triggered Events	10
3.1.5	Message Processing Events and Sequencing Rules	10
3.1.6	Timer Events	10
3.1.7	Other Local Events	10
3.2	Client Role Details	10
3.2.1	Abstract Data Model	10
3.2.2	Timers	10
3.2.3	Initialization	11
3.2.4	Higher-Layer Triggered Events	11
3.2.5	Message Processing Events and Sequencing Rules	11
3.2.6	Timer Events	11
3.2.7	Other Local Events	11
4	Protocol Examples	12
5	Security	14
5.1	Security Considerations for Implementers	14
5.2	Index of Security Parameters	14
6	(Updated Section) Appendix A: Product Behavior	15
7	Change Tracking	16
8	Index	17

1 Introduction

The Network Cost Transfer Protocol enables an IEEE 802.11 access point (AP) to communicate the network cost and tethering identification information about the AP type to wireless clients. It defines two vendor-specific Information Elements within the 802.11 beacon and probe response to relay this information to the client.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

802.11 Access Point (AP): Any entity that has IEEE 802.11 functionality and provides access to the distribution services, via the wireless medium for associated stations (STAs).

Beacon: A management frame that contains all of the information required to connect to a network. In a WLAN, Beacon frames are periodically transmitted to announce the presence of the network.

information element (IE): A unit of information transmitted as part of the management frames in the IEEE 802.11 [IEEE802.11-2012] protocol. Wireless devices, such as access points, communicate descriptive information about themselves in the form of one or more IEs in their management frames.

Medium Access Control (MAC): A data communication protocol sublayer that is part of the seven-layer OSI model data-link layer (layer 2). It provides addressing and channel access control mechanisms that make it possible for several terminals or network nodes to communicate within a multipoint network, typically a local area network (LAN).

network cost: Information about how the Internet service provider bills customers for data usage on the network.

organizationally unique identifier (OUI): A unique 24-bit string that uniquely identifies a vendor, manufacturer, or organization on a worldwide basis, as specified in [IEEE-OUI]. The OUI is used to help distinguish both physical devices and software, such as a network protocol, that belong to one entity from those that belong to another.

Probe Response: A frame that contains the advertisement IE for a device. The Probe Response is sent in response to a Probe Request. The Probe Response frame is defined in the Wi-Fi Peer-to-Peer (P2P) Specification v1.2 [WF-P2P1.2] section 4.2.3.

tether: Enables a device to gain access to the Internet by establishing a connection with another device that is connected to the Internet.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.2.1 (Updated Section) Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[IEEE-OUI] IEEE Standards Association, "IEEE MAC Address Block Large (MA-L) Field Registration Authority Public Listing", <http://standards-oui.ieee.org/oui/oui.txt>

[IEEE802.11-2007] Institute of Electrical and Electronics Engineers, "~~Standard for Information Technology~~ Telecommunications and Information Exchange Between Systems - Local and Metropolitan Area Networks - Specific Requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications", ~~ANSI/IEEE Std 802.11-2007~~, <http://standards.ieee.org/findstds/standard/802.11-2007.html/3605/>

Note ~~There is a charge~~ [Subscription Login or purchase](#) to download this document.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/info/rfc2119.txt>

1.2.2 Informative References

None.

1.3 Overview

The Network Cost Transfer Protocol enables an IEEE 802.11 access point (AP) to communicate the network cost and information about the AP type to clients. It defines two vendor-specific information elements (IEs), Network Cost and Tethering Identifier, within the 802.11 Beacon and Probe Response to relay this information to the client. Tethering allows a Windows device to share Internet connectivity from one interface over a Wi-Fi adapter, acting as a network to which other devices can connect.

Network Cost IE is used by clients to determine whether data transferred on that specific connection is metered (section 2.2.1). The Tethering Identifier IE is used to differentiate tethering (device-based) networks from stand-alone APs (section 2.2.2). The difference can then be used to vary the experience in implementation-defined ways.

1.4 Relationship to Other Protocols

The Network Cost Transfer Protocol extends the IEEE802.11 standard, whose conventions are applied as specified in [IEEE802.11-2007]. The Network Cost Transfer Protocol introduces a specific use for one of that protocol's reserved information element types, and it defines additional Medium Access Control (MAC) layer abstract service primitives for managing the configuration, transmission, and receipt of these new information elements.

1.5 Prerequisites/Preconditions

The Network Cost Transfer Protocol requires APs to adhere to 802.11 standard specifications. The AP SHOULD have knowledge about the metered state of its network connection. This state may be explicitly configured, inferred from media type, or obtained using any other relevant means.

1.6 Applicability Statement

This protocol is only applicable to APs that support tethering. The client is required to support connecting to Wi-Fi networks. Lastly, the Tethering Identifier information element (IE) only applies to multi-purpose devices capable of acting as access points, not to dedicated network hardware.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

Parameter	Value	Reference
OUI	00-50-F2	As specified in [IEEE-OUI]

2 Messages

2.1 Transport

The two vendor-specific information elements in the Network Cost Transfer Protocol are transmitted as part of IEEE802.11 Beacons or Probe Responses. There are no requirements for the order of the information elements and it is not necessary that both be used at the same time.

The format of information elements is specified in [IEEE802.11-2007] section 7.3.2. The format and processing of Beacon or Probe Response frames are also specified in [IEEE802.11-2007].

2.2 Message Syntax

The following sections specify Network Cost Transfer Protocol Message syntax.

2.2.1 Network Cost IE

The **Network Cost IE** structure SHOULD<1> be used by clients to determine whether data transferred on that specific connection is metered. The structure of the Network Cost information element (IE) is shown in the following packet.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Attribute_ID										Length						OUI															
...										OUI_Type						Cost_Level						Reserved									
Cost_Flags										Reserved																					

Attribute_ID (1 byte): Contains the ID of the element as specified [IEEE802.11-2007] section 7.3.2. It MUST contain a value of 221 (0xDD), identifying a vendor-specific element (as specified in [IEEE802.11-2007] table 26) in which the vendor is identified by an IEEE-issued OUI.

Length (1 byte): The total length of the subsequent fields. This value MUST be 0x08.

OUI (3 bytes): The IEEE-assigned organizationally unique identifier (OUI) for Microsoft. The **OUI** field MUST contain a value of (00:50:F2) as specified in [IEEE-OUI].

OUI_Type (1 byte): A packet subtype within the universe specific to a specific OUI value. For the Network Cost IE, the OUI Type MUST contain a value of 0x11.

Cost_Level (1 byte): A value indicating the metering type of the network connection, as specified in section 2.2.1.2.

Reserved (1 byte): SHOULD be 0.

Cost_Flags (1 byte): Flags that indicate possible states of the network connection, as specified in section 2.2.1.1.

Reserved (1 byte): SHOULD be 0.

2.2.1.1 Cost Flags

The following table shows the possible **cost flags** that can be represented in the IE:

Value	Name	Description
0x00	Unknown	The usage is unknown or unrestricted.
0x01	Over Data Limit	Usage has exceeded the data limit of the metered network; different network costs or conditions might apply.
0x02	Congested	The network operator is experiencing or expecting heavy load.
0x04	Roaming	The tethering connection is roaming outside the provider's home network or affiliates.
0x08	Approaching Data Limit	Usage is near the data limit of the metered network; different network costs or conditions might apply once the limit is reached.

If the AP is aware that any of these states applies to its network connection, it SHOULD indicate the corresponding flag in all Beacons and Probe Responses.

2.2.1.2 Cost Level

The following table shows the possible **cost levels** that can be represented in the IE:

Value	Name	Description
0x00	Unknown	The connection cost is unknown.
0x01	Unrestricted	The connection is unlimited and has unrestricted usage constraints.
0x02	Fixed	Usage counts toward a fixed allotment of data which the user has already paid for (or agreed to pay for).
0x04	Variable	The connection cost is on a per-byte basis.

The AP MUST indicate the cost level that most accurately describes the network's cost and metering type, based on configuration or other information sources.<2>

2.2.2 Tethering Identifier IE

The Tethering Identifier information element (IE) SHOULD<3> be used to differentiate tethering (device-based) networks from stand-alone APs. The structure of the Tethering Identifier IE is shown in the following packet.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Attribute_ID										Length										OUI											
...										OUI_Type										Type											
Length															MAC_Address																
...																															

Attribute_ID (1 byte): Contains the ID of the element as specified [IEEE802.11-2007] section 7.3.2. It MUST contain a value of 221 (0xDD), identifying a vendor-specific element (as specified in [IEEE802.11-2007] table 26) in which the vendor is identified by an IEEE-issued OUI.

Length (1 byte): The length of the subsequent fields. This value MUST be 14 (0x0E).

OUI (3 bytes): The IEEE-assigned organizationally unique identifier (OUI) for Microsoft. The **OUI** field MUST contain a value of (00:50:F2) as specified in [IEEE-OUI].

OUI_Type (1 byte): A packet subtype within the universe specific to a specific OUI value. For the Tethering Identifier IE, the OUI Type MUST contain a value of 18 (0x12).

Type (2 bytes): Used to specify that the network is broadcasted as tethered. The **Type** field MUST contain a value of 43 (0x2B).

Length (2 bytes): Contains the length of the **MAC_Address** field in octets. This value MUST be 6 (0x06).

MAC_Address (6 bytes): Contains the Medium Access Control (MAC) address of the AP.

3 Protocol Details

3.1 AP Role Details

To compensate for an unreliable transmission over the wireless medium, the information elements SHOULD be contained in each Beacon frame and Probe Response.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

The 802.11 Access Point (AP) MUST have initial information about the cost state of the upstream flow of data and convey the appropriate flag in the IE. This information may be administratively configured, inferred from media type, or acquired by other means.

3.1.4 Higher-Layer Triggered Events

If the metering state of the network changes, the AP SHOULD immediately reflect the new value in all future Beacons and Probe Responses.

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Client Role Details

The client acquires information about the network during network discovery and connection. The client role is triggered when in range of an 802.11 Access Point (AP) and finding the relevant information element in the Beacon or Probe Response frame.

3.2.1 Abstract Data Model

For each AP to which the client is currently connected, the client SHOULD maintain the current estimated cost state and network type.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

When in range of an 802.11 Access Point (AP), the client SHOULD inspect the Beacon and Probe Response frames for the information elements defined by this protocol. If they are present, they SHOULD inform the client's data about the network. If not, the client may infer value using implementation-specific defaults.

3.2.5 Message Processing Events and Sequencing Rules

If these information elements are found, the local knowledge of the current network SHOULD be updated with the information they contain. Use of this information is implementation-dependent and handled by higher-layer protocols.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

The following table shows some sample cost attribute values:

Name	Cost Flag	Cost Level	Description
Default WLAN	0x00	0x01	Unrestricted connection; standard WLAN backed by fixed broadband.
Portable Hotspot Default	0x00	0x02	Metered network; limit unknown or not yet reached; reasonable default for mobile broadband connections without other information.
Over Limit / Throttled	0x01	0x01	User has exceeded data limit; speed is reduced, but no further usage limitation applies.
Over Limit / Charges	0x01	0x04	User has exceeded data limit; additional usage incurs incremental charges.
Portable Hotspot / Roaming	0x04	0x04	Connection is roaming; incremental charges apply due to network state.

The following is an example of the Network Cost IE conveyed in a Beacon or Probe Response frame for the over data limit cost flag.

Offset (hex)	Value (hex)	Field
0000	DD	Element ID
0001	08	Length
0002	00	OUI (Microsoft)
0003	50	
0004	F2	
0005	11	OUI Type
0006	02	Cost Level (Fixed)
0007	00	Reserved
0008	01	Cost Flag (Over Data Limit)
0009	00	Reserved

Figure 1: Example of the Network Cost IE

The following is an example of the Tethering Identifier IE conveyed in a Beacon or Probe Response frame.

Offset (hex)	Value (hex)	Field
0000	DD	Element ID
0001	0E	Length
0002	00	OUI (Microsoft)
0003	50	
0004	F2	
0005	12	OUI Type
0006	00	Type
0007	2B	
0008	00	Length
0009	06	
0010	68	MAC Address
0011	5D	
0012	43	
0013	0B	
0014	66	
0015	12	

Figure 2: Example of the Tethering Identifier IE

5 Security

5.1 Security Considerations for Implementers

The information transferred by this protocol is transmitted unencrypted, even for a secured AP. Do not include sensitive information.

5.2 Index of Security Parameters

None.

6 (Updated Section) Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Windows 8 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system
- Windows Server 2016 operating system
- Windows Server 2019 operating system
- Windows Server 2022 operating system
- Windows 11 operating system
- Windows Server 2025 operating system

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

<1> Section 2.2.1: Windows 8 and Windows Server 2012 could consume but not generate the IE. They implemented only the client role.

<2> Section 2.2.1.2: Windows acting as APs always set the cost to Fixed with no flags set, regardless of the actual state.

<3> Section 2.2.2: Windows 8 and Windows Server 2012 did not implement this IE.

7 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
6 Appendix A: Product Behavior	Added Windows Server 2025 to the list of applicable products.	Major

8 Index

A

Applicability 5

C

Capability negotiation 6
Change tracking 16

F

Fields - vendor-extensible 6

G

Glossary 4

I

Implementer - security considerations 14
Index of security parameters 14
Informative references 5
Introduction 4

M

Messages
 Network Cost IE 7
 Tethering Identifier IE 8
 transport 7

N

Network Cost IE message 7
Normative references 5

O

Overview (synopsis) 5

P

Parameters - security index 14
Preconditions 5
Prerequisites 5
Product behavior 15

R

References 4
 informative 5
 normative 5
Relationship to other protocols 5

S

Security
 implementer considerations 14
 parameter index 14
Standards assignments 6

T

Tethering Identifier IE message 8
Tracking changes 16
Transport 7

V

Vendor-extensible fields 6
Versioning 6