

## [MS-OAPXBC]: OAuth 2.0 Protocol Extensions for Broker Clients

This topic lists the Errata found in [MS-OAPXBC] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V1.0 – 2015/10/16](#).

Errata Published*	Description
2016/02/22	<p>In Section 3.2.5.1.2.3, Processing Details, updated alternateSecurityIdentifiers to altSecurityIdentities.</p> <p>Changed from: The server finds the msDS-Device object in Active Directory that has an alternateSecurityIdentifiers value matching the value of the x5c parameter of the request header.</p> <p>Changed to: The server finds the msDS-Device object in Active Directory that has an altSecurityIdentities value matching the value of the x5c parameter of the request header.</p>
2016/02/22	<p>In Section 3.2.5.1.2.1.2, User JWT Authentication, removed the redundant "use" fields.</p> <p>Changed from: assertion (REQUIRED): A signed JWT used to authenticate the user. The JWT fields for the JWT provided in the assertion field MUST be given the following values: iss (REQUIRED): The username of the user for which the primary refresh token is requested. iat (REQUIRED): See [OIDCCore] section 6.1. exp (REQUIRED): See [OIDCCore] section 6.1. use (REQUIRED): "ngc" aud (REQUIRED): The Issuer Identifier ([OIDCCore] section 1.2) of the server that the client is sending the request to. use (REQUIRED): "ngc"</p> <p>Changed to: assertion (REQUIRED): A signed JWT used to authenticate the user. The JWT fields for the JWT provided in the assertion field MUST be given the following values: iss (REQUIRED): The username of the user for which the primary refresh token is requested. iat (REQUIRED): See [OIDCCore] section 6.1. exp (REQUIRED): See [OIDCCore] section 6.1. aud (REQUIRED): The Issuer Identifier ([OIDCCore] section 1.2) of the server that the client is sending the request to.</p>
2016/02/22	<p>In Section 4.2, Obtain a Primary Refresh Token, and Section 4.3, Obtain an Access Token, corrected the example for grant_type.</p> <p>Changed from:</p>

<b>Errata Published*</b>	<b>Description</b>
	grant_type=urn:ietf:params:oauth:grant-type:jwt-bearer  Changed to: grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Ajwt-bearer

\* Date format: YYYY/MM/DD