[MS-RAI]: Remote Assistance Initiation Protocol

This topic lists the Errata found in [MS-RAI] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.

<mark>₪</mark>RSS ₪Atom

Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version V9.0 - 2018/09/12.

Errata Published*	Description		
2019/06/24	In Section 2.2.2, Remote Assistance Connection String 2, details for the URI attribute have been added for the Listener node.		
	Changed from:		
	3. The Transport Node has Listener child Nodes that give information about the Server IP and port. This Listener node $<$ L> has the following attributes.		
	Value	Meaning	
	P	Port: The dynamic port on which the Remote Assistance connection could happen.	
	Ν	Server Name: The name/IP address of the server, that is, the novice computer.	
	Changed to:		
	3. The Transport Node has Listener child Nodes that give information about the Server IP and port. This Listener node $<$ L> has the following attributes.		
	Value	Meaning	
	P	Port: The dynamic port on which the Remote Assistance connection could happen.	
	Ν	Server Name: The name/IP address of the server, that is, the novice computer.	
	U	URI: The full URI if websocket listener is enabled. The U (URI) is used instead	

Errata Published*	Description	
		of the P (port) attribute. N (server name) attribute is still included.

*Date format: YYYY/MM/DD