

[MS-RTPDT]: Real-Time Transport Protocol (RTP/RTCP): DTMF Digits, Telephony Tones and Telephony Signals Data Extensions

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard

specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/08/2008	0.1		Initial Availability.
05/16/2008	0.1.1	Editorial	Revised and edited the technical content.
06/20/2008	1.0	Major	Updated and revised the technical content.
07/25/2008	1.0.1	Editorial	Revised and edited the technical content.
08/29/2008	1.0.2	Editorial	Revised and edited the technical content.
10/24/2008	1.0.3	Editorial	Revised and edited the technical content.
12/05/2008	1.1	Minor	Updated the technical content.
01/16/2009	1.2	Minor	Updated the technical content.
02/27/2009	1.3	Minor	Updated the technical content.
04/10/2009	1.3.1	Editorial	Revised and edited the technical content.
05/22/2009	1.3.2	Editorial	Revised and edited the technical content.
07/02/2009	1.3.3	Editorial	Revised and edited the technical content.
08/14/2009	1.3.4	Editorial	Revised and edited the technical content.
09/25/2009	1.3.5	Editorial	Revised and edited the technical content.
11/06/2009	1.3.6	Editorial	Revised and edited the technical content.
12/18/2009	1.3.7	Editorial	Revised and edited the technical content.
01/29/2010	1.4	Minor	Updated the technical content.
03/12/2010	1.4.1	Editorial	Revised and edited the technical content.
04/23/2010	1.4.2	Editorial	Revised and edited the technical content.
06/04/2010	1.4.3	Editorial	Revised and edited the technical content.
07/16/2010	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2010	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
11/19/2010	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	1.4.3	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	1.5	Minor	Clarified the meaning of the technical content.
09/23/2011	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
03/30/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/12/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
01/31/2013	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
08/08/2013	1.5	No change	No changes to the meaning, language, or formatting of the technical content.

Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	7
1.3 Overview	7
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor-Extensible Fields	8
1.9 Standards Assignments	8
2 Messages	9
2.1 Transport	9
2.2 Message Syntax	9
2.2.1 DTMF Telephony Event	9
3 Protocol Details	10
3.1 Common Details	10
3.1.1 Abstract Data Model	10
3.1.2 Timers	10
3.1.3 Initialization	10
3.1.4 Higher-Layer Triggered Events	10
3.1.5 Message Processing Events and Sequencing Rules	11
3.1.6 Timer Events	11
3.1.7 Other Local Events	11
3.2 Receiver Details	11
3.2.1 Abstract Data Model	11
3.2.2 Timers	11
3.2.3 Initialization	11
3.2.4 Higher-Layer Triggered Events	11
3.2.5 Message Processing Events and Sequencing Rules	11
3.2.6 Timer Events	11
3.2.7 Other Local Events	11
3.3 Sender Details	11
3.3.1 Abstract Data Model	12
3.3.2 Timers	12
3.3.3 Initialization	12
3.3.4 Higher-Layer Triggered Events	12
3.3.5 Message Processing Events and Sequencing Rules	12
3.3.6 Timer Events	12
3.3.7 Other Local Events	12
4 Protocol Examples	13
5 Security	14
5.1 Security Considerations for Implementers	14
5.2 Index of Security Parameters	14
6 Appendix A: Product Behavior	15

7	Change Tracking.....	16
8	Index	17

1 Introduction

The Real-Time Transport Protocol (RTP/RTCP): DTMF Digits, Telephony Tones, and Telephony Signals Data Extensions Protocol (RTPDTE) is an extension to [\[RFC4733\]](#). RTPDTE describes the payload format needed to carry **DTMF** digits, tones, and signals in RTP packets over a network transport.

Any behavior not explicitly defined in this document means the behavior defined in [\[RFC4733\]](#) must be used.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are specific to this document:

Dual Tone Multiple Frequency (DTMF): The signaling system used in telephony systems, in which each digit is associated with two specific frequencies. Most commonly associated with telephone touch-tone keypads.

Real-Time Transport Protocol (RTP): A network protocol that provides end-to-end network transport functions suitable for applications transmitting real-time data, such as audio and video.

Session Description Protocol (SDP): A protocol that is used for session announcement, session invitation, and other forms of multimedia session initiation [\[MS-SDP\]](#).

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

A reference marked "(Archived)" means that the reference document was either retired and is no longer being maintained or was replaced with a new document that provides current implementation details. We archive our documents online [\[Windows Protocol\]](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-RTPME] Microsoft Corporation, "[Real-Time Transport Protocol \(RTP/RTCP\): Microsoft Extensions](#)".

[MS-RTPRAD] Microsoft Corporation, "[Real-Time Transport Protocol \(RTP/RTCP\): Redundant Audio Data Extensions](#)".

[MS-SDP] Microsoft Corporation, "[Session Description Protocol \(SDP\) Extensions](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC4733] Schulzrinne, H., "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals", RFC 4733, December 2006, <http://www.ietf.org/rfc/rfc4733.txt>

1.2.2 Informative References

None.

1.3 Overview

The RTP/RTCP: DTMF Digits, Telephony Tones, and Telephony Signals Data Extensions protocol describes a mechanism for transmission of in-band and out-of-band telephony digits, tones, and signals. It is an extension to [\[RFC4733\]](#).

The RTPDPT protocol is limited to telephony signals using out-of-band transmission. The in-band transmission of digits and tones is not supported by this protocol.

1.4 Relationship to Other Protocols

This protocol relies on **RTP** as specified in [\[MS-RTPME\]](#) as its transport mechanism. This protocol can be used to communicate signaling DTMF telephony events between clients and gateways using the RTP payload.

1.5 Prerequisites/Preconditions

This protocol is a payload of RTP; therefore, a valid RTP session must be established between a client and a gateway.

Furthermore, because of the dynamic payload typing of the telephony events, out-of-band negotiation is required to bind the payload type of the RTP payload to the telephony events. This is done using the Session Description Protocol [\[MS-SDP\]](#).

1.6 Applicability Statement

This protocol is applicable wherever telephony digits, tones, or signals need to be sent or consumed either by remote clients or through gateways.

1.7 Versioning and Capability Negotiation

- Supported Transports: This protocol is sent using the RTP transport mechanism [\[MS-RTPME\]](#).
- Protocol Versions: This protocol, as a format of an RTP payload, does not provide for versioning information within the scope of the protocol itself. However, as a part of the RTP payload, any versioning information about the RTP level will apply.
- Security and Authentication Methods: This specification does not describe any security or authentication methods. Security and authentication are dependent on the security method, authentication method, or both methods used by the RTP version 2 protocol.

- Localization: None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The RTP/RTCP: DTMF Digits, Telephony Tones and Telephony Signals Data Extensions protocol MUST be sent using RTP as specified in [\[MS-RTPME\]](#) as its transport. This protocol assumes that a successful RTP session has been established with valid payload information.

The **Session Description Protocol (SDP)** [\[MS-SDP\]](#) MUST be used to negotiate the payload type information.

2.2 Message Syntax

The structure and syntax of the RTP/RTCP: DTMF Digits, Telephony Tones and Telephony Signals Data Extensions protocol is defined in [\[RFC4733\]](#) section 2.3.

2.2.1 DTMF Telephony Event

The DTMF Telephony Event format is described in [\[RFC4733\]](#) section 2.3.

3 Protocol Details

The RTP/RTCP: DTMF Digits, Telephony Tones, and Telephony Signals Extensions protocol conforms more to the "sender-receiver" paradigm than the classic "client-server" paradigm. More specifically, it is appropriate to discuss in terms of the receiver of the telephony signals and the sender of the telephony signals.

This specification covers the common details between the sender and receiver. It then provides the specifics of the sender and receiver details.

3.1 Common Details

In [\[RFC4733\]](#), out-of-band negotiation of telephony signal information is required to establish a session. During this negotiation, both payload types and the clock rate of the telephony signals are negotiated as described in [\[RFC4733\]](#) section 2.5.1.1 using SDP for out-of-band negotiation. While dynamic payload type binding is required, both the sender and receiver of message blocks conforming to RTPDT MUST fix the telephony signaling information at 8,000 Hertz. Dynamic negotiation of the clock frequency of the DTMF payload MUST NOT be used.

[\[RFC4733\]](#) allows a "zero" duration in the payload of an RTP packet for state events. Endpoints using RTPDT MUST NOT send telephony events with a "zero" duration. Telephony events include the state and nonstate events.

All event duration values MUST NOT exceed the maximum duration expressible in the duration field of the payload format as described in [\[RFC4733\]](#) section 2.3.5.

Redundancy support as described in [\[MS-RTPRAD\]](#) MUST NOT be used. Integrity for the payload is not defined by this specification; see [\[MS-RTPRAD\]](#) section 2.2 for payload integrity information.

Multiple payload type binding for different telephony events MUST NOT be used. There MUST be only one telephony event binding for a payload type. The payload type binding MUST be symmetrical. This means the receive payload type and send payload type MUST be the same. Asymmetrical payload type information MUST NOT be used.

RTPDT supports only the telephony event. An in-band telephony tone transmission MUST NOT be used.

All clock frequencies for DTMF signals, tones, and digits MUST be fixed at 8,000 Hertz.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

There are no sequence rules or processing event requirements for this protocol above that described in [\[RFC4733\]](#).

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Receiver Details

Redundant payload support as described in [\[MS-RTPRAD\]](#) MUST NOT be used.

Multiple events per the RTP block MUST NOT be used.

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

There are no sequence rules or processing event requirements for this protocol above that described in [\[RFC4733\]](#).

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

3.3 Sender Details

Implementation for this protocol MUST NOT generate redundant blocks as described in [\[MS-RTPRAD\]](#).

The sender MUST NOT pack multiple DTMF payloads into a single RTP packet.

The sender MUST NOT generate a DTMF event whose duration exceeds the maximum expressible duration as specified in [\[RFC4733\]](#) section 2.3.5.

The sender MUST NOT generate a DTMF event payload with a zero duration.

3.3.1 Abstract Data Model

None.

3.3.2 Timers

None.

3.3.3 Initialization

None.

3.3.4 Higher-Layer Triggered Events

None.

3.3.5 Message Processing Events and Sequencing Rules

There are no sequence rules or processing event requirements for this protocol above that described in [\[RFC4733\]](#).

3.3.6 Timer Events

None.

3.3.7 Other Local Events

None.

4 Protocol Examples

The following is an example of the SDP negotiation for the DTMF events.

```
m=audio 51712 RTP/AVP 114 111 112 115 116 4 8 0 97 101
...
a=rtpmap:114 x-msrta/16000
a=fmtp:114 bitrate=29000
a=rtpmap:111 SIREN/16000
a=fmtp:111 bitrate=16000
a=rtpmap:112 G7221/16000
a=fmtp:112 bitrate=24000
a=rtpmap:115 x-msrta/8000
a=fmtp:115 bitrate=11800
a=rtpmap:116 AAL2-G726-32/8000
a=rtpmap:4 G723/8000
a=rtpmap:8 PCMA/8000
a=rtpmap:0 PCMU/8000
a=rtpmap:97 RED/8000
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-16
```

The preceding sample uses the default DTMF payload type for Microsoft Office Communicator (PT=101). This would result in the following payload being generated (and expected).

```

0             1             2             3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|V=2|P|X| CC |M| PT | sequence number |
| | | | |0| 101 | | | | | | | | | | |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|
| timestamp
|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|
| synchronization source (SSRC) identifier
|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|
| event |E R| volume | duration
| 1 | |1 0| 20 | 1760
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
```

5 Security

5.1 Security Considerations for Implementers

There are no additional protocol considerations beyond those described in [\[RFC4733\]](#).

5.2 Index of Security Parameters

No security parameters are used by this protocol.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Windows 2000 operating system
- Windows XP operating system
- Windows Server 2003 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

Abstract data model
 receiver ([section 3.1.1](#) 10, [section 3.2.1](#) 11)
 sender ([section 3.1.1](#) 10, [section 3.3.1](#) 12)
[Applicability](#) 7

C

[Capability negotiation](#) 7
[Change tracking](#) 16

D

Data model - abstract
 receiver ([section 3.1.1](#) 10, [section 3.2.1](#) 11)
 sender ([section 3.1.1](#) 10, [section 3.3.1](#) 12)
[DTMF Telephony Event format](#) 9

E

[Examples - overview](#) 13

F

[Fields - vendor-extensible](#) 8

G

[Glossary](#) 6

H

Higher-layer triggered events
 receiver ([section 3.1.4](#) 10, [section 3.2.4](#) 11)
 sender ([section 3.1.4](#) 10, [section 3.3.4](#) 12)

I

[Implementer - security considerations](#) 14
[Index of security parameters](#) 14
[Informative references](#) 7
Initialization
 receiver ([section 3.1.3](#) 10, [section 3.2.3](#) 11)
 sender ([section 3.1.3](#) 10, [section 3.3.3](#) 12)
[Introduction](#) 6

L

Local events
 receiver ([section 3.1.7](#) 11, [section 3.2.7](#) 11)
 sender ([section 3.1.7](#) 11, [section 3.3.7](#) 12)

M

Message processing
 receiver ([section 3.1.5](#) 11, [section 3.2.5](#) 11)
 sender ([section 3.1.5](#) 11, [section 3.3.5](#) 12)
Messages

syntax
 [DTMF Telephony Event format](#) 9
 [overview](#) 9
 [transport](#) 9

N

[Normative references](#) 6

O

[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 14
[Preconditions](#) 7
[Prerequisites](#) 7
[Product behavior](#) 15

R

Receiver
 abstract data model ([section 3.1.1](#) 10, [section 3.2.1](#) 11)
 higher-layer triggered events ([section 3.1.4](#) 10, [section 3.2.4](#) 11)
 initialization ([section 3.1.3](#) 10, [section 3.2.3](#) 11)
 local events ([section 3.1.7](#) 11, [section 3.2.7](#) 11)
 message processing ([section 3.1.5](#) 11, [section 3.2.5](#) 11)
 overview ([section 3.1](#) 10, [section 3.2](#) 11)
 sequencing rules ([section 3.1.5](#) 11, [section 3.2.5](#) 11)
 timer events ([section 3.1.6](#) 11, [section 3.2.6](#) 11)
 timers ([section 3.1.2](#) 10, [section 3.2.2](#) 11)
References
 [informative](#) 7
 [normative](#) 6
[Relationship to other protocols](#) 7

S

Security
 [implementer considerations](#) 14
 [parameter index](#) 14
Sender
 abstract data model ([section 3.1.1](#) 10, [section 3.3.1](#) 12)
 higher-layer triggered events ([section 3.1.4](#) 10, [section 3.3.4](#) 12)
 initialization ([section 3.1.3](#) 10, [section 3.3.3](#) 12)
 local events ([section 3.1.7](#) 11, [section 3.3.7](#) 12)
 message processing ([section 3.1.5](#) 11, [section 3.3.5](#) 12)
 overview ([section 3.1](#) 10, [section 3.3](#) 11)
 sequencing rules ([section 3.1.5](#) 11, [section 3.3.5](#) 12)
 timer events ([section 3.1.6](#) 11, [section 3.3.6](#) 12)

timers ([section 3.1.2](#) 10, [section 3.3.2](#) 12)
Sequencing rules
 receiver ([section 3.1.5](#) 11, [section 3.2.5](#) 11)
 sender ([section 3.1.5](#) 11, [section 3.3.5](#) 12)
[Standards assignments](#) 8
Syntax
 [DTMF Telephony Event format](#) 9
 [overview](#) 9

T

Timer events
 receiver ([section 3.1.6](#) 11, [section 3.2.6](#) 11)
 sender ([section 3.1.6](#) 11, [section 3.3.6](#) 12)
Timers
 receiver ([section 3.1.2](#) 10, [section 3.2.2](#) 11)
 sender ([section 3.1.2](#) 10, [section 3.3.2](#) 12)
[Tracking changes](#) 16
[Transport](#) 9
Triggered events - higher-layer
 receiver ([section 3.1.4](#) 10, [section 3.2.4](#) 11)
 sender ([section 3.1.4](#) 10, [section 3.3.4](#) 12)

V

[Vendor-extensible fields](#) 8
[Versioning](#) 7