

# [MS-UPMC]: UPnP Device and Service Templates: Media Property and Compatibility Extensions

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
01/29/2010	0.1	Major	First Release.
03/12/2010	0.1.1	Editorial	Revised and edited the technical content.
04/23/2010	0.1.2	Editorial	Revised and edited the technical content.
06/04/2010	0.1.3	Editorial	Revised and edited the technical content.
07/16/2010	0.1.3	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	1.0	Major	Significantly changed the technical content.
10/08/2010	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	1.0	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	1.1	Minor	Clarified the meaning of the technical content.
09/23/2011	1.1	No change	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	2.0	Major	Significantly changed the technical content.
03/30/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/12/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/31/2013	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
08/08/2013	3.0	Major	Significantly changed the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
11/14/2013	3.1	Minor	Clarified the meaning of the technical content.
02/13/2014	4.0	Major	Significantly changed the technical content.
05/15/2014	4.0	No change	No changes to the meaning, language, or formatting of the technical content.

# Contents

<b>1</b>	<b>Introduction</b>	<b>6</b>
1.1	Glossary	6
1.2	References	7
1.2.1	Normative References	7
1.2.2	Informative References	7
1.3	Overview	8
1.4	Relationship to Protocols and Other Structures	8
1.5	Applicability Statement	8
1.6	Versioning and Localization	9
1.7	Vendor-Extensible Fields	9
<b>2</b>	<b>Structures</b>	<b>10</b>
2.1	MMPE	10
2.1.1	Artist Properties	10
2.1.1.1	artistAlbumArtist	10
2.1.1.2	artistPerformer	10
2.1.1.3	artistConductor	11
2.1.2	Author Properties	11
2.1.2.1	authorComposer	11
2.1.2.2	authorOriginalLyricist	11
2.1.2.3	authorWriter	12
2.1.3	Ratings Properties	12
2.1.3.1	userRating	12
2.1.3.2	userEffectiveRating	12
2.1.3.3	userRatingInStars	12
2.1.3.4	userEffectiveRatingInStars	13
2.1.4	serviceProvider	13
2.1.5	sourceURL	13
2.1.6	year	13
2.1.7	folderPath	14
2.1.8	fileIdentifier	14
2.2	MCEF	14
2.2.1	Compatibility Flag Values and Behaviors	15
2.2.1.1	WMC_COMPAT_EXCLUDE_HTTP	15
2.2.1.2	WMC_COMPAT_EXCLUDE_RTSP	15
2.2.1.3	WMC_COMPAT_EXCLUDE_DLNA	16
2.2.1.4	WMC_COMPAT_EXCLUDE_DLNA_1_5	17
2.2.1.5	WMC_COMPAT_EXCLUDE_PCMPARAMS	17
2.2.1.6	WMC_COMPAT_EXCLUDE_WMDRMND	18
2.2.1.7	WMC_COMPAT_INCLUDE_RTSP_FOR_VIDEO	18
2.2.1.8	WMC_COMPAT_EXCLUDE_WMALOSSLESS_NONTRANSCODED	18
2.2.1.9	WMC_COMPAT_EXCLUDE_SEARCH	18
2.2.1.10	WMC_COMPAT_DO_NOT_LIMIT_RESPONSE_SIZE	18
2.2.1.11	WMC_COMPAT_EXCLUDE_VIDEO_TRANSCODING	19
2.2.1.12	WMC_COMPAT_PLAYLIST_FAKECHILDCCOUNT	19
2.2.1.13	WMC_COMPAT_EXCLUDE_NONPCM_AUDIO_TRANSCODING	19
2.2.1.14	WMC_COMPAT_EXCLUDE_TRANSCODING_TO_MPEG2	19
2.2.1.15	WMC_COMPAT_EXCLUDE_RES_FILTERING	19
2.3	MPME	20
2.3.1	Magic Packets	20

2.3.1.1	microsoft:magicPacketWakeSupported .....	20
2.3.1.2	microsoft:magicPacketSendSupported .....	20
2.4	Microsoft ProtocolInfo Extensions .....	20
2.4.1	PlayToApp Extension .....	20
<b>3</b>	<b>Structure Examples .....</b>	<b>22</b>
3.1	MMPE Examples .....	22
3.1.1	Artist Properties Tags .....	22
3.1.2	Author Properties Tags .....	22
3.1.3	Ratings Properties Tags .....	22
3.1.4	serviceProvider Property Tag .....	22
3.1.5	year Property Tag .....	23
3.1.6	folderPath Property Tag .....	23
3.1.7	fileIdentifier Property Tag .....	23
3.2	MCEF Examples .....	23
3.2.1	X_DeviceCaps Example .....	23
3.3	MPME Examples .....	24
3.3.1	magicPacketWakeSupported .....	24
3.3.2	magicPacketSendSupported .....	24
3.4	Microsoft ProtocolInfo Extensions Examples .....	24
3.4.1	PlayToApp Extension .....	24
<b>4</b>	<b>Security Considerations .....</b>	<b>26</b>
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>27</b>
<b>6</b>	<b>Change Tracking .....</b>	<b>28</b>
<b>7</b>	<b>Index .....</b>	<b>29</b>

# 1 Introduction

This document defines the **Microsoft Media Property Extensions (MMPE)**, the **Microsoft Compatibility Extension Flags (MCEF)**, the **Microsoft Power Management Extensions (MPME)**, and the Microsoft ProtocolInfo Extensions. These flags and extensions extend the **Universal Plug and Play (UPnP)** interoperability guidelines, as specified by the UPnP Forum [\[UPnP\]](#) and used by the **Digital Living Network Alliance (DLNA)** [\[DLNA\]](#).

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Hypertext Transfer Protocol (HTTP)**  
**Universal Plug and Play (UPnP)**  
**UTF-8**  
**XML**

The following terms are specific to this document:

**device description document (DDD):** A document used to specify device information and its capabilities, as described in the **UPnP** standard [\[UPnP\]](#).

**digital item declaration language (DIDL-Lite):** A subset of the Digital Item Declaration Language (DIDL), which is an **XML** dialect developed within ISO/MPEG21 [\[MPEG-21\]](#).

**Digital Living Network Alliance (DLNA):** A cross-industry organization of leading consumer electronics, computing industry, and mobile device companies, which are focused on delivering [interoperability guidelines](#), based upon open industry standards, in order to complete the cross-industry digital convergence.

**digital media player (DMP):** A Device Class that is defined in the **DLNA guidelines**. A **DMP** implements an **UPnP** AV control point that issues actions to a **DMS** with unexposed **DMR** functionality.

**digital media reader (DMR):** A Device Class that is defined in the **DLNA guidelines**. A **DMR** is a **UPnP** Device that implements the **UPnP** MediaRenderer Device type.

**digital media server (DMS):** A Device Class that is defined in the **DLNA guidelines**. A **DMS** is a **UPnP** Device that implements the **UPnP** MediaServer Device type.

**DLNA guidelines:** The DLNA Networked Device Interoperability Guidelines [\[DLNA\]](#) consist of three volumes that provide vendors with the information required to build interoperable networked platforms and devices for the digital home, including architecture and protocols, profiles for media formats, and link protection.

**Microsoft Compatibility Extension Flags (MCEF):** Flags provided by **DMRs** and **DMPs** to filter specific **res** elements exposed to these devices.

**Microsoft Media Property Extensions (MMPE):** Additional metadata properties that describe a media item that further enriches the metadata properties defined by [\[UPnP\]](#).

**Microsoft Power Management Extensions (MPME):** XML tags used to communicate the devices support of magic packets.

**Microsoft ProtocolInfo Extensions:** Extensions to the **ProtocolInfo** syntax, defined by Microsoft.

**ProtocolInfo:** As specified in [\[UPNPNMGR\]](#) section 2.5.2.

**Real-Time Streaming Protocol (RTSP):** As specified in [\[RFC2326\]](#).

**res:** Identifies a resource. A resource is typically some type of a binary asset, such as a photo, song, video, etc. A **res** element contains an URI that identifies the resource.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[DLNA] Digital Living Network Alliance, "The DLNA Networked Device Interoperability Guidelines", <http://www.dlna.org/dlna-for-industry/about-dlna/guidelines>

**Note** There is a charge to download the specification.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3629] Yergeau, F., "UTF-8, A Transformation Format of ISO 10646", STD 63, RFC 3629, November 2003, <http://www.ietf.org/rfc/rfc3629.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[UPnP] UPnP Forum, "Standards", <http://www.upnp.org/standardizeddcps/default.asp>

[XML10] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Third Edition)", February 2004, <http://www.w3.org/TR/2004/REC-xml-20040204/>

### 1.2.2 Informative References

[MPEG-21] Various, "ISO/IEC 21000 - Multimedia framework (MPEG-21)", <http://www.upnp.org/schemas/av/didl-lite-v2.xsd>

[MS-DLNHND] Microsoft Corporation, "[Digital Living Network Alliance \(DLNA\) Networked Device Interoperability Guidelines: Microsoft Extensions](#)".

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[RFC2326] Schulzrinne, H., Rao, A., and Lanphier, R., "Real Time Streaming Protocol (RTSP)", RFC 2326, April 1998, <http://www.ietf.org/rfc/rfc2326.txt>

[UPNPARCH1] UPnP Forum, "UPnP Device Architecture 1.0", October 2008, <http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf>

[UPNPADS1] UPnP Forum, "ContentDirectory:1 Service Template Version 1.01", June 2002, <http://www.upnp.org/standardizeddcps/documents/ContentDirectory1.0.pdf>

[UPNPCNMGR] UPnP Forum, "ConnectionManager:1 Service Template Versions 1.01", June 2002, <http://www.upnp.org/standardizeddcps/documents/ConnectionManager1.0.pdf>

### 1.3 Overview

Microsoft Compatibility Extension Flags (MCEF) are used to request specific device behavior(s) to enhance interoperability among UPnP Devices. For example, device manufacturers can develop a UPnP capable network device in order to retrieve information about the media content that is exposed to the network by a **digital media server (DMS)**. Such a device is enabled to include the MCEFs in its **device description document (DDD)** or User-Agent Header in order to tailor the metadata attributes in the **XML** responses that are provided by the DMS during interaction for enhanced interoperability.

Microsoft Media Property Extensions (MMPE) are used to expose several media content properties that are defined by Microsoft. These properties are generally not expressible, or are difficult to express, with the existing UPnP metadata attributes. In order to provide the expected query results with the existing attributes, additional processing capabilities are required on the device. For example, by using the additional properties defined by Microsoft, the device is relieved of the "heavy-lifting" involved in generating similar results and is enabled to provide a richer media browsing experience to their users.

Microsoft Power Management Extensions (MPME) are used to expose UPnP Device capabilities for power management. For example, a UPnP Device can support sleep mode and accept wake requests from other UPnP Devices. At the same time, a UPnP Device can support waking other UPnP Devices.

The **Microsoft ProtocolInfo Extensions** are extensions to the **ProtocolInfo**, defined by Microsoft. For example, a **digital media reader (DMR)** can use the [PlayToApp extension \(section 2.4.1\)](#) to indicate that it supports a nonstandard URI scheme.

### 1.4 Relationship to Protocols and Other Structures

MMPE are extensions to the XML syntax called **DIDL-Lite**, which are defined in the UPnP ContentDirectory service specification. For more information, see [\[UPNPADS1\]](#) Appendix A.

MPME are extensions to the XML syntax for UPnP DDDs. The DDDs are defined in [\[UPNPARCH1\]](#) section 2.1.

MMPE, MCEF, and MPME can be used in implementations of the Digital Living Network Alliance (DLNA) Home Networked Device Interoperability Guidelines: Microsoft Extensions [\[MS-DLNHND\]](#).

### 1.5 Applicability Statement

The MMPE and MCEF are only applicable to implementations of the Microsoft Extensions to the Digital Living Network Alliance (DLNA) Home Networked Device Interoperability Guidelines [\[MS-DLNHND\]](#).



The MPME is only applicable to implementations of the Microsoft Extensions to the Digital Living Network Alliance (DLNA) Home Networked Device Interoperability Guidelines.

Implementations of the MMPE and/or MCEF and/or MPME are not required in order to interoperate with Windows. The Media Property and Compatibility Extensions enhance the Digital Living Network Alliance (DLNA) Home Networked Device Interoperability Guidelines and the Remote Media Streaming Initiation Protocol without breaking interoperability.

Implementers are recommended to consider whether or not the MMPE and/or MCEF and/or MPME are applicable to their scenarios in order to provide a richer multimedia experience.

## 1.6 Versioning and Localization

The MMPE, MCEF, and MPME do not support versioning.

The MMPE, MCEF, and MPME do not explicitly address localization. However, these Microsoft Extensions use the **UTF-8** character set, as specified in [\[DLNA\]](#) section 7.2.5.9 and [\[RFC3629\]](#).

## 1.7 Vendor-Extensible Fields

None.

## 2 Structures

This protocol references commonly used data types, as defined in [\[MS-DTYP\]](#).

### 2.1 MMPE

Each MMPE is a property that describes a media item, where all but one of the properties can be included in a DIDL-Lite XML document. In the case of the property that is not included, the name of the property is used as the name of an XML tag that is included within a <desc> XML tag, which itself is included within an <item> tag that contains all of the tags associated with the media item.

The properties can also be specified as input parameters to the UPnP ContentDirectory [\[UPNPCDS1\]](#) service Search and Browse actions, wherever those actions allow properties to be used. For example, the ContentDirectory service Search action allows property names to be used to formulate a search query.

- The sourceURL property (section [2.1.5](#)) cannot appear in DIDL-Lite
- The XML tags MUST follow the syntax rules for XML defined in [\[XML10\]](#). Unless otherwise specified, any characters in the value of an XML tag MUST be escaped, using the XML escaping mechanism defined in [\[XML10\]](#) section 2.4.
- The syntax of each tag is specified using ABNF [\[RFC5234\]](#).

#### 2.1.1 Artist Properties

A group of XML properties that supports various artist roles, which is included in the multimedia content, such as album artist, performer (also known as a contributing artist), and conductor. Support for the artist properties enables devices to provide results for queries such as "browse by performer, and then find albums by the selected performer".

##### 2.1.1.1 artistAlbumArtist

This property specifies the name of an artist that is listed on the album when the media item is part of an album (i.e., a music album). For some albums, the name of the album artist can differ from the name of the artist of individual songs.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:artistAlbumArtist"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

##### 2.1.1.2 artistPerformer

This property specifies the name of a performing artist that is associated with the media item.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:artistPerformer"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### **2.1.1.3 artistConductor**

This property specifies the name of a conductor (typically, a musical conductor) that is associated with the media item.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:artistConductor"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

## **2.1.2 Author Properties**

A group of properties that supports various roles that one or more authors can have in multimedia content: Composer, Original Lyricist, or Writer. Support for the Author attributes enables devices to provide results for queries such as "browse by composer, and then find genres for the selected composer".

### **2.1.2.1 authorComposer**

Specifies the name of a composer (typically, a musical composer) that is associated with the media item.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:authorComposer"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### **2.1.2.2 authorOriginalLyricist**

This property specifies the name of a person who created the original lyrics of the media item.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:authorOriginalLyricist"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### 2.1.2.3 authorWriter

This property specifies the name of a person who is considered the writer of the media item.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:authorWriter"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### 2.1.3 Ratings Properties

The Ratings properties support metadata that is supplied from both the user and from the metadata provider. These properties allow devices to provide "prioritized" or "scoped" results to end users based on their preferences. This enables a user, for example, to choose to browse only musical content that has been rated at "5 or more stars".

There are four Ratings-related properties:

- [userRating](#) and [userEffectiveRating](#) represent the user rating (if present) and an automatic rating, respectively. The values of the userRating and userEffectiveRating properties are expressed as a number, in the range between 0 and 99, inclusive.
- [userRatingInStars](#) and [userEffectiveRatingInStars](#) represent the same information as userRating and userEffectiveRating, respectively. The values of the userRatingInStars and userEffectiveRatingInStars properties are expressed as a number, in the range between 0 and 5, inclusive.

At most, one instance of each property is allowed.

#### 2.1.3.1 userRating

The syntax of the property is defined as follows:

PropertyName = "microsoft:userRating"; UTF-8

PropertyValue = 1\*2DIGIT; unsigned integer ranges from 0 to 99

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.3.2 userEffectiveRating

The syntax of the property is defined as follows:

PropertyName = "microsoft:userEffectiveRating"; UTF-8

PropertyValue = 1\*2DIGIT; unsigned integer ranges from 0 to 99

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.3.3 userRatingInStars

The syntax of the property is defined as follows:

PropertyName = "microsoft:userRatingInStars"; UTF-8

PropertyValue = "0" / "1" / "2" / "3" / "4" / "5"; unsigned integer ranges from 0 to 5

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.3.4 userEffectiveRatingInStars

The syntax of the property is defined as follows:

PropertyName = "microsoft:userEffectiveRatingInStars"; UTF-8

PropertyValue = "0" / "1" / "2" / "3" / "4" / "5"; unsigned integer ranges from 0 to 5

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.4 serviceProvider

The serviceProvider property represents the name of the distributor of the media item. The serviceProvider property allows devices to return results categorized by the entity that provided the content.

Multiple instances of this property are allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:serviceProvider"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.5 sourceURL

The sourceURL property supports the grouping of results by file system path, which enables a device to group media files by parent folder. For example, the device can return results that enumerate all of the pictures in the "January Ski Trip to Canada" folder.

**Note** The use of the "ParentID" attribute can provide results similar to sourceURL, but only for a container hierarchy that replicates the file system hierarchy.

At most, one instance of each property is allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:sourceURL"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

#### 2.1.6 year

The year property enables the organization of multimedia content based solely on year, whereas the commonly-used "dc:date" UPnP property provides the whole date. For example, use of the year property enables a device to more easily return results for all of the pictures taken in "2006".

The syntax of the property is defined as follows:

PropertyName = "microsoft:year"; UTF-8

PropertyValue = 4DIGIT; unsigned integer, format YYYY

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### 2.1.7 folderPath

The folderPath property represents a folder path to the media item, relative to a root folder.

At most, one instance of each property is allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:folderPath"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

### 2.1.8 fileIdentifier

The fileIdentifier property is obtained from the media file. The property is assigned by the creator of the media file. [<1>](#)

For example, if the same file is shared by two different DMS implementations, although the value of the "id" attribute on the "item" property can be different on each DMS, the value of the fileIdentifier property is the same, since the value is obtained from the file itself.

At most, one instance of each property is allowed.

The syntax of the property is defined as follows:

PropertyName = "microsoft:fileIdentifier"; UTF-8

PropertyValue = ALPHA; UTF-8

MMPE = "<" PropertyName ">" PropertyValue "</" PropertyName ">";

## 2.2 MCEF

MCEFs are used to define specific behavior(s) for a particular device in order to enhance interoperability. The flags can be provided by a **DMP**, or digital media reader (DMR) via its User-Agent header, as described in [\[MS-DLNHND\]](#) or its DDD, as defined in [\[UPNPARCH1\]](#) section 2.1. To provide the flag, the device **MUST** specify the Microsoft-defined microsoft:X\_DeviceCaps tag within the Device node of the DDD, as shown in section [3.2.1](#). The syntax to follow for this tag is specified using ABNF [\[RFC5234\]](#), as follows:

**CompatibilityFlag**= 1\*DIGIT; it is the decimal numerical representation of the bitwise-OR operation among the hexadecimal flags used, as defined in section [2.2.1](#);

```
<microsoft:X_DeviceCaps xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0"/>CompatibilityFlag</microsoft:X_DeviceCaps>
```

**Note** The Microsoft-defined microsoft:X\_DeviceCaps attribute does not change in any respect the manner regarding how DDDs are made available to other devices in the network as, described by [\[UPNPARCH1\]](#).

## 2.2.1 Compatibility Flag Values and Behaviors

Any flag value that is not documented in this section is considered reserved and SHOULD not be used.

### 2.2.1.1 WMC\_COMPAT\_EXCLUDE\_HTTP

This flag causes a DMS to exclude **res** and upnp:albumArtURI elements in the DIDL-Lite response of the Browse or Search UPnP actions that implement the **HTTP** protocol in their URLs, as specified in [\[UPnP\]](#).

**Value:** %x1

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse, ContentDirectory:Search, and ConnectionManager:GetProtocolInfo.

```
<res duration="0:03:20.000" bitrate="24000" protocolInfo="http-
get:*:audio/mpeg:DLNA.ORG_PN=MP3;DLNA.ORG_OP=01;DLNA.ORG_FLAGS=015000000000000000000000000000
00" sampleFrequency="44100" bitsPerSample="16" nrAudioChannels="2"
microsoft:codec="{00000055-0000-0010-8000-00AA00389B71}" xmlns:microsoft="urn:schemas-
microsoft-com:WMPNSS-1-
0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/0_ezI0OTI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFG
M0M5N30uMC40.mp3</res>
<upnp:albumArtURI dlna:profileID="JPEG_TN" xmlns:dlna="urn:schemas-dlna-org:metadata-1-
0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/ezI0OTI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFGM0
M5N30uMC40.jpg?albumArt=true,formatID=13</upnp:albumArtURI>
```

When this flag is specified, the value of the protocolInfo attribute, as defined in [\[UPNPCDS1\]](#) section 6, on res elements, only specifies non-HTTP transport-dependent formats. Any res element with a protocolInfo attribute whose value begins with an "http-get" MUST be excluded from the response. For more information regarding the syntax of the ProtocolInfo string, see [\[UPNPCNMGR\]](#).

**Note** This flag MUST NOT be used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_RTSP](#).

### 2.2.1.2 WMC\_COMPAT\_EXCLUDE\_RTSP

This flag causes a DMS to exclude res elements in the DIDL-Lite response of the Browse or Search UPnP actions that implement the **RTSP** protocol in their URLs, as specified by [\[UPnP\]](#). Elements in the DIDL-Lite response, as demonstrated in the following syntax block, MUST be removed with the use of this flag.

**Value:** %x2

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse, ContentDirectory:Search, and ConnectionManager:GetProtocolInfo.

```
<res duration="0:03:20.000" bitrate="24000" protocolInfo="rtsp-rtp-
udp:*:audio/mpeg:DLNA.ORG_PN=MP3;DLNA.ORG_OP=10;DLNA.ORG_FLAGS=831000000000000000000000000000
00;DLNA.ORG_MAXSP=5" sampleFrequency="44100" bitsPerSample="16" nrAudioChannels="2"
microsoft:codec="{00000055-0000-0010-8000-00AA00389B71}" xmlns:microsoft="urn:schemas-
microsoft-com:WMPNSS-1-
```

```
0/">rtsp://127.0.0.1:554/WMPNSSv4/2815481477/0_ezI00TI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFGM0M5N30uMC40.mp3</res>
```

A consequence of constructing the DIDL-Lite response as shown in this example is that the value of the protocolInfo attribute, as defined in [\[UPNPCDS1\]](#) section 6, on res elements MUST specify only non-RTSP transport-dependent formats. Any res element with a protocolInfo attribute whose value begins with "rtsp-rtp-udp" MUST be excluded from the response. For more information regarding the syntax of the ProtocolInfo string, see [\[UPNPCNMGR\]](#).

**Note** This flag MUST NOT be used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_HTTP](#) because at least one protocol (either HTTP or RTSP) SHOULD be enabled. This flag MUST NOT be used in combination with [WMC\\_COMPAT\\_INCLUDE\\_RTSP\\_FOR\\_VIDEO](#).

### 2.2.1.3 WMC\_COMPAT\_EXCLUDE\_DLNA

This flag causes a DMS to exclude all DLNA-defined attributes and parameters in the DIDL-Lite responses given by the Browse or Search UPnP actions, as specified by [\[UPnP\]](#).

**Value:** %x4

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse, ContentDirectory:Search, and ConnectionManager:GetProtocolInfo.

**Note** The dlna:profileID and xmlns:dlna attributes MUST NOT be included in the upnp:albumArtURI nodes.

```
<upnp:albumArtURI dlna:profileID="JPEG_SM" xmlns:dlna="urn:schemas-dlna-org:metadata-1-0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/0_ezI00TI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFGM0M5N30uMC40.jpg?albumArt=true</upnp:albumArtURI>
```

The following content feature flags MUST also be removed from the protocolInfo attribute, as defined in [\[UPNPCDS1\]](#) section 6, of res elements:

- DLNA.ORG\_PN
- DLNA.ORG\_OP
- DLNA.ORG\_PS
- DLNA.ORG\_CI
- DLNA.ORG\_FLAGS
- DLNA.ORG\_MAXSP

```
<res duration="0:03:20.000" bitrate="24000" protocolInfo="http-get:*:audio/mpeg:DLNA.ORG_PN=MP3;DLNA.ORG_OP=01;DLNA.ORG_FLAGS=0150000000000000000000000000" sampleFrequency="44100" bitsPerSample="16" nrAudioChannels="2" microsoft:codec="{00000055-0000-0010-8000-00AA00389B71}" xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/0_ezI00TI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFGM0M5N30uMC40.mp3</res>
```

Because some devices fall down if the string DLNA exists in the protocol response, the [WMC\\_COMPAT\\_EXCLUDE\\_DLNA\\_1\\_5](#) compatibility flag MUST be set to indicate that the specified



attributes have not been included in the upnp:albumArtURI and res nodes. Setting this compatibility flag causes the server to not include the DLNA string as specified in the XML response.

Moreover, because DLNA support is non-existent if the [WMC\\_COMPAT\\_INCLUDE\\_RTSP\\_FOR\\_VIDEO](#) flag has been set, it MUST be ignored. By setting this flag, RTSP-based URLs will be excluded from res nodes in the case of video content.

**Note** In order to preserve backwards compatibility, when the [WMC\\_COMPAT\\_EXCLUDE\\_RTSP](#) flag is included within the descriptor <desc> tag, it can be escaped as described in [\[MS-DLNHND\]](#) section 3.4.5.1.

In the case of the UPnP action ConnectionManager:GetProtocolInfo, all format support information MUST NOT contain protocol information that announces DLNA profiles, as specified in [\[DLNA\]](#).

```
http-get:*:audio/x-ms-wma:DLNA.ORG_PN=WMABASE
```

**Note** The XML tags can be escaped, as described in section [3.1](#) of this document, when this compatibility flag is used.

#### 2.2.1.4 WMC\_COMPAT\_EXCLUDE\_DLNA\_1\_5

This flag causes a DMS to map the DLNA Profile ID "MP3X" to "MP3", and to map the DLNA Profile IDs "WMVSPLL\_BASE" and "WMVSPML\_BASE" to "WMVMED\_BASE". In addition, this flag causes the DLNA Profile ID for any media item whose DLNA Profile ID begins with "WMDRM\_" to be omitted. When this flag is used, all URLs MUST have a file extension, such as ".mp3" for MP3 content and ".pcm" for LPCM content.

**Value:** %x8

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse, ContentDirectory:Search, and ConnectionManager:GetProtocolInfo.

```
<res duration="0:03:20.000" bitrate="24000" protocolInfo="http-  
get:*:audio/mpeg:DLNA.ORG_PN=MP3;DLNA.ORG_OP=01;DLNA.ORG_FLAGS=015000000000000000000000000000  
00" sampleFrequency="44100" bitsPerSample="16" nrAudioChannels="2"  
microsoft:codec="{00000055-0000-0010-8000-00AA00389B71}" xmlns:microsoft="urn:schemas-  
microsoft-com:WMPNSS-1-  
0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/1_ezI00TI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFG  
M0M5N30uMC40.mp3</res>
```

**Note** The XML tags can be escaped, as described in section [3.1](#) of this document, when this compatibility flag is used.

#### 2.2.1.5 WMC\_COMPAT\_EXCLUDE\_PCMPARAMS

This flag causes a DMS to exclude sample rate and channels information from the protocolInfo attribute in the res element for audio/L16 and audio/L8 MIME types.

**Value:** %x10

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

```
<res duration="0:03:20.000" bitrate="176400" protocolInfo="http-  
get:*:audio/L16;rate=44100;channels=2:DLNA.ORG_PN=LPCM;DLNA.ORG_OP=10;DLNA.ORG_CI=1;DLNA.ORG_  
FLAGS=01500000000000000000000000000000" sampleFrequency="44100" bitsPerSample="16"  
nrAudioChannels="2" microsoft:codec="{00000001-0000-0010-8000-00AA00389B71}"  
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-  
0/">http://127.0.0.1:10243/WMPNSSv4/2815481477/ezI0OTI3N0I5LUU2MUQtNDdEMi05MTI3LTJBNjFDOTFGMO  
M5N30uMC40?formatID=20</res>
```

### 2.2.1.6 WMC\_COMPAT\_EXCLUDE\_WMDRMND

This flag causes a DMS to not generate res tags where the URL requires the use of WMDRM-ND.

**Value:** %x20

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

### 2.2.1.7 WMC\_COMPAT\_INCLUDE\_RTSP\_FOR\_VIDEO

This flag causes a DMS to include res tags with RTSP-based URLs for video even if [WMC\\_COMPAT\\_EXCLUDE\\_RTSP](#) and/or [WMC\\_COMPAT\\_EXCLUDE\\_DLNA\\_1\\_5](#) are set.

**Value:** %x40

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

### 2.2.1.8 WMC\_COMPAT\_EXCLUDE\_WMALOSSLESS\_NONTRANSCODED

This flag causes a DMS to not generate res tags with URLs for non-transcoded WMA Lossless content. This flag MUST be ignored if used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_RES\\_FILTERING](#).

**Value:** %x80

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

### 2.2.1.9 WMC\_COMPAT\_EXCLUDE\_SEARCH

This flag causes the ContentDirectory:Search UPnP action to not be supported for this DMS. In order to accomplish this action, ContentDirectory:GetSearchCapabilities MUST NOT provide any search capabilities.

**Value:** %x100

**This flag affects the response of UPnP Actions:** ContentDirectory:Search and ContentDirectory:GetSearchCapabilities.

### 2.2.1.10 WMC\_COMPAT\_DO\_NOT\_LIMIT\_RESPONSE\_SIZE

This flag causes the DIDL-Lite responses to not be limited to 200 kB in size for these UPnP actions.

**Value:** %x400

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

#### **2.2.1.11 WMC\_COMPAT\_EXCLUDE\_VIDEO\_TRANSCODING**

This flag causes a DMS to not offer res tags with URLs that correspond to transcoded versions of video items. This flag **MUST** be ignored if used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_RES\\_FILTERING](#).

**Value:** %x800

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

#### **2.2.1.12 WMC\_COMPAT\_PLAYLIST\_FAKECHILDCOUNT**

This flag causes a value of "1" to be returned for the child count of playlists containers. This flag is used to counteract the reduction in performance caused by calculating the "real" child count for playlist container.

**Value:** %x1000

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

#### **2.2.1.13 WMC\_COMPAT\_EXCLUDE\_NONPCM\_AUDIO\_TRANSCODING**

This flag causes res tags with URLs that correspond to transcoded versions of audio items to not be offered, unless the res tag is for an audio item transcoded into LPCM. This flag **MUST** be ignored if used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_RES\\_FILTERING](#).

**Value:** %x2000

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

#### **2.2.1.14 WMC\_COMPAT\_EXCLUDE\_TRANSCODING\_TO\_MPEG2**

This flag causes res tags with URLs that correspond to transcoded versions of video items into the MPEG-2 format to not be offered. This flag **MUST** be ignored if used in combination with [WMC\\_COMPAT\\_EXCLUDE\\_RES\\_FILTERING](#).

**Value:** %x4000

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

#### **2.2.1.15 WMC\_COMPAT\_EXCLUDE\_RES\_FILTERING**

All DIDL-Lite responses from a DMS **MUST** contain all applicable transcoding res elements associated to the requested media.

**Value:** %x8000

**This flag affects the response of UPnP Actions:** ContentDirectory:Browse and ContentDirectory:Search.

## 2.3 MPME

MPMEs are used to signal support for specific behaviors for a particular device in order to enhance power management. The MPME XML tags can be provided by a DMR or a DMS in its DDD, as described in [\[UPNPARCH1\]](#) section 2.1. This section defines the MPME XML tags.

### 2.3.1 Magic Packets

This section defines MPME XML tags for indicating support for magic packets. For more information about magic packets, see [\[MS-DLNHND\]](#) section 2.2.5.

#### 2.3.1.1 microsoft:magicPacketWakeSupported

This is an XML tag that a UPnP device provides in its DDD to announce that it can be awakened by the use of a magic packet. [<2>](#)

For more information about the syntax of magic packet, see [\[MS-DLNHND\]](#) section 2.2.5.

An UPnP device MUST only provide this information if it implements a low power mode of operation.

An UPnP device that can be woken from a low power mode MUST provide the following tag in its DDD:

flag = "1" / "0"; true or false, respectively.

```
<microsoft:magicPacketWakeSupported xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0">flag</microsoft:magicPacketWakeSupported>
```

#### 2.3.1.2 microsoft:magicPacketSendSupported

This is an XML tag that a UPnP device provides in its DDD to announce whether the device is able to wake a sleeping UPnP device. [<3>](#) The following syntax shows how the element is used to announce this capability.

flag = "1" / "0"; true or false respectively.

```
<microsoft:magicPacketSendSupported xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0">flag</microsoft:magicPacketSendSupported>
```

## 2.4 Microsoft ProtocolInfo Extensions

The Microsoft ProtocolInfo Extensions extend the syntax of the ProtocolInfo syntax element, as described in [\[UPNPCNMGR\]](#) section 2.5.2.

### 2.4.1 PlayToApp Extension

The PlayToApp ProtocolInfo extension can be used by DMR devices to specify support for additional URI schemes beyond those defined in [\[UPNPCNMGR\]](#) sections 5.1.1 through 5.1.4. [<4>](#)

The PlayToApp ProtocolInfo extension adheres to the extension mechanism for ProtocolInfo as defined in [\[UPNPCNMGR\]](#) section 5.1.5.

The syntax of the extension is defined as follows:

CustomURIScheme = 1\*( ALPHA / DIGIT / "-" )

Protocol = "microsoft.com"

Network = "\*"

ContentFormat = "application/vnd.ms-playtoapp;target=" DQUOTE CustomURIScheme DQUOTE

AdditionalInfo = "\*"

PlayToApp = Protocol ":" Network ":" ContentFormat ":" AdditionalInfo

## 3 Structure Examples

### 3.1 MMPE Examples

In order to preserve backwards compatibility, XML tags inside the descriptor <desc> tag can be escaped. For more information, refer to [\[MS-DLNHND\]](#) section 3.4.5.1. For example, "<microsoft:artistAlbumArtist>" can appear as "&lt;microsoft:artistAlbumArtist&gt;" in the XML response.

#### 3.1.1 Artist Properties Tags

The following is an example of the usage of the Artist properties in an XML response:

```
<desc id="Artist" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:artistAlbumArtist>Album</microsoft:artistAlbumArtist>
  <microsoft:artistPerformer>Performer</microsoft:artistPerformer>
  <microsoft:artistConductor>Conductor</microsoft:artistConductor>
</desc>
```

#### 3.1.2 Author Properties Tags

The following is an example of the usage of the Author properties in an XML response:

```
<desc id="Author" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:authorComposer>Composer</microsoft:authorComposer>
  <microsoft:authorOriginalLyricist>Lyricist</microsoft:authorOriginalLyricist>
  <microsoft:authorWriter>Writer</microsoft:authorWriter>
</desc>
```

#### 3.1.3 Ratings Properties Tags

The following is an example of the usage of the Ratings properties in an XML response:

```
<desc id="UserRating" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:userRating>50</microsoft:userRating>
  <microsoft:userEffectiveRating>60</microsoft:userEffectiveRating>
  <microsoft:userRatingInStars>3</microsoft:userRatingInStars>
  <microsoft:userEffectiveRatingInStars>3</microsoft:userEffectiveRatingInStars>
</desc>
```

#### 3.1.4 serviceProvider Property Tag

The following is an example of the usage of the serviceProvider property in an XML response:

```
<desc id="ServiceProvider" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:serviceProvider>Service Provider</microsoft:serviceProvider>
</desc>
```

### 3.1.5 year Property Tag

The following is an example of the usage of the year property in an XML response:

```
<desc id="Year" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:year>2004</microsoft:year>
</desc>
```

### 3.1.6 folderPath Property Tag

The following is an example of the usage of the folderPath property in an XML response: [<5>](#)

```
<desc id="folderPath" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:folderPath>Audio\Songs</microsoft:folderPath>
</desc>
```

### 3.1.7 fileIdentifier Property Tag

The following is an example of the usage of the fileIdentifier property (section [2.1.8](#)) in an XML response:

```
<desc id="fileInfo" namespace="urn:schemas-microsoft-com:WMPNSS-1-0/"
xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0/">
  <microsoft:fileIdentifier>AMGt_id=T 821854;AMGp_id=P 4744;AMGa_id=R
78327;X_id={5E8A0C00-0500-11DB-89CA-0019B92A3933};XA_id={F7310100-0400-11DB-89CA-
0019B92A3933};XAP_id={88120000-0600-11DB-89CA-0019B92A3933}</microsoft:fileIdentifier>
</desc>
```

## 3.2 MCEF Examples

### 3.2.1 X\_DeviceCaps Example

Device compatibility flags are specified in a DDD by using the following format:

```
<device>
  <UDN>uuid:00000000-1111-2222-3333-444444444444</UDN>
  <friendlyName>Sample Renderer</friendlyName>
  <deviceType>urn:schemas-upnp-org:device:MediaRenderer:1</deviceType>
  <manufacturer>Microsoft</manufacturer>
  ...
  <microsoft:X_DeviceCaps xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-
0">94</microsoft:X_DeviceCaps>
</device>
```

Use of microsoft:X\_DeviceCaps requires that the Microsoft XML namespace (urn:schemas-microsoft-com:WMPNSS-1-0) be specified in the DDD. The value for microsoft:X\_DeviceCaps is given in decimal and represents a bitwise OR combination of the individual compatibility flag values described in section [2.2](#). In this example, the value of "94" for microsoft:X\_DeviceCaps indicates the following compatibility flags:

- [WMC COMPAT EXCLUDE RTSP](#)
- [WMC COMPAT EXCLUDE DLNA](#)
- [WMC COMPAT EXCLUDE DLNA 1 5](#)
- [WMC COMPAT EXCLUDE PCMPARAMS](#)
- [WMC COMPAT INCLUDE RTSP FOR VIDEO](#)

### 3.3 MPME Examples

#### 3.3.1 magicPacketWakeSupported

The following example shows a DDD that announces that the UPnP device supports [microsoft:magicPacketWakeSupported](#) (section [2.3.1.1](#)). [<6>](#)

```
<device>
  <UDN>uuid:00000000-1111-2222-3333-444444444444</UDN>
  <friendlyName>Sample Renderer</friendlyName>
  <deviceType>urn:schemas-upnp-org:device:MediaRenderer:1</deviceType>
  <manufacturer>Microsoft</manufacturer>
  ...
  <microsoft:magicPacketWakeSupported
    xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0">1
  </microsoft:magicPacketWakeSupported>
</device>
```

#### 3.3.2 magicPacketSendSupported

The following example shows a DDD that announces that the UPnP device supports [microsoft:magicPacketSendSupported](#) (section [2.3.1.2](#)). [<7>](#)

```
<device>
  <UDN>uuid:00000000-1111-2222-3333-444444444444</UDN>
  <friendlyName>Sample Renderer</friendlyName>
  <deviceType>urn:schemas-upnp-org:device:MediaRenderer:1</deviceType>
  <manufacturer>Microsoft</manufacturer>
  ...
  <microsoft:magicPacketSendSupported
    xmlns:microsoft="urn:schemas-microsoft-com:WMPNSS-1-0">1
  </microsoft:magicPacketSendSupported>
</device>
```

### 3.4 Microsoft ProtocolInfo Extensions Examples

#### 3.4.1 PlayToApp Extension

The following example shows a ProtocolInfo string (section [2.4.1](#)) that a DMR device can include in its SinkProtocolInfo state variable ([\[UPNPENMGR\]](#) section 2.2.2) to declare that it supports playing media using the "example://" URI schemes.



microsoft.com:\*:application/vnd.ms-playtoapp;target="example":\*

## 4 Security Considerations

The MMPE and MCEF do not introduce any new security considerations beyond those that already apply to XML-based formats. Therefore, the same security considerations that pertain to the UPnP and **DLNA guidelines** also apply.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Windows Vista operating system
- Windows 7 operating system
- Windows Home Server 2011 server software
- Windows 8 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.8:](#) The `Microsoft:fileIdentifier` XML tag is not supported in Windows Vista, Windows 7, and Windows Home Server 2011.

[<2> Section 2.3.1.1:](#) The `microsoft:magicPacketWakeSupported` XML tag is not supported in Windows Vista.

[<3> Section 2.3.1.2:](#) The `microsoft:magicPacketSendSupported` XML tag is not supported in Windows Vista.

[<4> Section 2.4.1:](#) The PlayToApp ProtocolInfo extension is not supported in Windows Vista, Windows 7, Windows Home Server 2011, and Windows 8.

[<5> Section 3.1.6:](#) The FolderPath XML tag is not supported in Windows Vista.

[<6> Section 3.3.1:](#) The `microsoft:magicPacketWakeSupported` XML tag is not supported in Windows Vista.

[<7> Section 3.3.2:](#) The `microsoft:magicPacketSendSupported` XML tag is not supported in Windows Vista.

## 6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 7 Index

### A

[Applicability](#) 8  
[Artist properties](#) 10  
[Artist properties tags example](#) 22  
[artistAlbumArtist properties](#) 10  
[artistConductor properties](#) 11  
[artistPerformer properties](#) 10  
[Author properties](#) 11  
[Author properties tags example](#) 22  
[authorComposer properties](#) 11  
[authorOriginalLyricist properties](#) 11  
[authorWriter properties](#) 12

### C

[Change tracking](#) 28  
[Common data types and fields](#) 10  
[Compatibility flags - values and behaviors](#) 15

### D

[Data types and fields - common](#) 10  
Details  
[artist properties](#) 10  
[artistAlbumArtist properties](#) 10  
[artistConductor properties](#) 11  
[artistPerformer properties](#) 10  
[author properties](#) 11  
[authorComposer properties](#) 11  
[authorOriginalLyricist properties](#) 11  
[authorWriter properties](#) 12  
[common data types and fields](#) 10  
[compatibility flags - values and behaviors](#) 15  
[fileIdentifier property](#) 14  
[flags - values and behaviors](#) 15  
[folderPath properties](#) 14  
[magic packets](#) 20  
[MCEF property](#) 14  
[microsoft:magicPacketSendSupported tag](#) 20  
[microsoft:magicPacketWakeSupported tag](#) 20  
[MMPE property](#) 10  
[MPME property](#) 20  
[ratings properties](#) 12  
[serviceProvider properties](#) 13  
[sourceURL properties](#) 13  
[userEffectiveRating properties](#) 12  
[userEffectiveRatingInStars properties](#) 13  
[userRating properties](#) 12  
[userRatingInStars properties](#) 12  
[WMC COMPAT DO NOT LIMIT RESPONSE SIZE flag](#) 18  
[WMC COMPAT EXCLUDE DLNA flag](#) 16  
[WMC COMPAT EXCLUDE DLNA 1\\_5 flag](#) 17  
[WMC COMPAT EXCLUDE HTTP flag](#) 15  
[WMC COMPAT EXCLUDE NONPCM AUDIO TRANSCODING flag](#) 19  
[WMC COMPAT EXCLUDE PCMPARAMS flag](#) 17

[WMC COMPAT EXCLUDE RES FILTERING flag](#) 19  
[WMC COMPAT EXCLUDE RTSP flag](#) 15  
[WMC COMPAT EXCLUDE SEARCH flag](#) 18  
[WMC COMPAT EXCLUDE TRANSCODING TO MP EG2 flag](#) 19  
[WMC COMPAT EXCLUDE VIDEO TRANSCODING flag](#) 19  
[WMC COMPAT EXCLUDE WMALOSSLESS NONT RANSCODED flag](#) 18  
[WMC COMPAT EXCLUDE WMDRMND flag](#) 18  
[WMC COMPAT INCLUDE RTSP FOR VIDEO flag](#) 18  
[WMC COMPAT PLAYLIST FAKECHILDCOUNT flag](#) 19  
[year properties](#) 13

### E

Examples  
[artist properties tags](#) 22  
[author properties tags](#) 22  
[fileIdentifier property tag](#) 23  
[folderPath property tag](#) 23  
[magicPacketSendSupported](#) 24  
[magicPacketWakeSupported](#) 24  
[MMPE](#) 22  
[ratings properties tags](#) 22  
[serviceProvider property tag](#) 22  
[X\\_DeviceCaps](#) 23  
[year property tag](#) 23

### F

[Fields - vendor-extensible](#) 9  
[fileIdentifier property](#) 14  
[fileIdentifier property tag example](#) 23

#### Flags

[values and behaviors](#) 15  
[WMC COMPAT DO NOT LIMIT RESPONSE SIZE](#) 18  
[WMC COMPAT EXCLUDE DLNA](#) 16  
[WMC COMPAT EXCLUDE DLNA 1\\_5](#) 17  
[WMC COMPAT EXCLUDE HTTP](#) 15  
[WMC COMPAT EXCLUDE NONPCM AUDIO TRANSCODING](#) 19  
[WMC COMPAT EXCLUDE PCMPARAMS](#) 17  
[WMC COMPAT EXCLUDE RES FILTERING](#) 19  
[WMC COMPAT EXCLUDE RTSP](#) 15  
[WMC COMPAT EXCLUDE SEARCH](#) 18  
[WMC COMPAT EXCLUDE TRANSCODING TO MP EG2](#) 19  
[WMC COMPAT EXCLUDE VIDEO TRANSCODING](#) 19  
[WMC COMPAT EXCLUDE WMALOSSLESS NONT RANSCODED](#) 18  
[WMC COMPAT EXCLUDE WMDRMND](#) 18  
[WMC COMPAT INCLUDE RTSP FOR VIDEO](#) 18  
[WMC COMPAT PLAYLIST FAKECHILDCOUNT](#) 19

[folderPath properties](#) 14  
[folderPath property tag example](#) 23

## G

[Glossary](#) 6

## I

[Implementer - security considerations](#) 26

[Informative references](#) 7

[Introduction](#) 6

## L

[Localization](#) 9

## M

[Magic packets](#) 20

[magicPacketSendSupported example](#) 24

[magicPacketWakeSupported example](#) 24

[MCEF property](#) 14

[microsoft:magicPacketSendSupported tags](#) 20

[microsoft:magicPacketWakeSupported tags](#) 20

[MMPE example](#) 22

[MMPE property](#) 10

[MPME property](#) 20

## N

[Normative references](#) 7

## O

[Overview \(synopsis\)](#) 8

## P

[Packets - magic](#) 20

[PlayToApp extension](#) 20

[PlayToApp extension example](#) 24

[Product behavior](#) 27

Properties

[artist](#) 10

[artistAlbumArtist](#) 10

[artistConductor](#) 11

[artistPerformer](#) 10

[author](#) 11

[authorComposer](#) 11

[authorOriginalLyricist](#) 11

[authorWriter](#) 12

[compatibility flags - values and behaviors](#) 15

[fileIdentifier](#) 14

flags

[values and behaviors](#) 15

[WMC\\_COMPAT\\_DO\\_NOT\\_LIMIT\\_RESPONSE\\_SIZE](#) 18

[WMC\\_COMPAT\\_EXCLUDE\\_DLNA](#) 16

[WMC\\_COMPAT\\_EXCLUDE\\_DLNA\\_1\\_5](#) 17

[WMC\\_COMPAT\\_EXCLUDE\\_HTTP](#) 15

[WMC\\_COMPAT\\_EXCLUDE\\_NONPCM\\_AUDIO\\_TRANSCODING](#) 19

[WMC\\_COMPAT\\_EXCLUDE\\_PCMPARAMS](#) 17

[WMC\\_COMPAT\\_EXCLUDE\\_RES\\_FILTERING](#) 19

[WMC\\_COMPAT\\_EXCLUDE\\_RTSP](#) 15

[WMC\\_COMPAT\\_EXCLUDE\\_SEARCH](#) 18

[WMC\\_COMPAT\\_EXCLUDE\\_TRANSCODING\\_TO\\_MPEG2](#) 19

[WMC\\_COMPAT\\_EXCLUDE\\_VIDEO\\_TRANSCODING](#) 19

[WMC\\_COMPAT\\_EXCLUDE\\_WMALOSSLESS\\_NON\\_TRANSCODED](#) 18

[WMC\\_COMPAT\\_EXCLUDE\\_WMDRMND](#) 18

[WMC\\_COMPAT\\_INCLUDE\\_RTSP\\_FOR\\_VIDEO](#) 18

[WMC\\_COMPAT\\_PLAYLIST\\_FAKECHILDCOUNT](#)

19

[folderPath](#) 14

[MCEF](#) 14

[MMPE](#) 10

[MPME](#) 20

[ratings](#) 12

[serviceProvider](#) 13

[sourceURL](#) 13

[userEffectiveRating](#) 12

[userEffectiveRatingInStars](#) 13

[userRating](#) 12

[userRatingInStars](#) 12

[year](#) 13

[ProtocolInfo Extensions](#) 20

## R

[Ratings properties](#) 12

[Ratings properties tags example](#) 22

References

[informative](#) 7

[normative](#) 7

[Relationship to protocols and other structures](#) 8

## S

[Security - implementer considerations](#) 26

[serviceProvider properties](#) 13

[serviceProvider property tag example](#) 22

[sourceURL properties](#) 13

Structures

[MCEF property](#) 14

[MMPE property](#) 10

[MPME property](#) 20

[overview](#) 10

[ProtocolInfo Extensions](#) 20

## T

Tags

[magic packets](#) 20

[microsoft:magicPacketSendSupported](#) 20

[microsoft:magicPacketWakeSupported](#) 20

[Tracking changes](#) 28

## U

[userEffectiveRating\\_properties](#) 12  
[userEffectiveRatingInStars\\_properties](#) 13  
[userRating\\_properties](#) 12  
[userRatingInStars\\_properties](#) 12

## **V**

[Vendor-extensible\\_fields](#) 9  
[Versioning](#) 9

## **X**

[X\\_DeviceCaps\\_example](#) 23

## **Y**

[year\\_properties](#) 13  
[year\\_property\\_tag\\_example](#) 23