

[MS-WCFESAN]: WCF-Based Encrypted Server Administration and Notification Protocol

This topic lists the Errata found in [MS-WCFESAN] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V6.0 – 2015/10/16](#).

Errata Published*	Description
2016/03/21	<p>In this document, added new content for 3 operation contracts.</p> <p>Added new sections:</p> <p>2.2.4.11 Client Notification Service</p> <p>2.2.4.11.1 NotificationResult</p> <p>The NotificationResult type describes the notification result in the client notification service.</p> <pre><xs:complexType name="NotificationResult"> <xs:sequence> <xs:element minOccurs="0" name="clientName" nillable="true" type="xs:string" /> <xs:element minOccurs="0" name="result" type="xs:boolean" /> </xs:sequence> </xs:complexType></pre> <p>2.2.4.11.2 NotificationResults</p> <p>The NotificationResults type describes notification results in the client notification service.</p> <pre><xs:complexType name="NotificationResults"> <xs:sequence> <xs:list minOccurs="0" name="result" type="NotificationResult" /> </xs:sequence> </xs:complexType></pre> <p>...</p> <p>3.11.5.3 IClientNotificationProvider.NotifyClientByName</p> <p>The operation sends a notification message to a client by using the machine name.</p> <pre><wsdl:operation name="NotifyClientByName"> <wsdl:input wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByName" message="tns:IClientNotificationProvider_NotifyClientByName_InputMessage" /> <wsdl:output wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyClientByNameResponse" /></pre>

Errata Publishe d*	Description
	<pre data-bbox="409 304 1421 382">message="tns:IClientNotificationProvider_NotifyClientByName_OutputMessage" /> </wsdl:operation></pre> <p>3.11.5.3.1 Messages</p> <p>3.11.5.3.1.1 IClientNotificationProvider_NotifyClientByName_InputMessage</p> <p>This message is the request for the NotifyClientByName operation.</p> <pre data-bbox="409 593 1372 720"><wsdl:message name="IClientNotificationProvider_NotifyClientByName_InputMessage"> <wsdl:part name="parameters" element="tns:NotifyClientByName" /> </wsdl:message></pre> <p>The message MUST be sent with the following SOAP action: http://tempuri.org/IClientNotificationProvider/NotifyClientByName</p> <p>The body of the SOAP message MUST contain the NotifyClientByName element.</p> <p>3.11.5.3.1.2 IClientNotificationProvider_NotifyClientByName_OutputMessage</p> <p>This message is the response for the NotifyClientByName operation.</p> <pre data-bbox="409 994 1388 1121"><wsdl:message name="IClientNotificationProvider_NotifyClientByName_OutputMessage"> <wsdl:part name="parameters" element="tns:NotifyClientByNameResponse" /> </wsdl:message></pre> <p>The message MUST be sent with the following SOAP action: http://tempuri.org/ClientNotificationProvider/NotifyClientByNameResponse</p> <p>The body of the SOAP message MUST contain the NotifyClientByNameResponse element.</p> <p>3.11.5.3.2 Elements</p> <p>3.11.5.3.2.1 NotifyClientByName</p> <p>This element specifies input values for the NotifyClientByName operation.</p> <pre data-bbox="409 1438 1405 1755"><xss:element name="NotifyClientByName"> <xss:complexType> <xss:sequence> <xss:element minOccurs="0" name="name" nillable="true" type="xss:string" /> <xss:element minOccurs="0" name="messageId" type="xss:unsignedInt" /> <xss:element minOccurs="0" name="message" nillable="true" type="xss:string" /> </xss:sequence> </xss:complexType> </xss:element></pre> <p>3.11.5.3.2.2 NotifyClientByNameResponse</p> <p>This element specifies output values for the NotifyClientByName operation.</p>

Errata Publishe d*	Description
	<pre data-bbox="409 325 1209 530"><xs:element name="NotifyClientByNameResponse"> <xs:complexType> <xs:sequence> <xs:element minOccurs="0" name="NotifyClientByNameResult" type="xs:boolean" /> </xs:sequence> </xs:complexType> </xs:element></pre> <p data-bbox="360 587 1078 614">3.11.5.4 IClientNotificationProvider.NotifyClientId</p> <p data-bbox="360 620 1237 648">The operation sends a notification message to a client by using the machine SID.</p> <pre data-bbox="409 671 1421 1001"><wsdl:operation name="NotifyClientId"> <wsdl:input wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyClien ntById" message="tns:IClientNotificationProvider_NotifyClientId_InputMessage " /> <wsdl:output wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyClien tByIdResponse" message="tns:IClientNotificationProvider_NotifyClientId_OutputMessag e" /> </wsdl:operation></pre> <p data-bbox="360 1058 670 1085">3.11.5.4.1 Messages</p> <p data-bbox="360 1091 1274 1119">3.11.5.4.1.1 IClientNotificationProvider_NotifyClientId_InputMessage</p> <p data-bbox="360 1125 1041 1153">This message is the request for the NotifyClientId operation.</p> <pre data-bbox="409 1176 1348 1305"><wsdl:message name="IClientNotificationProvider_NotifyClientId_InputMessage"> <wsdl:part name="parameters" element="tns:NotifyClientId" /> </wsdl:message></pre> <p data-bbox="360 1362 1005 1389">The message MUST be sent with the following SOAP action:</p> <p data-bbox="551 1396 1225 1423">http://tempuri.org/IClientNotificationProvider/NotifyClientId</p> <p data-bbox="360 1429 1179 1457">The body of the SOAP message MUST contain the NotifyClientId element.</p> <p data-bbox="360 1463 1292 1491">3.11.5.4.1.2 IClientNotificationProvider_NotifyClientId_OutputMessage</p> <p data-bbox="360 1497 1054 1524">This message is the response for the NotifyClientId operation.</p> <pre data-bbox="409 1548 1364 1676"><wsdl:message name="IClientNotificationProvider_NotifyClientId_OutputMessage"> <wsdl:part name="parameters" element="tns:NotifyClientIdResponse" /> </wsdl:message></pre> <p data-bbox="360 1733 1005 1761">The message MUST be sent with the following SOAP action:</p> <p data-bbox="551 1767 1321 1795">http://tempuri.org/ClientNotificationProvider/NotifyClientIdResponse</p> <p data-bbox="360 1801 1279 1828">The body of the SOAP message MUST contain the NotifyClientIdResponse element.</p> <p data-bbox="360 1867 665 1894">3.11.5.4.2 Elements</p>

Errata Publishe d*	Description
	<p>3.11.5.4.2.1 NotifyClientId</p> <p>This element specifies input values for the NotifyClientId operation.</p> <pre data-bbox="409 382 1372 709"><xs:element name="NotifyClientId"> <xs:complexType> <xs:sequence> <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" /> <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" /> <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" /> </xs:sequence> </xs:complexType> </xs:element></pre>
	<p>3.11.5.4.2.2 NotifyClientIdResponse</p> <p>This element specifies output values for the NotifyClientId operation.</p> <pre data-bbox="409 878 1188 1100"><xs:element name="NotifyClientIdResponse"> <xs:complexType> <xs:sequence> <xs:element minOccurs="0" name="NotifyClientIdResult" type="xs:boolean" /> </xs:sequence> </xs:complexType> </xs:element></pre>
	<p>3.11.5 IClientNotificationProvider.NotifyAllClients</p> <p>The operation sends notification messages to all the online clients.</p> <pre data-bbox="409 1237 1421 1564"><wsdl:operation name="NotifyAllClients"> <wsdl:input wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyAllC lients" message="tns:IClientNotificationProvider_NotifyAllClients_InputMessage " /> <wsdl:output wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyAllCl ientsResponse" message="tns:IClientNotificationProvider_NotifyAllClients_OutputMessag e" /> </wsdl:operation></pre> <p>3.11.5.5.1 Messages</p> <p>3.11.5.5.1.1 IClientNotificationProvider_NotifyAllClients_InputMessage</p> <p>This message is the request for the NotifyAllClients operation.</p> <pre data-bbox="409 1765 1351 1881"><wsdl:message name="IClientNotificationProvider_NotifyAllClients_InputMessage"> <wsdl:part name="parameters" element="tns:NotifyAllClients" /></pre>

Errata Publishe d*	Description
	<pre data-bbox="551 302 771 329"></wsdl:message></pre> <p>The message MUST be sent with the following SOAP action: http://tempuri.org/IClientNotificationProvider/NotifyAllClients</p> <p>The body of the SOAP message MUST contain the NotifyAllClients element.</p> <p>3.11.5.5.1.2 IClientNotificationProvider_NotifyAllClients_OutputMessage</p> <p>This message is the response for the NotifyAllClients operation.</p> <pre data-bbox="409 608 1356 734"><wsdl:message name="IClientNotificationProvider_NotifyAllClients_OutputMessage"> <wsdl:part name="parameters" element="tns:NotifyAllClientsResponse" /> </wsdl:message></pre> <p>The message MUST be sent with the following SOAP action: http://tempuri.org/ClientNotificationProvider/NotifyAllClientsResponse</p> <p>The body of the SOAP message MUST contain the NotifyAllClientsResponse element.</p> <p>3.11.5.5.2 Elements</p> <p>3.11.5.5.2.1 NotifyAllClients</p> <p>This element specifies input values for the NotifyAllClients operation.</p> <pre data-bbox="409 1041 1241 1311"><xs:element name="NotifyAllClients"> <xs:complexType> <xs:sequence> <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" /> <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" /> </xs:sequence> </xs:complexType> </xs:element></pre> <p>3.11.5.5.2.2 NotifyAllClientsResponse</p> <p>This element specifies output values for the NotifyAllClients operation.</p> <pre data-bbox="409 1453 1258 1670"><xs:element name="NotifyAllClientsResponse"> <xs:complexType> <xs:sequence> <xs:element minOccurs="0" name="NotifyAllClientsResult" type="NotificationResults" /> </xs:sequence> </xs:complexType> </xs:element></pre>

*Date format: YYYY/MM/DD