

[MS-WKST]: Workstation Service Remote Protocol

This topic lists the Errata found in [MS-WKST] since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Protocol Document Version [V26.0 – 2015/10/16](#).

Errata Published*	Description												
2016/04/18	<p>In three sections, corrected the name used for a return value.</p> <p>In Section 3.2.4.1, NetrWkstaGetInfo (Opnum 0), changed from:</p> <p>Return Values: When the message processing result meets the description in column two of the following table, this method MUST return one of the following values ([MS-ERREF] section 2.2).</p> <table border="1" data-bbox="402 898 1458 1087"> <thead> <tr> <th>Return value/code</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>0x00000000 ERROR_SUCCESS</td> <td>The operation completed successfully.</td> </tr> <tr> <td>...</td> <td>...</td> </tr> </tbody> </table> <p>Changed to:</p> <p>Return Values: When the message processing result meets the description in column two of the following table, this method MUST return one of the following values ([MS-ERREF] section 2.2).</p> <table border="1" data-bbox="402 1255 1458 1444"> <thead> <tr> <th>Return value/code</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>0x00000000 NERR_Success</td> <td>The operation completed successfully.</td> </tr> <tr> <td>...</td> <td>...</td> </tr> </tbody> </table> <p>In Section 4.1, NetrWkstaGetInfo Example, changed from:</p> <pre> ... (type unsigned long) return_status = ERROR_SUCCESS NetrWkstaGetInfo ([in, string, unique] WKSSVC_IDENTIFY_HANDLE ServerName = {unchanged}, [in] unsigned long Level = {unchanged}, [out, switch_is(Level)] LPWKSTA_INFO WkstaInfo = {filled in as shown below}); </pre> <p>Changed to:</p>	Return value/code	Description	0x00000000 ERROR_SUCCESS	The operation completed successfully.	Return value/code	Description	0x00000000 NERR_Success	The operation completed successfully.
Return value/code	Description												
0x00000000 ERROR_SUCCESS	The operation completed successfully.												
...	...												
Return value/code	Description												
0x00000000 NERR_Success	The operation completed successfully.												
...	...												

Errata Published*	Description
	<pre data-bbox="386 283 1291 577"> ... (type unsigned long) return_status = NERR_Success NetrWkstaGetInfo ([in,string,unique] WKSSVC_IDENTIFY_HANDLE ServerName = {unchanged}, [in] unsigned long Level = {unchanged}, [out, switch_is(Level)] LPWKSTA_INFO WkstaInfo = {filled in as shown below}); </pre> <p data-bbox="386 619 1047 651">In Section 4.2, NetrWkstaUserEnum Example, changed from:</p> <p data-bbox="386 661 1437 787"> ... On receiving this method, the server executes the method locally to continue enumeration based on a ResumeHandle value of 0x00000120, and returns ERROR_SUCCESS. The server returns the names of the next three logged-on users in the UserInfo parameter. It also sets the value of TotalEntries to 0x00000005. The value of ResumeHandle is irrelevant. </p> <p data-bbox="386 829 527 861">Changed to:</p> <p data-bbox="386 871 1437 997"> ... On receiving this method, the server executes the method locally to continue enumeration based on a ResumeHandle value of 0x00000120, and returns NERR_Success. The server returns the names of the next three logged-on users in the UserInfo parameter. It also sets the value of TotalEntries to 0x00000005. The value of ResumeHandle is irrelevant. </p>

*Date format: YYYY/MM/DD